

MPN: MO-MGBIC-BX40-D

# SFP 1.25 Gbps, SMF, 40 km, LC, DOM support, Compatible with Extreme networks MGBIC-BX40-D

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- **\*\*100% Extreme Networks Compatible\*\***



## Specifications

<b>Features</b>	<b>Brand compatibility</b>	Extreme Networks
	<b>Certification</b>	MSA
	<b>Compatible products</b>	Extreme networks MGBIC-BX40-D
	<b>Easy to install</b>	Y
	<b>Form factor</b>	SFP
	<b>Plug and Play</b>	Y
	<b>RoHS compliance</b>	Y
<b>Operational conditions</b>	<b>Operating temperature (T-T)</b>	0-70 °C
<b>Package dimensions</b>	<b>Depth (package,cm)</b>	10 cm
	<b>Gross Weight (Package, kg)</b>	0.03 kg
	<b>Height (package,cm)</b>	3 cm
	<b>Width (package,cm)</b>	6 cm
<b>Performance</b>	<b>Cabling technology</b>	1000BASE-BX10-D
	<b>Ethernet interface type</b>	Gigabit Ethernet
	<b>Fiber cable diameters supported (core/cladding)</b>	9/125 µm
	<b>Fiber ethernet cabling technology</b>	1000BASE-BX
	<b>Fiber optic connector</b>	SFP
	<b>Maximum data transfer rate</b>	1000 Mbit/s
	<b>Maximum transfer distance</b>	40000 m
	<b>Rx wavelength (max)</b>	1310 nm
	<b>SFP transceiver standard</b>	BX-D
	<b>SFP transceiver type</b>	Fiber optic
	<b>Single-mode fiber (SMF) supported</b>	Y

<b>Performance</b>	<b>Tx wavelength (max)</b>	1490 nm
<b>Product dimensions</b>	<b>Net Weight (Product, kg)</b>	0.02 kg
	<b>Product Depth</b>	5.6 cm
	<b>Product Height</b>	1.6 cm
	<b>Product Width</b>	2 cm
<b>Vendor information</b>	<b>Brand Name</b>	MicroOptics
	<b>Warranty</b>	3 Year(s)

## Other images

