



MSI MPG A1000G PCIE5 virtalähdeyksikkö 1000 W 20+4 pin ATX ATX musta



Tuotemerkki : MSI

Tuotekoodi: MPG A1000G PCIE5

Tuotteen nimi : MPG A1000G PCIE5

MSI MPG A1000G PCIE5. Kokonaisteho: 1000 W, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 50 - 60 Hz. Emolevyn virtaliitin: 20+4 pin ATX, Emolevyn virtapiuhan pituus: 60 cm, SATA-virtakaapelin pituus: 500,650,700,850 mm. Tarkoitus: PC/palvelin, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS Gold. Tuotteen väri: musta, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 13,5 cm. Tuotteen leveys: 150 mm, Tuotteen syvyys: 150 mm, Tuotteen korkeus: 86 mm



| Power | | Ports & interfaces | |
|---|---|--|---------------|
| Total power * | 1000 W | EPS power connector (4+4 pin) | ✓ |
| AC input voltage * | 100 - 240 V | PCI Express power connectors (6+2 pin) | 6 |
| AC input frequency | 50 - 60 Hz | PCI Express power connectors (16-pin) | 1 |
| Power Factor Correction (PFC) type | Active | PCI Express power cable length | 75 cm |
| Combined power (+3.3V) | 120 W | Floppy disk drive connector | ✓ |
| Combined power (+12V) | 1000 W | Cabling type | Fully-Modular |
| Combined power (+5V) | 120 W | Performance | |
| Combined power (-12V) | 3.6 W | 80 PLUS certification * | 80 PLUS Gold |
| Combined power (+5Vsb) | 15 W | Purpose * | PC/Server |
| Max output current (+3.3V) | 22 A | Power supply unit (PSU) form factor * | ATX |
| Max output current (+12V) | 83.5 A | ATX version | 3.0 |
| Max output current (+5V) | 22 A | Bearing technology | FDB |
| Max output current (-12V) | 0.3 A | Design | |
| Max output current (+5Vsb) | 3 A | Product colour | Black |
| Efficiency | 90% | Cooling type | Active |
| Power protection features | Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage | Fan diameter | 13.5 cm |
| | | Number of fans | 1 fan(s) |
| | | Illumination | ✗ |
| Ports & interfaces | | Weight & dimensions | |
| Motherboard power connector * | 20+4 pin ATX | Width | 150 mm |
| Motherboard power cable length | 60 cm | Depth | 150 mm |
| Number of SATA power connectors | 12 | Height | 86 mm |
| SATA power cable length | 500,650,700,850 mm | Other features | |
| Peripheral (Molex) power connectors (4-pin) * | 4 | EPS cable length | 70 cm |
| Peripheral (Molex) power cable length | 1100,500,650,700,850 mm | | |
| EPS power connector (8-pin) | ✗ | | |



4719072972196

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date