




## FEATURES



### Supercharged with Gen 5

The PCIe Gen 5 controller empowers next-level storage transfer rates faster than previous-gen SSDs by up to 1.5 times.



### Aluminum Heatsink

Bronze-colored aluminum heatsink with a stacked fin structure maximizes performance under heavy loads.



### 3D NAND Flash

3D NAND Flash technology brings dense storage in a compact design and allows storage capacities up to 2TB.



### Security & Reliability

Built-in data security and error-correction capabilities extend the longevity of the NAND flash storage.



### Low Latency Gaming

Enjoy minimal latency in smooth gameplay and loading games with optimized high-performance bandwidth and throughput.



### Nonstop Creativity Booster

Keep up nonstop productivity by opening up images, movies, documents, and heavy-duty applications at lightning speeds.



### MSI Center

Migrate data with backup & restore functionality, monitor drive health and performance metrics in real-time in MSI Center.



### Optimal M.2 SSD

Designed in the M.2 2280 form factor, MSI SSDs are easy to install into external enclosures, desktops, or laptops.



### 5 Years Warranty

MSI stands by the quality and reliability of their SSD's with a 5 year limited warranty.

## SPECIFICATIONS

<b>Model Name</b>	SPATIUM M570 PCIe 5.0 NVMe M.2 HS	
<b>Capacity</b>	1TB	2TB
<b>Controller</b>	PHISON E26	
<b>Flash Memory</b>	3D NAND	
<b>DRAM Cache</b>	2GB LPDDR4	4GB LPDDR4
<b>Form Factor</b>	M.2 2280	
<b>Interface</b>	PCIe Gen5x4, NVMe 2.0	
<b>Compatibility</b>	PCIe Gen5 / Gen4 / Gen3 / Gen2 / Gen1	
<b>Dimensions</b>	80.00mm (L) x 22.00mm (W) x 3.5mm (H) (w/o heatsink) 80.40mm (L) x 23.00mm (W) x 20.40mm (H) (w/ heatsink)	
<b>Sequential Read up to (MB/s)</b>	9,500	10,000
<b>Sequential Write up to (MB/s)</b>	8,500	10,000
<b>Random Read 4KB up to (IOPS)</b>	1,300,000	1,400,000
<b>Random Write 4KB up to (IOPS)</b>	1,500,000	
<b>Maximum Operating Power (W)</b>	10	11
<b>Operating Temperatures</b>	0°C - 70°C	
<b>Storage Temperatures</b>	-40°C - 85°C	
<b>Terabytes Written (TBW)</b>	700	1400
<b>Mean Time Between Failure (MTBF)</b>	Up to 1,600,000 Hours	
<b>Limited Warranty</b>	5 Years, or the coverage for the maximum TBW as stated, whichever comes first.	
<b>Advanced Features</b>	TRIM (Performance Optimization, OS Support required) SMART (Self-Monitoring, Analysis and Reporting Technology) LDPC (Low Density Parity Check) ECC Algorithm End to End Data Path Protection APST (Autonomous Power State Transition)	