ASUS PRIME H610M-K D4 ARGB Intel H610 LGA 1700 mikro ATX

Tuotemerkki: ASUS Tuotekoodi: 90MB1HN0-M0EAY0

Tuotteen nimi: PRIME H610M-K D4 ARGB

ASUS PRIME H610M-K D4 ARGB. Suoritinvalmistaja: Intel, Prosessorin kanta: LGA 1700, Yhteensopivat prosessorit: Intel® Celeron®, Intel® Pentium® Gold, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i5, Intel® Core™ Tuetut muistityypit: DDR4-SDRAM, Sisäinen enimmäismuisti: 64 GB, Muistipaikkojen tyyppi: DIMM. Tuetut tallennusasemaliitännät: M.2, SATA III, Tuetut tallennusasematyypit: HDD & SSD. Ethernetliitännän tyyppi: Gigabitti Ethernet. Komponentti (tuotteelle): PC, Emolevyn muototekijä: mikro ATX, Emolevyn piirisarjan perhe: Intel





Processor		Internal I/O	
Processor manufacturer *	Intel	12V power connector	✓
Processor socket *	LGA 1700	Rear panel I/O ports	
Compatible processor series *	Intel® Celeron®, Intel® Pentium® Gold, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9	USB 2.0 ports quantity *	4
Compatible processor series		USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2
Supported processor sockets	LGA 1700	Ethernet LAN (RJ-45) ports *	1
Memory		PS/2 ports quantity	1
Supported memory types *	DDR4-SDRAM	HDMI ports quantity *	1
Number of memory slots *	2	Microphone in	✓
Memory slots type	DIMM	Network	
Memory channels	Dual-channel	Ethernet LAN	√
ECC compatibility	Non-ECC	Ethernet interface type	Gigabit Ethernet
Supported memory clock speeds	3200,3000,2933,2800,2666,2400,2133 MHz	Wi-Fi *	X
Supported memory clock speed (max)	3200 MHz	Features	
(IIIax)			
Maximum internal memory *	64 GB	Motherboard chipset *	Intel H610
, ,	64 GB ✓	Motherboard chipset * Audio output channels *	Intel H610 7.1 channels
Maximum internal memory * Unbuffered memory		Audio output channels * Component for *	7.1 channels PC
Maximum internal memory * Unbuffered memory Storage controllers	/	Audio output channels * Component for * Motherboard form factor *	7.1 channels PC micro ATX
Maximum internal memory * Unbuffered memory Storage controllers Supported storage drive types	HDD & SSD	Audio output channels * Component for * Motherboard form factor * Motherboard chipset family *	7.1 channels PC
Maximum internal memory * Unbuffered memory Storage controllers	HDD & SSD	Audio output channels * Component for * Motherboard form factor *	7.1 channels PC micro ATX
Maximum internal memory * Unbuffered memory Storage controllers Supported storage drive types Supported storage drive interfaces Graphics Parallel processing technology	HDD & SSD * M.2, SATA III	Audio output channels * Component for * Motherboard form factor * Motherboard chipset family * Windows operating systems	7.1 channels PC micro ATX Intel
Maximum internal memory * Unbuffered memory Storage controllers Supported storage drive types Supported storage drive interfaces Graphics	HDD & SSD	Audio output channels * Component for * Motherboard form factor * Motherboard chipset family * Windows operating systems supported	7.1 channels PC micro ATX Intel
Maximum internal memory * Unbuffered memory Storage controllers Supported storage drive types Supported storage drive interfaces Graphics Parallel processing technology	HDD & SSD * M.2, SATA III	Audio output channels * Component for * Motherboard form factor * Motherboard chipset family * Windows operating systems supported Expansion slots	7.1 channels PC micro ATX Intel Windows 10 x64, Windows 11
Maximum internal memory * Unbuffered memory Storage controllers Supported storage drive types Supported storage drive interfaces Graphics Parallel processing technology support *	HDD & SSD * M.2, SATA III	Audio output channels * Component for * Motherboard form factor * Motherboard chipset family * Windows operating systems supported Expansion slots PCI Express x1 (Gen 3.x) slots	7.1 channels PC micro ATX Intel Windows 10 x64, Windows 11

Internal I/O		BIOS	
Number of SATA III connectors *	4	BIOS type *	UEFI AMI
S/PDIF out connector	✓	BIOS memory size	128 Mbit
Audio connector	✓	Packaging data	
Front panel audio connector	✓	Package width	270 mm
ATX Power connector (24-pin)	✓	Package depth	263 mm
CPU fan connector	✓	Package height	51.5 mm
Number of chassis fan connectors	1	Package weight	800 g
EPS power connector (8-pin)	✓	Weight & dimensions	
Number of COM connectors	1	Width	234 mm
TPM connector	✓	Depth	203 mm
		Packaging content	
		Cables included	SATA



4711387460177

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.