



## Lindy USB 3.2 Gen 1 Hub and Gigabit Ethernet Converter

**Brand :** Lindy

**Product code:** 43379

**Product name :** USB 3.2 Gen 1 Hub and Gigabit Ethernet Converter

- Connects a USB 3.2 Type C or Type A computer to a Gigabit Ethernet network
- Provides three USB 3.2/3.1 Gen 1 / USB 3.0 Type A ports andnbsp;
- USB 3.2/3.1 Gen 1 / USB 3.0 SuperSpeed data transfer rates up to 5Gbps
- Supports 10/100/1000BASE-T, full and half duplex mode
- 2 year warranty

USB 3.2 Gen 1 Hub and Gigabit Ethernet Converter

Lindy USB 3.2 Gen 1 Hub and Gigabit Ethernet Converter. Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-A + Type-C, Hub interfaces: RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A. Data transfer rate: 5000 Mbit/s, Product colour: Grey, Housing material: Acrylonitrile butadiene styrene (ABS), Aluminium.

Ethernet interface type: Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s. Power supply type: USB, Power consumption (typical): 1.2 W. Width: 107 mm, Depth: 28 mm, Height: 12.5 mm



Ports & interfaces		Packaging data	
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A + Type-C	Quantity per pack	1 pc(s)
Hub interfaces *	RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Package width	160 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3	Package depth	90 mm
Ports quantity *	4	Package height	21 mm
Ethernet LAN (RJ-45) ports	1	Package weight	100 g
		Package type	Box
Features		Packaging content	
Data transfer rate *	5000 Mbit/s	Manual	✓
Product colour	Grey	Operational conditions	
Housing material	Acrylonitrile butadiene styrene (ABS), Aluminium	Minimum operating temperature	0 °C
HD type	4K Ultra HD	Maximum operating temperature	40 °C
Cable length	0.15 m	Operating temperature (T-T)	0 - 40 °C
		Operating temperature (T-T)	32 - 104 °F
Network		Storage temperature (T-T)	-20 - 60 °C
Ethernet interface type	Gigabit Ethernet	Operating relative humidity (H-H)	5 - 90%
Ethernet LAN data rates	10,100,1000 Mbit/s	Storage relative humidity (H-H)	5 - 90%
Power		Sustainability	
Power supply type	USB	Sustainability compliance	✓
Power consumption (typical)	1.2 W	Technical details	
Weight & dimensions		Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS
Width	107 mm		
Depth	28 mm		
Height	12.5 mm		
Weight	50 g		



4002888433792

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-DEC-2024. Prints or copies of Information are only valid on the printed Publication date