


LG 75UH5J-M infonäyttö Digitaalinen litteä infotaulu 190,5 cm (75") LED Wi-Fi 500 cd/m² 4K Ultra HD musta WebOS 24/7

Tuotemerkki: LG Tuotekoodi: 75UH5J-M

Tuotteen nimi: 75UH5J-M

LG 75UH5J-M. Tuotteen muotoilu: Digitaalinen litteä infotaulu. Näytön halkaisija: 190,5 cm (75"), Näytön teknologia: LED, Näytön erottelutarkkuus: 3840 x 2160 pikseliä, Näytön kirkkaus: 500 cd/m², HD-tyyppi: 4K Ultra HD. Wi-Fi. Toiminta-aika (tunteja/päiviä): 24/7. Käyttöjärjestelmä asennettu: WebOS. Tuotteen väri: musta





Display Design Panel type IPS Bezel width (bottom) 1.49 cm LED backlighting type Edge-LED Bezel width (top) 1.49 cm LED backlighting type Edge-LED Bezel width (top) 1.49 cm Display diagonal* 190.5 cm (75*) Performance Display technology* LED Purpose * Commercial Display brightness* 500 cd/m² Ambient light sensor ✓ HD type * 4K Ultra HD Ambient light sensor ✓ Touchscreen * X HDCP ✓ Response time 6 ms HDCP ✓ Contrast ratio (typical) 1000:1 International Protection (IP) code IPSX Contrast ratio (typical) 178° Power IPSX Viewing angle, vertical 178° Power IPSX Viewing angle, vertical 178° Power consumption (typical) * 170 W Display number of colours 1.07 billion colours Power consumption (standby) * 0.5 W Colour saturation 22% P				
LED backlight Y Bezel width (side) 1.49 cm LED backlighting type Edge-LED Bezel width (top) 1.49 cm Display diagonal* 190.5 cm (75") Performance Display technology* LED Purpose* Commercial Display presolution* 3840 x 2160 pixels On Screen Display (OSD) ✓ Display brightness* 500 cd/m² Ambient light sensor ✓ LD type* 4K Ultra HD Operating hours (hours/days) 24/7 Touchscreen* X HDCP Prover Response time 6 ms HDCP International Protection (IP) code IP5X Contrast ratio (typical) 1000:1 HDCP version 1.4/2.2 Viewing angle, horizontal 178° Power Viewing angle, vertical 178° Power Display number of colours 1.07 billion colours Power consumption (typical)* 1.70 W Oisplay number of colours 1.07 billion colours Power consumption (fmax) 2.30 W Surface hardness 28 Ac input voltage 100 - 240	Display		Design	
Display diagonal * 190.5 cm (75") Performance Display technology * LED Purpose * Commercial Display resolution * 3840 x 2160 pixels On Screen Display (OSD) ✓ Display brightness * 500 cd/m² Ambient light sensor ✓ HD type * 4K Ultra HD Operating hours (hours/days) 24/7 Touchscreen * X HDCP ✓ Response time 6 ms HDCP ✓ Contrast ratio (dynamic) 1000:01 HDCP version 1.4/2.2 Contrast ratio (dynamic) 1000000:1 HDCP version 1.4/2.2 Viewing angle, horizontal 178° Power 170 W Viewing angle, vertical 1.78° Power consumption (typical) ** 170 W Olisplay number of colours 1.07 billion colours Power consumption (ff) 0.5 W Colour saturation 72% Power consumption (ff) 0.5 W Native refresh rate 120 Hz Power consumption (max) 230 W Surface hardness 8 AC input voltage 100 - 240 V<	LED backlight	✓	Bezel width (side)	1.49 cm
Display resolution * 3840 x 2160 pixels		•	Performance	
Viewing angle, horizontal178°PowerViewing angle, vertical178°Power consumption (typical)*170 WDisplay number of colours1.07 billion coloursPower consumption (standby)*0.5 WColour saturation72%Power consumption (off)0.5 WNative refresh rate120 HzPower consumption (max)230 WSurface hardness28AC input voltage100 - 240 VPorts & interfacesHDMI ports quantity*3Heat dissipation581 BTU/hDVI port*✓Computer systemDVI-D ports quantity1Internal memory16 GBDisplayPorts quantity*1Operating system installedWebOSUSB port *✓Operating system version6.0USB ports quantity1Weight & dimensionsUSB version2.0Display width1682.4 mmEthernet LAN *✓Display depth57.9 mmEthernet LAN (RJ-45) ports1Display height960.3 mmWi-Fi *✓Display weight41.5 kgAudio (L/R) in1Packaging dataAudio (L/R) out1Package width1816 mmInfrared data port4Package depth228 mm	Display resolution * Display brightness * HD type * Touchscreen * Response time Contrast ratio (typical)	play resolution * 3840 x 2160 pixels play brightness * 500 cd/m² type * 4K Ultra HD uchscreen * x sponse time 6 ms ntrast ratio (typical) 1000:1	On Screen Display (OSD) Ambient light sensor Operating hours (hours/days) HDCP International Protection (IP) code	✓ ✓ 24/7 ✓ IP5X
Display number of colours 1.07 billion colours Power consumption (standby) * 0.5 W Colour saturation 72% Power consumption (off) 0.5 W Native refresh rate 120 Hz Power consumption (max) 230 W Surface hardness 28 AC input voltage 100 - 240 V Ports & interfaces HDMI ports quantity * 3 DVI port * V Computer system DVI-D ports quantity 1 Internal memory 16 GB DisplayPorts quantity * 1 Operating system installed WebOS USB port * USB ports quantity 1 Weight & dimensions USB version Ethernet LAN * Ethernet LAN (RJ-45) ports 1 Display height 1 Display weight 1 Display weight 41.5 kg Addio (L/R) in Audio (L/R) out Internal memory Power consumption (off) 0.5 W O.5 W Computer system 100 - 240 V AC input frequency 50/60 Hz Heat dissipation 581 BTU/h Computer system 100 - 240 V AC input frequency 50/60 Hz Heat dissipation 16 GB WebOS Operating system installed WebOS Operating system version 6.0 Weight & dimensions Display width 1682.4 mm 1682.4 mm 1682.4 mm Display height 960.3 mm Wi-Fi * V Display weight 41.5 kg Audio (L/R) in Audio (L/R) out RS-232C V Package width Package width Package width Package depth Internal memory 17 Usa depth 1816 mm Package depth Package depth			Power	
HDMI ports quantity * 3 DVI port *	Display number of colours Colour saturation Native refresh rate	1.07 billion colours 72% 120 Hz	Power consumption (standby) * Power consumption (off) Power consumption (max)	0.5 W 0.5 W 230 W
DVI port *	Ports & interfaces		AC input frequency	50/60 Hz
USB version 2.0 Display width 1682.4 mm Ethernet LAN *	DVI port * DVI-D ports quantity DisplayPorts quantity *	7 1 1	Computer system Internal memory Operating system installed	16 GB WebOS
Ethernet LAN * Ethernet LAN (RJ-45) ports 1 Display depth Display height Display weight 41.5 kg Audio (L/R) in Audio (L/R) out RS-232C Package width Package width Package depth Package depth Package depth Package depth Package depth	USB ports quantity	1	Weight & dimensions	
Audio (L/R) out 1 RS-232C Package width Package depth Package depth 228 mm	Ethernet LAN * Ethernet LAN (RJ-45) ports	✓ 1	Display depth Display height	57.9 mm 960.3 mm
RS-232C Package width 1816 mm Package depth 228 mm	, , ,		Packaging data	
Remote (IR) input 1 Package height 1123 mm 51.2 kg	RS-232C Infrared data port	✓	Package depth Package height	228 mm 1123 mm

Audio		Packaging content	
Built-in speaker(s) *	✓	Remote control included	✓
Design		Cables included	Power
Product design *	Digital signage flat panel	Tilt adjustment	✓
Placement supported *	Indoor	Operational conditions	
Orientation	Horizontal/Vertical	Operating temperature (T-T)	0 - 40 °C
Product colour *	Black	Operating relative humidity (H-H)	10 - 80%
Screen shape	Flat	Features	
VESA mounting *	✓	Heat dissipation (max)	785 BTU/h
Panel mounting interface	600 x 400 mm	ricat dissipation (max)	703 510/11





195174060810

0195174060810

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.