D-Link DBS-2000-52MP/E network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) White

Brand : D-Link


Product code: DBS-2000-52MP/E



Product name : DBS-2000-52MP/E

D-Link DBS-2000-52MP/E. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 48, Console port: RJ-45. Switching capacity: 104 Gbit/s. Networking standards: IEEE 802.3ad, IEEE 802.3at. Power over Ethernet (PoE). Rack mounting

| Management features | | Performance | |
|--|--------------------------------------|--|----------------------------------|
| Switch type * Switch layer Web-based management | Managed L2 ✔ | Internal memory Flash memory Mean time between failures (MTBF) | 256 MB 32 MB 236406 h |
| Ports & interfaces | | Power | |
| Basic switching RJ-45 Ethernet ports quantity * Basic switching RJ-45 Ethernet ports | | Power source * AC input voltage Power consumption (max) | DC/PoE 100 - 240 V 478.9 W |
| type * Combo SFP ports quantity | 4 | Power over Ethernet (PoE) | |
| Console port | - RJ-45 | Power over Ethernet (PoE) * | 1 |
| Network | | Power over Ethernet (PoE) ports quantity | 48 |
| Networking standards * 10G support * | IEEE 802.3ad, IEEE 802.3at × | Power over Ethernet (PoE) power per port | 30 W |
| Copper ethernet cabling technology | 10BASE-T, 100BASE-TX, 1000BASE- T | Total Power over Ethernet (PoE) budget | 370 W |
| Link aggregation | ✓ | Operational conditions | |
| Auto MDI/MDI-X | ✓ | Operating temperature (T-T) | -5 - 50 °C |
| Spanning tree protocol | ✓ | Storage temperature (T-T) | -20 - 70 °C |
| Data transmission | | Operating relative humidity (H-H) Storage relative humidity (H-H) | 0 - 95% 0 - 95% |
| Switching capacity * | 104 Gbit/s | Heat dissipation | 1634.01 BTU/h |
| Forwarding rate Packet buffer memory | 77.4 Mpps 12 MB | Weight & dimensions | |
| Security | | Width | 440 mm |
| IGMP snooping | 1 | Depth | 430 mm 44 mm |
| Security algorithms | WPA, WPA2 | Height Weight | 6.26 kg |
| Design | | Packaging data | |
| Rack mounting * Product colour LED indicators | ✓ White ✓ | Package width Package depth Package height | 558 mm 568 mm 149 mm |
| Performance | | Package weight | 8.66 kg |
| Built-in processor Processor frequency Memory type | ✓ 700 MHz DDR3-SDRAM | | |





790069471308

0790069471308

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.