

D-Link DGS-1210-52MP/ME/E verkkokytkin Hallittu L2+ Gigabit Ethernet (10/100/1000) 1U musta, Harmaa



Tuotemerkki : D-Link

Tuotekoodi: DGS-1210-52MP/ME/E

Tuotteen nimi : DGS-1210-52MP/ME/E

D-Link DGS-1210-52MP/ME/E. Kytkin tyyppi: Hallittu, Kytinkerros: L2+. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 48, Console-portti: RJ-45. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 104 Gbit/s. Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Virtaliitin: DC-tulo jakkiliitin. Telineasennus, Kotelo: 1U

Management features		Multicast features	
Switch type *	Managed	Multicast support	✓
Switch layer	L2+	Multicast Listener Discovery (MLD) snooping	MLD v1, MLD v2
Quality of Service (QoS) support	✓		
Ports & interfaces		Design	
Basic switching RJ-45 Ethernet ports quantity *	48	Rack mounting *	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Stackable *	✓
Gigabit Ethernet (copper) ports quantity	48	Form factor	1U
SFP module slots quantity	4	Product colour	Black, Grey
Fiber optic connector	SFP	LED indicators	Activity, Fan fail, Link, Power, Speed
Console port	RJ-45	Number of fans	2 fan(s)
Power connector	DC-in jack	Electromagnetic compatibility	FCC A, CE A, VCCI, C-Tick, BSMI, CCC
Network		Performance	
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Memory type	DDR3-SDRAM
10G support *	✗	Internal memory	256 MB
Copper ethernet cabling technology	10GBASE-T, 100BASE-TX, 1000BASE-T	Flash memory	32 MB
Port mirroring	✓	Noise level	52.4 dB
Full duplex	✓	Power	
Flow control support	✓	Power source *	AC/DC
Link aggregation	✓	Power supply included *	✓
Broadcast storm control	✓	AC input voltage	100 - 240 V
Auto MDI/MDI-X	✓	AC input frequency	50/60 Hz
Spanning tree protocol	✓	Power consumption (typical)	483.1 W
Number of VLANs	4094	Operational conditions	
Data transmission		Operating temperature (T-T)	-5 - 50 °C
Switching capacity *	104 Gbit/s	Storage temperature (T-T)	-40 - 70 °C
MAC address table *	16000 entries	Operating relative humidity (H-H)	10 - 90%
Packet buffer memory	3 MB	Storage relative humidity (H-H)	5 - 90%
Security		Heat dissipation	850.58 BTU/h
DHCP features	DHCP client, DHCP server	Weight & dimensions	
Access Control List (ACL)	✓	Width	440 mm
IGMP snooping	✓	Depth	430 mm
Security algorithms	802.1x RADIUS, SNMP, SSH	Height	44 mm
MAC address filtering	✓	Weight	5.78 kg
SSH/SSL support	✓	Packaging data	
Loop protection	✓	Package width	558 mm
BPDU filtering/protection	✓	Package depth	568 mm
		Package height	149 mm
		Package weight	8.54 kg
		Certificates	
		Certification	IEC61000-4-5, RoHS

Security

IP-MAC-Port binding



Authentication

Guest VLAN, MAC-based authentication, Port-based authentication



0790069468230



790069468230

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.