



TP-Link Omada EAP680 WLAN-tukiasema 4804 Mbit/s Valkoinen Power over Ethernet -tuki

Tuotemerkki : TP-Link

Tuoteperhe: Omada

Tuotekoodi: EAP680

Tuotteen nimi : EAP680

TP-Link Omada EAP680. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 4804 Mbit/s. Tietoturva-algoritmit: SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3-Enterprise,.... Ethernet LAN -datanopeudet: 10,100,1000,2500 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen



Features		Management features	
2.4 GHz *	✓	Web-based management	✓
5 GHz *	✓	Ports & interfaces	
6 GHz *	✗	Ethernet LAN (RJ-45) ports *	1
Maximum data transfer rate *	4804 Mbit/s	DC-in jack	✓
Maximum data transfer rate (2.4 GHz)	1148 Mbit/s	Power	
Maximum data transfer rate (5 GHz)	4804 Mbit/s	Power over Ethernet (PoE) *	✓
Ethernet LAN data rates	10,100,1000,2500 Mbit/s	Output voltage	12 V
Frequency band	2.4 - 5 GHz	Design	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Placement *	Ceiling, Wall
Automatic channel selection	✓	Product colour *	White
Automatic channel scanning	✓	Reset button	✓
MIMO	✓	LED indicators	✓
MIMO type	Multi User MIMO	Antenna	
Spread spectrum method	OFDMA	Antenna type *	Internal
Wi-Fi Multimedia (WMM)/(WME)	✓	Antenna direction type	Omni-directional
Fast roaming	✓	Antenna gain level (max)	5 dBi
VLAN support	✓	Certificates	
Rate limiting	✓	Certification	CE, RoHS
Wireless isolation	✓	Weight & dimensions	
Band steering	✓	Width	220 mm
Quality of Service (QoS) support	✓	Depth	220 mm
BeamForming	✓	Height	32.5 mm
		Packaging content	
		Quantity per pack	1 pc(s)
		AC adapter included	✓

Security		Operational conditions	
Security algorithms *	SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3-Enterprise, WPA3-PSK	Operating relative humidity (H-H)	10 - 90%
MAC address filtering	✓	Operating temperature (T-T)	0 - 40 °C
Service Set Identifier (SSID) features	Multiple SSIDs	Storage temperature (T-T)	-40 - 70 °C
Number of SSID supported	16	Storage relative humidity (H-H)	5 - 90%
Access Control List (ACL)	✓		



4897098687178



4897098681534

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.