



Lenovo ThinkSystem ST650 V2 server Tower (4U) Intel Xeon Silver 4309Y 2.8 GHz 32 GB DDR4-SDRAM 1100 W



Brand : Lenovo

Product family: ThinkSystem

Product code: 7Z74A03QEA

Product name : ST650 V2

- No OS
- Intel Xeon Silver 4309Y (12MB Cache, 2.8GHz)
- 32GB (3200MHz) DDR4-SDRAM (1 x 32)
Intel Xeon Silver 4309Y (12MB Cache, 2.8GHz), 32GB DDR4-SDRAM (3200MHz), LAN (Broadcom 57416), 930-8i 2GB, 1100W, No OS
Lenovo ThinkSystem ST650 V2. Processor family: Intel Xeon Silver, Processor frequency: 2.8 GHz, Processor model: 4309Y. Internal memory: 32 GB, Internal memory type: DDR4-SDRAM, Memory layout (slots x size): 1 x 32 GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 1100 W, Redundant power supply (RPS) support. Chassis type: Tower (4U)

Processor		Ports & interfaces	
Processor manufacturer *	Intel	Serial ports quantity	1
Processor family *	Intel Xeon Silver	Design	
Processor model *	4309Y	Chassis type *	Tower (4U)
Processor frequency *	2.8 GHz	Product colour	Black
Processor boost frequency	3.6 GHz	Rack mounting	✓
Processor cache	12 MB	Performance	
Number of processors installed	1	Performance management	XClarity Enterprise
Memory		Trusted Platform Module (TPM)	✓
Internal memory *	32 GB	Trusted Platform Module (TPM) version	2.0
Internal memory type *	DDR4-SDRAM	Software	
Memory clock speed	3200 MHz	Operating system installed *	✗
Memory layout (slots x size)	1 x 32 GB	Compatible operating systems *	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi
Storage		Power	
RAID support *	✓	Redundant power supply (RPS) support *	✓
RAID levels	0, 1, 5, 6, 10, 50, 60	Power supply *	1100 W
Supported RAID controllers	930-8i 2GB	Operational conditions	
Internal drive bays	8	Operating temperature (T-T)	5 - 45 °C
Graphics		Storage temperature (T-T)	-40 - 60 °C
Maximum graphics card memory	16 MB	Operating relative humidity (H-H)	8 - 90%
Network		Storage relative humidity (H-H)	8 - 90%
LAN controller	Broadcom 57416	Operating altitude	0 - 3050 m
Ethernet LAN	✓	Weight & dimensions	
Cabling technology	10/100/1000Base-T(X)	Width	175 mm
Ethernet interface type	10 Gigabit Ethernet	Depth	734 mm
Ports & interfaces		Height	462 mm
Ethernet LAN (RJ-45) ports *	3		
USB 2.0 ports quantity	1		
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	5		
VGA (D-Sub) ports quantity	1		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-DEC-2024. Prints or copies of Information are only valid on the printed Publication date