

ZYXEL

## Zyxel PoE12-30W 2.5 Gigabit Ethernet

**Brand :** Zyxel

**Product code:** POE12-30W-EU0101F

**Product name :** PoE12-30W

- MultiGig tot 2.5G PoE+ Injector
  - 30W PoE+ 802.3af/at standaard
  - Single port Powerinjector
  - Eenvoudige installatie voor IEEE 802.3at compatibele draadloze LAN Aps, IP-videocamera's of IP-telefoons
- Single 1-2.5G MultiGig 802.3at PoE+ Injector [POE12-30W]

[Zyxel PoE12-30W 2.5 Gigabit Ethernet:](#)

### Support 2.5 Gigabit High Network Speed

PoE12-30W is a Multi-Gigabit PoE injector supporting network speeds of up to 2.5Gbps. It is allowed to connect powered devices through existing Cat 5e or above cable.

### Plug and Play—Ease of Use

PoE12-30W is easy to connect network devices without any configuration. The wall-mount and desktop design accommodate most installations scenarios.

Zyxel PoE12-30W. Ethernet interface type: 2.5 Gigabit Ethernet, Ethernet LAN data rates: 100,1000,2500 Mbit/s, Networking standards: IEEE 802.3ab, IEEE 802.3at, IEEE 802.3bz, IEEE 802.3u. Product colour: Black. Output power: 30 W, Input voltage: 100 - 240 V, Input frequency: 50/60 Hz. Width: 140 mm, Depth: 45.5 mm, Height: 30 mm



Network		Power	
Ethernet interface type	2.5 Gigabit Ethernet	Total Power over Ethernet (PoE) budget	30 W
Ethernet LAN data rates	100,1000,2500 Mbit/s	<b>Operational conditions</b>	
Power over Ethernet (PoE)	✓	Operating temperature (T-T)	-10 - 45 °C
Networking standards	IEEE 802.3ab, IEEE 802.3at, IEEE 802.3bz, IEEE 802.3u	Operating temperature (T-T)	14 - 113 °F
<b>Features</b>		Operating relative humidity (H-H)	5 - 90%
Product colour	Black	Storage temperature (T-T)	-25 - 70 °C
Wall mountable	✓	Storage relative humidity (H-H)	5 - 90%
Plug and Play	✓	<b>Weight &amp; dimensions</b>	
<b>Ports &amp; interfaces</b>		Width	140 mm
Ethernet LAN (RJ-45) ports	2	Depth	45.5 mm
RJ-45 input ports	1	Height	30 mm
RJ-45 output ports	1	Weight	144 g
<b>Power</b>		<b>Packaging content</b>	
Output power	30 W	Power cord included	✓
Input voltage	100 - 240 V	<b>Logistics data</b>	
Input frequency	50/60 Hz	Harmonized System (HS) code	85176990
Input current	1 A		



4718937620227

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-DEC-2024. Prints or copies of Information are only valid on the printed Publication date