Verbatim CMH-13 USB Type-C 10000 Mbit/s Hopea

Tuotemerkki : Verbatim   **Tuotekoodi:** 32153

Tuotteen nimi : CMH-13

Verbatim CMH-13. Isäntäkoneen käyttöliittymä: USB Type-C, Liittimiä: 3.5mm, DisplayPort, HDMI, RJ-45, USB 2.0, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 2 (3.1 Gen.... Tiedonsiirtonopeus: 10000 Mbit/s, Suurin päivitystaajuus: 30 Hz, Tuotteen väri: Hopea. Ethernet-liitännän tyyppi: Gigabitti Ethernet. Ulostulojännite: 5 V, Lähtövirta: 0,9 A. Windows-käyttöjärjestelmätuki: Windows 10, Windows 11, Windows 7, Windows 8, Mac-käyttöjärjestelmätuki: Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X..., Muu käyttöjärjestelmätuki: ChromeOS

Ports & interfaces

Host interface *	USB Type-C
Hub interfaces *	3.5mm, DisplayPort, HDMI, RJ-45, USB 2.0, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 2 (3.1 Gen 2) Type-A, USB Type-C
USB 2.0 ports quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2
HDMI ports quantity	2
DisplayPorts quantity	1
Combo headphone/mic port	✔
Ports quantity *	13
Ethernet LAN (RJ-45) ports	1

Features

Data transfer rate *	10000 Mbit/s
Maximum refresh rate	30 Hz
Product colour	Silver
Housing material	Acrylonitrile butadiene styrene (ABS), Aluminium
USB Power Delivery (USB PD)	✔
USB Power Delivery up to	100 W
HD type	8K Ultra HD
LED indicators	✔
Cable length	0.2 m

Weight & dimensions

Width	55.4 mm
Depth	160.2 mm
Height	15 mm
Weight	150 g

Packaging data

Quantity per pack	1 pc(s)
Package width	100 mm
Package depth	200 mm
Package height	22 mm
Package weight	206 g
Package type	Hanging box

Packaging content

Quick start guide	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	10 - 85%

Logistics data

Packs per box (outer)	40
Box (outer) per layer	8
Products per pallet	960 pc(s)
Master (outer) case width	245 mm
Layers per pallet	3 pc(s)
Master (outer) case length	435 mm
Master (outer) case height	290 mm

Features

Country of origin	China
Certification	EAC/CE/UKCA/FCC RoHS/REACH

Network

Ethernet interface type	Gigabit Ethernet

Power

Output voltage	5 V
Output current	0.9 A

System requirements

Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8
Mac operating systems supported	Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey
Linux operating systems supported	✔
Other operating systems supported	ChromeOS

Logistics data

Master (outer) case gross weight	9.4 kg
Products per master (outer) case	40 pc(s)
Shipping (inner) case width	11.2 cm
Shipping (inner) case length	41.5 cm
Shipping (inner) case height	13 cm
Shipping (inner) case gross weight	2.21 kg
Products per shipping (inner) case	10 pc(s)

Technical details

Master (outer) cases per pallet	24 pc(s)

0023942321538

023942321538

(01)20023942321532

(01)50023942321533