Verbatim CMH-09 USB Type-C 10000 Mbit/s Hopea

Tuotemerkki : Verbatim

Tuotteen nimi : CMH-09

Tuotekoodi: 32152

Verbatim CMH-09. Isäntäkoneen käyttöliittymä: USB Type-C, Liittimiä: HDMI, RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 2 (3.1 Gen 2) Type-A, USB 3.2 Gen 2..., Yhteensopivat muistikortit: MicroSD (TransFlash), SD. Tiedonsiirtonopeus: 10000 Mbit/s, Suurin päivitystaajuus: 60 Hz, Tuotteen väri: Hopea. Ethernet-liitännän tyyppi: Gigabitti Ethernet. Ulostulojännite: 5 V, Lähtövirta: 1,5 A. Windows-käyttöjärjestelmätuki: Windows 10, Windows 11, Windows 7, Windows 8, Mac-käyttöjärjestelmätuki: Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X..., Muu käyttöjärjestelmätuki: ChromeOS

Ports & interfaces

Host interface *	USB Type-C
Hub interfaces *	HDMI, RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 2 (3.1 Gen 2) Type-A, USB 3.2 Gen 2 (3.1 Gen 2) Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2
HDMI ports quantity	1
Ports quantity *	9
Ethernet LAN (RJ-45) ports	1
Card reader slot	2
Compatible memory cards	MicroSD (TransFlash), SD

Features

Data transfer rate *	10000 Mbit/s
Maximum refresh rate	60 Hz
Product colour	Silver
Housing material	Acrylonitrile butadiene styrene (ABS), Aluminium
USB Power Delivery (USB PD)	✘
HD type	4K Ultra HD
LED indicators	✘
Cable length	0.15 m
Country of origin	China
Certification	EAC/CE/UKCA/FCC RoHS/REACH

Network

Ethernet interface type	Gigabit Ethernet

Weight & dimensions

Width	49 mm
Depth	121 mm
Height	15.5 mm
Weight	88 g

Packaging data

Quantity per pack	1 pc(s)
Package width	85 mm
Package depth	155 mm
Package height	20 mm
Package weight	132 g
Package type	Hanging box

Packaging content

Quick start guide	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	10 - 85%

Logistics data

Packs per box (outer)	40
Box (outer) per layer	12
Products per pallet	1920 pc(s)
Master (outer) case width	215 mm
Layers per pallet	4 pc(s)
Master (outer) case length	345 mm
Master (outer) case height	250 mm
Master (outer) case gross weight	6.12 kg
Products per master (outer) case	40 pc(s)

Power

Output voltage	5 V
Output current	1.5 A

System requirements

Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8
Mac operating systems supported	Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Linux operating systems supported	✔
Other operating systems supported	ChromeOS

Logistics data

Shipping (inner) case width	9.7 cm
Shipping (inner) case length	32.5 cm
Shipping (inner) case height	11 cm
Shipping (inner) case gross weight	1.43 kg
Products per shipping (inner) case	10 pc(s)

Technical details

Master (outer) cases per pallet	48 pc(s)

0023942321521

023942321521

(01)20023942321525

(01)50023942321526