



## Lindy 39384 KVM -kytkin Lähetin & vastaanotin

**Tuotemerkki :** Lindy

**Tuotekoodi:** 39384

**Tuotteen nimi :** 39384

Lindy 39384. Malli: Lähetin & vastaanotin, Yhteysteknologia: Langallinen, Suurin siirtoetäisyys: 150 m. Lähettimen paikallisen videoportin tyyppi: HDMI. Vastaanottimen paikallisen videoportin tyyppi: HDMI. AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 50 - 60 Hz, Tehonkulutus (lähetin) (max): 13,2 W. Lähettimen leveys: 14 cm, Lähettimen syvyys: 6,5 cm, Lähettimen korkeus: 1,8 cm



Features		Power	
Type *	Transmitter & receiver	Power consumption (transmitter) (max)	13.2 W
Connectivity technology *	Wired	Power consumption (receiver) (max)	13.2 W
Maximum transfer distance	150 m	DC-in jack	✓
Cable types supported	Cat6	<b>Weight &amp; dimensions</b>	
Maximum digital resolution	3840 x 2160 pixels	Transmitter width	14 cm
Maximum refresh rate	60 Hz	Transmitter depth	6.5 cm
Colour depth	12 bit	Transmitter height	1.8 cm
Supported resolutions	3840 x 2160 1920 x 1080	Transmitter weight	790 g
Product colour	Black	Receiver width	14 cm
Material	Metal	Receiver depth	6.5 cm
Chipset	VS010-A0	Receiver height	1.8 cm
<b>Transmitter</b>		Receiver weight	790 g
Transmitter local video port	✓	<b>Packaging data</b>	
Transmitter local video port type	HDMI	Package width	245 mm
RJ-45 ports quantity (transmitter)	1	Package depth	185 mm
Transmitter Micro-USB ports quantity	1	Package height	75 mm
Transmitter USB Type-B ports quantity	1	Package weight	1.02 kg
<b>Receiver</b>		<b>Packaging content</b>	
Receiver local video port type	HDMI	Cables included	IR, USB Type-A to USB Type-B
RJ-45 ports quantity (receiver)	1	Manual	✓
Receiver Micro-USB ports quantity	1	Included power plug types	AU, EU, UK, US
Receiver USB Type-A ports quantity	2	Screws included	✓
<b>Ports &amp; interfaces</b>		<b>Operational conditions</b>	
HDMI version	2.0	Operating temperature (T-T)	0 - 40 °C
Remote (IR) input	2	Storage temperature (T-T)	-20 - 60 °C
Remote (IR) output	2	Operating relative humidity (H-H)	20 - 90%

Power		Sustainability	
AC input voltage	100 - 240 V	Sustainability compliance	✓
AC input frequency	50 - 60 Hz	<b>Other features</b>	
		HDCP	✓
		HDCP version	2.2
		Extended display identification data (EDID)	✓
		Bandwidth	18 Gbit/s
		Infrared (IR) frequency range	20 - 60 kHz
		Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA



4002888393843

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-DEC-2024. Prints or copies of Information are only valid on the printed Publication date