StarTech.com D86A2-4-PORT-8K-KVM KVM-kytkin musta

Tuotemerkki : StarTech.com

Tuotteen nimi : D86A2-4-PORT-8K-KVM

Tuotekoodi: D86A2-4-PORT-8K-KVM

StarTech.com D86A2-4-PORT-8K-KVM. Näppäimistöportin liitin: USB, Hiiriportin liitin: USB, Videoportin tyyppi: DisplayPort. HD-tyyppi: 8K Ultra HD, Enimmäiserottelutarkkuus: 7680 x 4320 pikseliä, Tiedonsiirtonopeus (maks.): 5000 Gbit/s. Tuotteen väri: musta, Kotelon materiaali: Terästä, Keskimääräinen vikaantumisaika: 130000 h. Voimanlähde: DC, Tulojännite: 100 - 240 V, Syöttöjännite: 1 A. Vaatimustenmukaisuustodistukset: CE, RoHS, Laki kauppasopimuksista (TAA)

Ports & interfaces

Number of computers controlled *	4
Keyboard port type *	USB
Mouse port type *	USB
Video port type *	DisplayPort
DisplayPorts quantity	4
DisplayPort version	1.4
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	4
Console ports *	3.5mm headphone, DisplayPort, USB A
Console DisplayPorts ports quantity	1
USB 2.0 Type-A hub ports quantity	4
USB 3.2 Gen 1 (3.1 Gen 1) Type-A hub ports quantity	2
Audio connections	✔
Headphone outputs	4
DC-in jack	✔

Performance

HD type *	8K Ultra HD
Maximum resolution *	7680 x 4320 pixels
Data transfer rate (max)	5000 Gbit/s
Scan interval	3,8,15,30 s
High Dynamic Range (HDR) supported	✔
HDCP	✔
Daisy chain	✗
Chipset	GL-3523
HDCP version	1.4/2.2

Display

Built-in display *	✗

Power

Power source	DC
Input voltage	100 - 240 V
Input current	1 A
Output voltage	12 V
Output current	3 A
Power consumption (typical)	36 W
Power plug type	Type M
Compatible power plug types	EU, JP, UK, US

Sustainability

Sustainability compliance	✔
Compliance certificates	CE, RoHS, Trade Agreements Act (TAA)

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 85%

Weight & dimensions

Width	130 mm
Depth	220 mm
Height	44 mm
Weight	1 kg

Packaging data

Package width	409 mm
Package depth	212 mm
Package height	87 mm

Design

Rack mounting *	✘
Product colour *	Black
Housing material	Steel
LED indicators	✔
Push button	✔
Hot keys	✔
Mean time between failures (MTBF)	130000 h

Packaging data

Package weight	1.6 kg

Packaging content

Quick installation guide	✔
Rubber feet	✔

Other features

IP control	✘

Logistics data

Master (outer) case width	545 mm
Master (outer) case length	427 mm
Master (outer) case height	245 mm
Products per master (outer) case	60 pc(s)

0065030893206

065030893206