

## ASUS Dual -RTX4070-O12G-EVO NVIDIA GeForce RTX 4070 12 GB GDDR6X

**Brand :** ASUS

**Product family:** Dual

**Product code:** 90YV0J15-M0NA00

**Product name :** DUAL-RTX4070-O12G-EVO



- Powered by NVIDIA DLSS3, ultra-efficient Ada Lovelace arch, and full ray tracing
  - 4th Generation Tensor Cores: Up to 4x performance with DLSS 3 vs. brute-force rendering
  - 3rd Generation RT Cores: Up to 2x ray tracing performance
  - OC edition: Boost Clock 2550 MHz (OC Mode)/2520 MHz (Default Mode)
  - Axial-tech fan design features a smaller fan hub that facilitates longer blades and a barrier ring that increases downward air pressure
  - A 2.5-slot design maximizes compatibility and cooling efficiency for superior performance in small chassis
  - 0dB technology lets you enjoy light gaming in relative silence
  - Dual ball fan bearings can last up to twice as long as sleeve bearing designs
- Dual GeForce RTX 4070 EVO OC Edition 12GB GDDR6X with two powerful Axial-tech fans and a 2.5-slot design for broad compatibility

<b>Processor</b>		<b>Performance</b>	
CUDA *	✓	HDCP	✓
CUDA cores	5888	HDCP version	2.3
Graphics processor family *	NVIDIA	<b>Design</b>	
Graphics processor *	GeForce RTX 4070	Cooling type *	Active
Processor boost clock speed	2520 MHz	Cooling technology	ASUS Axial-tech
Processor frequency (OC mode)	2550 MHz	Number of fans	2 fan(s)
Maximum resolution *	7680 x 4320 pixels	Number of slots	2.5
Parallel processing technology support *	Not supported	Product colour	Black
Maximum displays per videocard	4	<b>Power</b>	
<b>Memory</b>		Minimum system power supply *	650 W
Discrete graphics card memory *	12 GB	Supplementary power connectors	1x 8-pin
Graphics card memory type *	GDDR6X	<b>Weight &amp; dimensions</b>	
Memory bus *	192 bit	Weight	684 g
<b>Ports &amp; interfaces</b>		Length	227.2 mm
Interface type *	PCI Express 4.0	Depth	49.6 mm
HDMI ports quantity *	1	Height	123.2 mm
HDMI version	2.1a	<b>Packaging data</b>	
DisplayPorts quantity *	3	Package width	368 mm
DisplayPort version	1.4a	Package depth	220.5 mm
<b>Performance</b>		Package height	68 mm
OpenGL version *	4.6	Package weight	1.13 kg
		Package type	Box
		<b>Packaging content</b>	
		Manual	✓



4711387432006

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-NOV-2024. Prints or copies of Information are only valid on the printed Publication date