

Philips Evnia 5000 25M2N5200P/00 tietokoneen litteä näyttö 62,2 cm (24.5") 1920 x 1080 pikseliä Full HD LCD Harmaa

Tuotemerkki : Philips

Tuoteperhe: Evnia

Tuotekoodi: 25M2N5200P/00

Tuotteen nimi :
25M2N5200P/00

Gaming Monitor 25M2N5200P Full HD -pelinäyttö

Philips Evnia 5000 25M2N5200P/00 tietokoneen litteä näyttö 62,2 cm (24.5") 1920 x 1080 pikseliä Full HD LCD Harmaa:

Tämän pelinäytön avulla et joudu tekemään kompromisseja. SmartContrast, AMD FreeSync Premium -tekniikka ja 280 hertsin virkistystaajuus takaavat sulavan ja viiveettömän pelikokemuksen kuvanlaadusta tinkimättä.

Philips Evnia 5000 25M2N5200P/00. Näytön halkaisija: 62,2 cm (24.5"), Näytön erotelutarkkuus: 1920 x 1080 pikseliä, HD-tyyppi: Full HD, Näytön teknologia: LCD, Vasteaika (tyypillinen): 1 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäänrakennettu USB-keskus. VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: Harmaa



Display		Ergonomics	
Display diagonal *	62.2 cm (24.5")	Cable lock slot type	Kensington
Display resolution *	1920 x 1080 pixels	Height adjustment *	✓
HD type *	Full HD	Height adjustment	13 cm
Native aspect ratio *	16:9	Pivot	✓
Display technology *	LCD	Pivot angle	-90 - 90°
Panel type *	IPS	Swivelling	✓
LED backlight	✓	Swivel angle range	-30 - 30°
Backlight type	W-LED	Tilt adjustment	✓
Touchscreen *	✗	Tilt angle range	-5 - 20°
Display brightness (typical)	400 cd/m ²	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Response time *	1 ms	Plug and Play	✓
Anti-glare screen	✓	LED indicators	Operation, Stand-by
Screen shape *	Flat	Power	
Contrast ratio (typical) *	1000:1	Energy efficiency class (SDR) *	E
Maximum refresh rate *	240 Hz	Power consumption (typical) *	18.7 W
Viewing angle, horizontal	178°	Power consumption (standby) *	0.5 W
Viewing angle, vertical	178°	Power consumption (off)	0.3 W
Display number of colours *	16.7 million colours	AC input voltage	100 - 240 V
Response time (fast)	0.5 ms	AC input frequency	50 - 60 Hz
Pixel pitch	0.2832 x 0.2802 mm	Power supply type	Internal
Pixel density	89.91 ppi	Energy efficiency scale	A to G
Vertical scan range	48 - 240 Hz	Operational conditions	
Viewable size, horizontal	54.4 cm	Operating temperature (T-T)	0 - 40 °C
Viewable size, vertical	30.3 cm	Storage temperature (T-T)	-20 - 60 °C
Display diagonal (metric)	62.2 cm	Operating relative humidity (H-H)	20 - 80%
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)	Operating altitude	0 - 3658 m
DDC/CI	✓		
Haze rate	25%		
Surface hardness	3H		
sRGB coverage (typical)	110%		

Display		Operational conditions	
NTSC coverage (typical)	93.4%	Non-operating altitude	0 - 12192 m
Display sRGB	✓	Weight & dimensions	
Performance		Width (with stand)	557 mm
AMD FreeSync *	✓	Depth (with stand)	239 mm
AMD FreeSync type	FreeSync Premium	Height (with stand)	508 mm
Component video sync	Separate sync	Weight (with stand)	4.64 kg
Flicker-free technology	✓	Width (without stand)	557 mm
Multimedia		Depth (without stand)	64 mm
Built-in speaker(s) *	✗	Height (without stand)	331 mm
Built-in camera *	✗	Weight (without stand)	3.3 kg
Design		Packaging data	
Market positioning *	Gaming	Package width	730 mm
Product colour *	Grey	Package depth	188 mm
Ports & interfaces		Package height	420 mm
Built-in USB hub *	✓	Package weight	7.6 kg
USB upstream port type	USB Type-B	Packaging content	
Number of upstream ports	1	Stand included	✓
USB Type-A downstream ports quantity	4	Manual	✓
HDMI *	✓	Sustainability	
HDMI ports quantity	2	Doesn't contain	Mercury, PVC/BFR
HDMI version	2.0	Other features	
DisplayPorts quantity	1	Low input lag	✓
DisplayPort version	1.4	Exterior finish type	Textured
Audio output	✓	Picture enhancement	SmartImage game
HDCP	✓	Recyclable packaging material	100%
HDCP version	1.4/2.2	Regulatory Approvals	CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV/ISO9241-307; TUV-BAUART
Ergonomics		Delta E	2
VESA mounting *	✓	EasyRead mode	✓
Panel mounting interface	100 x 100 mm	LowBlue mode	✓
Cable lock slot *	✓	Philips SmartUniformity	93 - 105%
		Mean time between failures (MTBF)	50000 h



8712581799601

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-DEC-2024. Prints or copies of Information are only valid on the printed Publication date