PHILIPS

Philips Evnia 25M2N3200W/00 computer monitor 62.2 cm (24.5") 1920 x 1080 pixels Full HD LCD Grey

Brand : Philips

Product family: Evnia

Product code: 25M2N3200W/00

Product name : 25M2N3200W/00

Gaming Monitor 25M2N3200W Full HD gaming monitor

Philips Evnia 25M2N3200W/00 computer monitor 62.2 cm (24.5") 1920 x 1080 pixels Full HD LCD Grey:


We are all about "beautiful" speed. This monitor has a 240Hz refresh rate and a 16:9 Full HD display for so you can play your game at real-time speed accompanied with crisp and detailed imaging. Philips Evnia 25M2N3200W/00. Display diagonal: 62.2 cm (24.5"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 1 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. VESA mounting, Height adjustment. Product colour: Grey





Display		Ergonomics	
Display diagonal *	62.2 cm (24.5")	Height adjustment	13 cm
Display resolution *	1920 x 1080 pixels	Pivot	v
HD type *	Full HD	Pivot angle	-90 - 90°
Native aspect ratio *	16:9	Swivelling	1
Display technology *	LCD	Swivel angle range	-30 - 30°
Panel type *	VA	Tilt adjustment	1
Backlight type	W-LED	Tilt angle range	-5 - 20°
Touchscreen *	×	On Screen Display (OSD)	1
Display brightness (typical)	300 cd/m ²		Simplified Chinese, Traditional
Response time *	1 ms		Chinese, Czech, German, Dutch,
Anti-glare screen	1	On Screen Display (OSD) languages	English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian,
Screen shape *	Flat		
Contrast ratio (typical) *	3000:1		Swedish, Turkish, Ukrainian
Dynamic contrast ratio marketing name	Mega Infinity DCR	Plug and Play	
Maximum refresh rate *	240 Hz	LED indicators	Operation, Stand-by
Viewing angle, horizontal	178°	Power	
Viewing angle, vertical	178°	Energy efficiency class (SDR) *	E
Display number of colours *	1.07 billion colours	Energy efficiency class (HDR) *	Not available
Response time (fast)	0.5 ms	Energy consumption (SDR) per 1000	19 kWh
Pixel pitch	0.2832 x 0.2802 mm	hours *	
Pixel density	89.91 ppi	Power consumption (typical) *	27.7 W
Horizontal scan range	30 - 274 kHz	Power consumption (standby) *	0.5 W 0.3 W
Vertical scan range	48 - 240 Hz	Power consumption (off)	0.3 W 100 - 240 V
Viewable size, horizontal	54.4 cm	AC input voltage AC input frequency	50 - 60 Hz
Viewable size, vertical	30.3 cm	Power supply type	Internal
Display diagonal (metric)	62.2 cm	Energy efficiency scale	A to G
DDC/CI	1	European Product Registry for	
Haze rate	25%	Energy Labelling (EPREL) code	1503715
Surface hardness	3H	Operational conditions	
Colour depth	8 bit	Operating temperature (T-T)	0 - 40 °C
sRGB coverage (typical)	120%	Storage temperature (T-T)	-20 - 60 °C
NTSC coverage (typical)	101.5%		-20 - 00 C

Display		Operational conditions	
Display sRGB	1	Operating relative humidity (H-H)	20 - 80%
Performance		Operating altitude	0 - 3658 m
NVIDIA G-SYNC *	×	Non-operating altitude	0 - 12192 m
AMD FreeSync *	×	Weight & dimensions	
VESA Adaptive Sync support	~	Width (with stand)	557 mm
Component video sync	Separate sync	Depth (with stand)	239 mm
Flicker-free technology		Height (with stand)	508 mm
Low Blue Light technology		Weight (with stand)	4.64 kg
,	•	Width (without stand) Depth (without stand)	557 mm 64 mm
Multimedia		Height (without stand)	331 mm
Built-in speaker(s) *	×	Weight (without stand)	3.3 kg
Built-in camera *	×	Packaging data	5
Design		Package width	730 mm
Market positioning *	Gaming	Package depth	188 mm
Product colour *	Grey	Package height	420 mm
Colour name	Dark Slate	Package weight	7.6 kg
Feet colour	Black	Packaging content	
Ports & interfaces		Stand included	1
Built-in USB hub *	×	Cables included	AC, DisplayPort, HDMI
HDMI *	1	Manual	1
HDMI ports quantity	2	Sustainability	
HDMI version DisplayPorts quantity	2.0 1	Doesn't contain	Mercury, PVC/BFR
DisplayPort version	1.4	Other features	
Audio output	1	Low input lag	1
HDCP	1	Exterior finish type	Textured
HDCP version	1.4/2.2	Picture enhancement	SmartImage game
Ergonomics		Recyclable packaging material	100%
VESA mounting * Panel mounting interface	✔ 100 x 100 mm	Regulatory Approvals	CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV/ISO9241-307; TUV-BAUART
Cable lock slot *	1	EasyRead mode	1
Cable lock slot type	Kensington	LowBlue mode	1
Height adjustment *	✓	Mean time between failures (MTBF)	50000 h



8712581800673

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.