PHILIPS

Philips 27M1N3200ZS/00 tietokoneen litteä näyttö 68,6 cm (27") 1920 x 1080 pikseliä Full HD LED musta

Tuotemerkki : Philips Tuotekoodi: 27M1N3200ZS/00

Tuotteen nimi: 27M1N3200ZS/00

Gaming Monitor 27M1N3200ZS Full HD -pelinäyttö

Philips 27M1N3200ZS/00 tietokoneen litteä näyttö 68,6 cm (27") 1920 x 1080 pikseliä Full HD LED musta:

Tämä pelinäyttö sopii täydellisesti nopeatahtisten PC-pelien pelaamiseen. 165 Hz:n virkistystaajuus ja 1 ms:n vasteaika takaavat sujuvan pelikokemuksen. Näytön erittäin ohuet kehykset ja Ultra Wide-Color - tekniikka varmistavat visuaalisen mukaansatempaavuuden.

Philips 27M1N3200ZS/00. Näytön halkaisija: 68,6 cm (27"), Näytön erottelutarkkuus: 1920 x 1080 pikseliä, HD-tyyppi: Full HD, Näytön teknologia: LED, Vasteaika (tyypillinen): 4 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. VESA-kiinnitys. Tuotteen väri: musta





Display		Ergonomics	
Display diagonal *	68.6 cm (27")	Tilt adjustment	✓
Display resolution *	1920 x 1080 pixels	Tilt angle range	-5 - 20°
HD type * Native aspect ratio * Display technology * Panel type * Backlight type	Full HD 16:9 LED IPS W-LED	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Display brightness (typical)	250 cd/m²	Number of OSD languages	21
Response time *	4 ms	Plug and Play	✓
Anti-glare screen	✓	LED indicators	Operation, Stand-by
Screen shape *	Flat	Power	
Supported graphics resolutions	1920 x 1080 (HD 1080)	Energy efficiency class (SDR) *	E
Supported video modes Aspect ratio	1080p 16:9	Energy consumption (SDR) per 1000 hours *	21 kWh
Contrast ratio (typical) *	1100:1	Power consumption (typical) *	28.2 W
Dynamic contrast ratio marketing name	Mega Infinity DCR	Power consumption (standby) *	0.5 W
Maximum refresh rate *	165 Hz	Power consumption (off)	0.3 W 100 - 240 V
Viewing angle, horizontal	178°	AC input voltage AC input frequency	50 - 60 Hz
Viewing angle, vertical	178°	Power supply type	Internal
Display number of colours *	16.7 million colours	Energy efficiency scale	A to G
Response time (fast)	1 ms	European Product Registry for	1527514
Pixel pitch	0.3114 x 0.3114 mm	Energy Labelling (EPREL) code	1327314
Pixel density	81.59 ppi 48 - 165 Hz	Operational conditions	
Vertical scan range Viewable size, horizontal	48 - 103 п2 59.8 cm	Operating temperature (T-T)	0 - 40 °C
Viewable size, Horizontal	33.6 cm	Storage temperature (T-T)	-20 - 60 °C
Display diagonal (metric)	68.5 cm	Operating relative humidity (H-H)	20 - 80%
DDC/CI	✓	Operating altitude	0 - 3658 m
Haze rate	25%	Non-operating altitude	0 - 12192 m
Surface hardness	3H	Weight & dimensions	
sRGB coverage (typical)	122%	Width (with stand)	612 mm

Display		Weight & dimensions	
NTSC coverage (typical) Adobe RGB coverage Display sRGB	107% 90.4% ✓	Depth (with stand) Height (with stand) Weight (with stand)	193 mm 449 mm 5.15 kg
Performance		Width (without stand)	612 mm
AMD FreeSync * AMD FreeSync type	type FreeSync Premium Weight (without stand)	Height (without stand)	55 mm 365 mm 3.7 kg
Component video sync Flicker-free technology	Separate sync	Packaging data	
Design Market positioning * Gaming	Package width Package depth Package height	780 mm 186 mm 525 mm	
Product colour *	Black	Package weight	9.28 kg
Detachable stand	✓	Packaging content	,
Ports & interfaces		Stand included	✓
HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Audio output	✓ 2	Cables included Manual	DisplayPort, HDMI, Power ✓
	2.0	Sustainability	
	1 1.2 ✓	Sustainability compliance Doesn't contain	✓ Mercury, PVC/BFR
HDCP	✓	Other features	
HDCP version	1.4/2.2	Low input lag	✓
Ergonomics		Exterior finish type	Textured
VESA mounting * ✓ Panel mounting interface 100 x 1	√ 100 x 100 mm	Picture enhancement Recyclable packaging material	SmartImage game 100%
Wall mountable Cable lock slot *	<i>'</i>	Regulatory Approvals	CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV/ISO9241-307; TUV-BAUART
Cable lock slot type	Kensington	EasyRead mode	1
•	J	LowBlue mode	✓
		Compliance certificates	CB, Federal Communications Commission (FCC), ICES, RoHS, cTUVus
		Mean time between failures (MTBF)	50000 h



8712581802738

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.