

DELL P Series P2425 computer monitor 61.1 cm (24.1") 1920 x 1200 pixels WUXGA LCD Black

Brand : DELL

Product family: P Series

Product code: DELL-P2425

Product name : P2425

- 61.1cm (24.07") WUXGA 1920 x 1200 LED IPS

- 8ms, 16:10, 300cd/m², 1500:1

- USB, VGA, HDMI, DisplayPort

61.1cm (24.07") WUXGA 1920 x 1200 LED IPS, 16:10, 300cd/m², 16.7M, 8ms, 178°/178°, 1500:1

DELL P Series P2425 computer monitor 61.1 cm (24.1") 1920 x 1200 pixels WUXGA LCD Black:

Certified by TÜV for 4-star eye comfort, this 16:10 hub monitor offers enhanced visual comfort and offers up to 90W of power delivery.


DELL P Series P2425. Display diagonal: 61.1 cm (24.1"), Display resolution: 1920 x 1200 pixels, HD type: WUXGA, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:10, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black





Display		Ergonomics	
Display diagonal *	61.1 cm (24.1")	Swivelling	✓
Display resolution *	1920 x 1200 pixels	Swivel angle range	-45 - 45°
HD type *	WUXGA	Tilt adjustment	1
Native aspect ratio *	16:10	Tilt angle range	-5 - 21°
Display technology *	LCD	On Screen Display (OSD)	1
Panel type *	IPS	Plug and Play	1
LED backlight	 Image: A set of the set of the	LED indicators	· ·
Backlight type	LED		•
Touchscreen *	×	Power	
Display brightness (typical)	300 cd/m ²	Energy efficiency class (SDR) *	D
Response time *	8 ms	Energy efficiency class (HDR) *	Not available
Anti-glare screen	 Image: A set of the set of the	Energy consumption (SDR) per 1000 hours *	14 kWh
Screen shape *	Flat	Power consumption (typical) *	13.6 W
	640 x 480 (VGA), 720 x 400, 800 x	Power consumption (typical) *	0.3 W
Supported graphics resolutions	600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1600	Power consumption (standby)	74 W
		Power consumption (off)	0.3 W
	x 1200, 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)	AC input voltage	100 - 240 V
Contrast ratio (typical) *	1500:1	AC input frequency	50/60 Hz
Maximum refresh rate *	100 Hz	Input current	1.5 A
Viewing angle, horizontal	178°	Power supply type	Internal
Viewing angle, vertical	178°	Energy efficiency scale	A to G
Display number of colours *	16.7 million colours	European Product Registry for	1870858
Response time (fast)	5 ms	Energy Labelling (EPREL) code	10/0050
Pixel pitch	0.27 x 0.27 mm	Operational conditions	
Pixel density	94.07 ppi	Operating temperature (T-T)	0 - 40 °C
Horizontal scan range	30 - 83 kHz	Storage temperature (T-T)	-20 - 60 °C
Vertical scan range	48 - 76 Hz	Operating relative humidity (H-H)	10 - 80%
vertical scall range	40 - 70 HZ	Operating relative number (n-n)	10 - 00 %

Viewabic size, vertical viewabic size diagonal begindy diagonal (nech) 6 1.1 cmOperating altitude Non-operating alt	Display		Operational conditions	
Weink singlight1.11Name1.121.1		32.4 cm	•	0 - 5000 m
Surface handnessHead for the statusSurface handness94%Beth (with stand)31.8 mmBell controriview technology4Beth (with stand)36.4 mmPerformancVerfaceHeight (with stand)36.4 mmProference×With (with stand)35.8 mmAND FreeSync*×Neight (without stand)30.3 mmSurface technologyMindows 1000000000000000000000000000000000000				
Surface handness3HWith (with stand)31.8 mmSurface handness99%Depth (with stand)18.1 mmBell confortView technology-Height (with stand)18.4 mmPerformance×Weight (with stand)3.64 mmNUDA G-SYNC *ADepth (without stand)50 mmAND FreeSync *×Depth (without stand)3.13 mmAND FreeSync *×Depth (without stand)3.13 mmAnd FreeSync *×Depth (without stand)3.13 kmAnd DeresSync *Nindows 10, YesBezel with (sloc)6.7 mmSurportating systems supportedMeoCsBezel with (sloc)6.7 mmNac coperating systems supportedMeoCsBezel with (sloc)6.7 mmBuilt-in camera *Nac Coperating depth without stand)1.8 mm1.0 mmBuilt-in camera *Nac Coperating depth without stand)1.0 mm1.0 mmBuilt-in camera *Nac Coper	Display diagonal (metric)		Weight & dimensions	
SRGE overge (typical)99%Depth (with stand)181.8 mmDel confort/we technology </td <td>Surface hardness</td> <td>ЗН</td> <td>-</td> <td>531.8 mm</td>	Surface hardness	ЗН	-	531.8 mm
Deal control type to technologyPerformanceHeight (with stand)94 mmPerformanceWeight (with stand)65 kgWODA C-SYNC-XDepth (without stand)531.8 mmAND FreeSync *XDepth (without stand)343.7 mmFlicker free technologyHeight (without stand)343.7 mmWindow so persing systemsWindow S10.YesBezel width (top)6.7 mmSupportedMacOsBezel width (top)6.7 mmMac operating systems supportMacOsBezel width (top)6.7 mmBuilt-in came SystemsYPerkage weight6.7 S kgBuilt-in came SystemsXPerkage weight8.7 S kgBuilt-in came SystemsStand included1.8 mmProfuct Colour *BlackStand included9.6 Spstep-Kt HMI, USBProfuct Colour *BlackQuick stard guide<	5 77	99%		
NDIA G-SYNC*XWith (without stand)S11.8 mmAND freeSync*XDepth (without stand)S0.1mmFlicker free technologyYHeight (without stand)343.7 mmFlicker free technologyWindows 10, YesBezel with (top)S.1.8 kgwith dwa caperaling systemsWindows 10, YesBezel with (top)G.7 mmAuc caperaling systems supportedNacOSBezel with (top)G.7 mmMac caperaling systemsNacOSBezel with (top)G.75 kgBuilt-in cames *XPackage weightG.75 kgBuilt-in cames *StackerStacker (top)S.8Design-Package weightG.75 kgProtot colour *BlackStand includedSignaport, HDM, USBFort bezel colour *BlackStand includedSignaport, HDM, USBFort bezel colour *BlackStand includedSignaport, HDM, USBSouth signaportsGreyQuick start guide on signaport, HDM, USBNumber of USB Type-BuyersGreySustainability certificatesRecry Start, TCOUSB Type-Adwardsream portsGrade containability certificatesSignaport, HDM, USBUSB Type-Grownstream portsGrade containability certificatesSignaport, HDM, USBUSB Type-Grownstrea	Dell ComfortView technology	1		
ADD FreeSyreA ADD F	Performance		Weight (with stand)	4.66 kg
AnD integrite"A Constraint of Source of	NVIDIA G-SYNC *	×	Width (without stand)	531.8 mm
Index prediction systems supportedVindows 10, YesWeight (without stand)3.15 kqSupportedWindows 10, YesBezel with (iside)6.7 mmMac operating systems supportedMacOSBezel with (toptom)1.3 cmMutimediaEvel with (toptom)1.3 cmBuilt-in speaker(s)*XPackage weight6.75 kgBuilt-in camera*XPackage weight6.75 kgPoduct colourBlackCables includedDisplayPort, HDMI, USBProduct colourBlackCables includedDisplayPort, HDMI, USBPorte colourBlackCables included1.8 mPorts & InterfacesOutk start guide.4 mBuilt-in USB hub*1Sustainability compliance.4 mVomber of USB Type-4 downstream ports quantity1.6 mSustainability compliance.4 mUSB Type-4 downstream ports quantity1.6 mCarloo emissions, naplatic (kg of CO2)1.6 mUSB Power Delivery (USB PUP.5 mCarloo emissions, naplatic (kg of CO2)1.6 mUSB Power Delivery (USB PUP.5 mCarloo emissions, naplatic (kg of CO2)1.6 mUSB Power Delivery (USB PUP.5 mCarloo emissions, naplatic (kg of CO2)1.6 mUSB Power Delivery (USB PUP.5 mCarloo emissions, naplatic (kg of CO2)1.6 mUSB Power Delivery (USB PUP.5 mCarloo emissions, naplatic (kg of CO2)1.6 mUSB Power Delivery (USB PUP.5 mCarloo emissions, naplatic (kg of CO2)1.6 mUSB Power Delivery (USB PUP.4 m	AMD FreeSync *	×	• •	
Windows sperating systemsWindows 10, YesBacel width (isole)5.15 kgsupportedMacOSBezel width (isole)6.7 mmMac operating systems supportedMacOSBezel width (isole)6.7 mmMac operating systems supportedMacOSBezel width (isole)6.7 mmMultimediaYPackage weight0.3 cm0.3 cmBuilts names *XPackage weight0.57 kg0.3 cmDesignYPackage weight0.57 kg0.3 cm0.3 cmDesignKStand included0.3 cm0.3 cmProduct colour *BlackStand included0.3 cm0.3 cmPotte 5 interfacesGrey Outlot sale length1.8 m0.3 cm0.3 cm0.3 cm0.3 cmNumber of USB Type-B upstrem1Sustainability compliance $I.8 m0.3 cm0.3 cm$	Flicker-free technology	1	-	
suppord aux bac operating systems suppord MacOSMatco besch wildt (top) besch wildt (top)6.7 mm besch wildt (top) besch wildt (top) b		Windows 10 Yes		5
Number of USB hubbit spectral spinolate Backal spice spinolate Backal spice spinolate Spice spinolate Builtin space series X Packaging data Spinolate Builtin space series X Packaging data Spinolate Builtin space series X Packaging data Spinolate Product colour * Back Stand included Spinolate Y Product colour * Back Stand included Spinolate Y Ports colour * Back Stand included Spinolate Y Number of upstream ports Back Substanbility compliance Y Y Number of USB Type-Bupteram ports quantity Substanability compliance Y Y Y USB Type-Adownstream ports quantity A Carbon footprint (kg of CO2) S S USB Payne-Delivery USB PD Y Carbon emissions, analysicut missions, and s S S USB Payne Delivery USB PD Y Carbon emissions, energy usage missions, and s S S S S S S S S		WINDOWS 10, Yes		
Mutimedia > Package weight use and use of the second of t	Mac operating systems supported	MacOS		
Builts peaker(s)* X Package weight USB cable length 6.75 kg USB cable length Built nummer USB cable length 1.8 m Product colour* Black Stand included > Product colour* Black Stand included > Fort basel colour Black Cables included > Ports interfaces DisplayPort cable length 1.8 m Number of USS Types Bustream ports quantity 1 Sustainability compliance Number of USS Types Adomstream ports quantity 1 Sustainability certificates ENERGY STAR, TCO USB Type-A domstream ports quantity 1 Sustainability certificates ENERGY STAR, TCO USB Power Delivery (USB PD) Carbon fontsprint (kg of CO2e) 162 USB Power Delivery (USB PD) Carbon emissions, nonfacturing 7 USB Power Delivery (USB PD) Carbon emissions, logistic (kg of Quantity 13 USB Power Delivery (USB PD) 1 Carbon emissions, dendor (kg of CO2e) 13 USB Power Delivery (USB PD) 1 Carbon emissions, dendor (kg of CO2e) 63 <td>Multimedia</td> <td></td> <td></td> <td>1.5 cm</td>	Multimedia			1.5 cm
Built-in camera*XUSB cable length1.8 mDesignPackaging contentProduct colourBlackStand included✓Front beel colourBlackStand included✓Fort beet colourBlackCables includedØisplayPort, HDM, USBPorts call interfacesUSB hub*I.8 mBuilt-in USB hub*SustainabilityI.8 mNumber of upstream ports1Sustainability compliance✓Number of USB Type-B upstream ports quantity1Sustainability compliance✓USB Type-C downstream ports quantity1Sustainability compliance✓USB Power Delivery (USB PD)✓Carbon footprint (Carbon emissions, manufacturing (Kg of CO2e)162USB Power Delivery (USB PD)✓Carbon emissions, energy usage (Kg of CO2e)13USB Power Delivery (USB PD)✓Carbon emissions, energy usage (Kg of CO2e)13USB Power Delivery (USB PD)✓Carbon emissions, energy usage (Kg of CO2e)35USB Power Delivery (USB PD)✓Carbon emissions, energy usage (Kg of CO2e)36USB Power Delivery (USB PD)✓Carbon emissions, energy usage (Kg of CO2e)36USB Power Delivery (USB PD)✓Carbon emissions, energy usage (Kg of CO2e)36USB Power Delivery (USB PD)✓Carbon emissions, energy usage (Kg of CO2e)36UDM ports quantity1Carbon emissions, energy usage (Kg of CO2e)36UDM ports quantity<	Built-in speaker(s) *	×		6 75 kg
DesignPackaging contentProduct colourBlackStand included/Front bezel colourBlackCables includedDisplayPort, HDMI, USBFeet colourGreyQuick start guide/Ports & interfacesJ.B mI.B mBuilt-in USB hub*MDM cable length1.8 mNumber of USE Type-B upstream1Sustainability complianceMERGY STAR, TCOVomber of USB Type-A downstream ports3Sustainability complianceMERGY STAR, TCOQuantity3Carbon footprintMercer, Mercury, PVC/BFRUSB Type-C downstream ports1Carbon emissions, manufacturing79Quantity15Sustainability compliance162USB Power Delivery (USB PD)15Carbon emissions, nanufacturing79VGA (D-Sub) ports quantity1Carbon emissions, nanufacturing70VGA (D-Sub) ports quantity1Carbon emissions, nanufacturing70USB Power Delivery (USB PO).Y100100VGA (D-Sub) ports quantity1Carbon emissions, endorg usage67UDI ports quant	Built-in camera *	×	5 5	5
Produccolour*Black BackStand included·Front bezel colourBackCables includedDisplayPort, HDMI, USBFeet colourOuick start guide·Forts finterfacesJanaJanaBuilt-in USB hub*·IamaNumber of upstream ports1SustainabilityNumber of USType-8 downstream ports1Sustainability complianceVSB Type-4 downstream ports-Sustainability conflicanceVSB Type-4 downstream ports-Carbon fontprint (kg of CO2e)USB Type-2 downstream ports-Total carbon footprint (kg of CO2e)USB Type-2 downstream ports-Carbon emissions, manufacturing (kg of CO2e)USB Power Delivery UDS PD0·Total carbon footprint (kg of CO2e)USB Power Delivery UDS PD1-Carbon emissions, nanufacturing (kg of CO2e)USB Power Delivery UDS PD2·Carbon emissions, logistics (kg of CO2e)USB Power Delivery UDS PD3-Carbon emissions, energy usage(kg CO2e)USB Power Delivery UDS PD3-Carbon emissions, energy usage(kg of CO2e)USB Power Delivery UDS PD3-Carbon emissions, energy usage(kg of CO2e)USB Power Delivery UDS PD3-Carbon emissions, energy usage(kg of CO2e)USB Power Delivery UD	Design		-	
Front bezel colour Black Cables included DisplayPort, HDMI, USB Feet colour Grey Quick start guide Ports & interfaces DisplayPort cable length 1.8 m Bullish USB hub* Sustainability 1.8 m Number of USB Type-B upstream ports quantity 1 Sustainability compliance USB Type-C downstream ports quantity 3 Sustainability compliance USB Type-C downstream ports quantity 3 Carbon fortoprint Kercury, PVC/BFR USB Poye-C downstream ports quantity 1 Carbon emissions, manufacturie (kg of CO2e) 162 162 USB Power Delivery UDS PDN Carbon emissions, logistics (kg of CO2e) 13 162 USB Power Delivery UD 0 15 W Carbon emissions, logistics (kg of CO2e) 13 162 USB Power Delivery UD 0 14 Carbon emissions, logistics (kg of CO2e) 3 3 USB Power Delivery UD 0 14 Carbon emissions, logistics (kg of CO2e) 3 3 USB Power Delivery UP 0 14 Alaversrion Gali versrion 1, 2024	Product colour *	Black		1
Prefer Color Origo Quick start guide Image: Procession of the start guide Image: Procession of the start guide Ports & interfaces DisplayPort cable length 1.8 m Built-in USB hub* Image: Procession of the start guide 1.8 m Number of USB Type-B upstream ports Image: Procession of the start guide Image: Procession of the start guide SUSS Type-A downstream ports Image: Procession of the start guide Image: Procession of the start guide Image: Procession of the start guide Quantity Image: Procession of the start guide Sustainability compliance Image: Procession of the start guide Image: Procession of the start guide Quantity Image: Procession of the start guide Quantity Image: Procession of the start guide Image: Procession o	Front bezel colour	Black		
Ports & interfaces DisplayPort cable length 1.8 m Builto USB hub* HDM cable length 1.8 m Number of USB Type-B upstream 1 Sustainability compliance VBB Type-B downstream ports 3 Sustainability certificates USB Type-C downstream ports 3 Carbon footprint Arsenics Mercury, PVC/BFR USB Power Delivery (USB PD) Total carbon footprint (kg of CO2e) 162 USB Power Delivery up to 15 W Carbon emissions, nengray usage (kg of CO2e) 3 USB Power Delivery up to 14 Carbon emissions, energy usage (kg of CO2e) 3 USB Power Delivery up to 1.4 Carbon emissions, energy usage (kg of CO2e) 3 USB Power Delivery up to 1.4 Carbon emissions, energy usage (kg of CO2e) 3 USB Power Delivery up to 1.4 Carbon emissions, whore usage (kg of CO2e) 3 USB Power Delivery up to 1.4 Carbon emissions, whore usage (kg of CO2e) 3 USB Power Delivery up to 1.4 Carbon emissions, whore usage (kg of CO2e) 3 USP were Delivery up to (kg of CO2e)	Feet colour	Grey		
Built-in USB hub* I Index of upstream ports I.a m Number of upstream ports I Sustainability I Number of USB Type-B upstream ports I Sustainability compliance I USB Type-A downstream ports 3 Sustainability compliance INERGY STAR, TCO USB Type-C downstream ports 1 Carbon footprint Nercury, PVC/BFR USB Power Delivery (USB PD) I Carbon footprint (kg of CO2) I62 USB Power Delivery up to IS W Carbon emissions, manufacturing 79 USB Power Delivery up to IS W Carbon emissions, olgistics (kg of CO2) Ia USB Power Delivery up to I Carbon emissions, energy usage (kg Ia HDMI version I.4 Carbon emissions, end-of-life (kg of CO2) Ia IDSplayPorts quantity I.4 Carbon emissions, end-of-life (kg of CO2) Ia HDMP I.4 Co2e Garbon emissions, end-of-life (kg of CO2) Ia IDSplayPort version I.4 Co2e Garbon emissions, end-of-life (kg of CO2) Ia HDCP IA	Ports & interfaces		-	
Number of USB Type-B upstream ports quantity1Sustainability certificates<	Built-in USB hub *	1		
Number of USB Type-B upstream ports quantity1Sustainability complianceUSB Type-A downstream ports quantity3Sustainability certificatesENERGY STAR, TCO Doen't containUSB Type-A downstream ports quantity1Carbon footprintArsenic, Mercury, PVC/BFRUSB Power Delivery (USB PD)<	Number of upstream ports	1	Sustainability	
USB Type-A downstream ports quantity 3 Sustainability certificates poesn't contain ENERGY STAR, TCO Arsenic, Mercury, PVC/BFR USB Type-C downstream ports quantity 1 Carbon footprint (rg of Co2e) 162 USB Power Delivery (USB PD) Total carbon footprint (kg of CO2) 162 USB Power Delivery up to 15 W Carbon emissions, manufacturin (kg of CO2e) 79 VGA (D-Sub) ports quantity 1 Carbon emissions, logistics (kg of CO2e) 13 HDMI version 1.4 Carbon emissions, energy usage (kg of CO2e) 67 DisplayPorts quantity 1.4 Carbon emissions, energy usage (kg of CO2e) 68 HDMI version 1.4 Carbon emissions, energy usage (kg of CO2e) 68 DisplayPorts quantity 1.2 Carbon emissions, w/o use phase (kg of CO2e) 68 HDCP PAIA version GaBi version 1, 2024 HDCP PAIA version GaBi version 1, 2024 HDCP version 1.4 Carbon emissions, M/o use phase (kg of CO2e) RHS, TŪV mark VESA mounting * Parad-spactific features Version <td></td> <td>1</td> <td>-</td> <td>1</td>		1	-	1
Quantity Deesn't contain Arsenic, Mercury, PVC/BFR VSB Type-C downstream ports quantity 1 Carbon footprint 1 VSB Power Delivery (USB PD) Total carbon footprint (kg of CO2e) 162 VSB Power Delivery (USB PD) 15 W Carbon emissions, manufacturing (kg of CO2e) 79 VGA (D-Sub) ports quantity 15 W Carbon emissions, logistics (kg of CO2e) 13 HDMI version 1.4 Carbon emissions, energy usage (CO2e) 67 DisplayPort version 1.4 Carbon emissions, end-of-life (kg of CO2e) 63 DisplayPort version 1.2 Carbon emissions, wolu ose (Kg of CO2e) 95 HDCP Palc carbon emissions, wolu ose (Kg of CO2e) 95 HDCP version 1.4 Carbon emissions, wolu ose (Kg of CO2e) 95 HDCP version 1.4 Carbon emissions, wolu ose (Kg of CO2e) 95 Feromonics 1.4 Carbon emissions, wolu ose (Kg of CO2e) 95 VEX mounting * * Carbon emissions, wolu ose (Kg of CO2e) 96 VSA mounting * * Som (Kg of CO2e) So		2	Sustainability certificates	ENERGY STAR, TCO
quantityICarbon tootprintUSB Power Delivery (USB PD)<		5	Doesn't contain	Arsenic, Mercury, PVC/BFR
Control Houring (Ed. 1)15 WCarbon emissions, manufacturing (kg of CO2e)79VGA (D-Sub) ports quantity1Carbon emissions, logistics (kg of CO2e)13HDMI *Carbon emissions, logistics (kg of of CO2e)67HDMI version1.4Carbon emissions, energy usage (kg of CO2e)67DisplayPorts quantity1Carbon emissions, energy usage (kg of CO2e)67DisplayPort version1.4Carbon emissions, end-of-life (kg of CO2e)63HDDP version1.2Total carbon emissions, w/o use phase (kg of CO2e)95HDCPAOther features638 version 1, 2024HDCP version1.4Corbon ecrificatesRoHS, TÜV markAC (power) inAOther features74VESA mounting interface100 x 100 mmPall pisplay Manager (DDM) compatibilityACable lock slot *SenSenHeight adjustment *SenFivot </td <td></td> <td>1</td> <td>Carbon footprint</td> <td></td>		1	Carbon footprint	
Obside Dentry up toIs in(kg of CO2e)19VGA (D-Sub) ports quantity1Carbon emissions, logistics (kg of CO2e)13HDMI *ACarbon emissions, energy usage (kg of CO2e)67HDMI version1.4Carbon emissions, energy usage (kg of CO2e)67DisplayPorts quantity1Carbon emissions, energy usage (kg of CO2e)63DisplayPort version1.2Total carbon emissions, w/o use phase (kg of CO2e)95HDCPPAIA versionGaBi version 1, 2024HDCPCompliance certificatesRolfs, TÜV markFromomicsCompliance certificatesRolfs, TÜV markVESA mounting *Pell Display Manager (DDM) compatibilityPanel mounting interface100 x 100 mmCompliance crtificatesFunctional featuresCable lock slot *Seminter Seminter Semi	USB Power Delivery (USB PD)	1	Total carbon footprint (kg of CO2e)	162
VGA (D-Sub) ports quantity1Carbon emissions, logistics (kg of CO2e)13HDMI orts quantity1Carbon emissions, energy usage (kg of CO2e)67HDMI version1.4Carbon emissions, energy usage (kg of CO2e)67DisplayPorts quantity1Carbon emissions, end-of-life (kg)67DisplayPort version1.2Total carbon emissions, w/o use phase (kg of CO2e)95HDCP✓VPAIA versionGaBi version 1, 2024HDCP version1.4Carbon emissions, w/o use phase (kg of CO2e)95HDCP version1.4Compliance certificatesRoHS, TÜV markFergonomics✓Pand-specific featuresVVESA mounting *✓Pell Display Manager (DDM) compatibility-Panel mounting interface✓Pell Display Manager (DDM) compatibility-Cable lock slot *✓-Height adjustment *✓Height adjustment *✓Front✓FrontFrontCable lock slot type-Height adjustment *-HowHowHowHordHordHordHordCable lock slot type <td>USB Power Delivery up to</td> <td>15 W</td> <td></td> <td>79</td>	USB Power Delivery up to	15 W		79
HDMI*✓✓CO2e)13HDMI ports quantity1Carbon emissions, energy usage (kg of CO2e)67HDMI version1.4Carbon emissions, energy usage (kg of CO2e)67DisplayPorts quantity1Carbon emissions, end-of-life (kg) CO2e)4DisplayPort version1.2Total carbon emissions, w/o use phase (kg of CO2e)95HDCP✓✓PAIA versionGaBi version 1, 2024HDCP version1.4Other featuresCompliance certificatesRoHS, TÜV markAC (power) in✓✓Compliance certificatesRoHS, TÜV markFeronomics✓Pall bisplay Manager (DDM) compatibility✓✓VESA mounting interface100 x 100 mmPoll Display Manager (DDM) compatibility✓✓Cable lock slot *✓✓✓✓Height adjustment *✓✓✓✓Height adjustment *✓✓✓✓Fivot✓✓✓✓✓Pivot✓✓✓✓✓Pivot✓✓✓✓✓Pivot✓✓✓✓✓Hor Height adjustment✓✓✓✓Pivot✓✓✓✓✓Hor Height adjustment✓✓✓✓Hor Height adjustment✓✓✓✓Hor Height adjustment✓✓✓✓Hor Height adjustment	VGA (D-Sub) ports quantity	1	-	
HDMI version1.4of CO2e)DisplayPorts quantity1Carbon emissions, end-of-life (kg of CO2e)4DisplayPort version1.2Carbon emissions, w/o use phase (kg of CO2e)95Headphone out *×PAIA cersionGaBi version 1, 2024HDCP·AOther featuresGaBi version 1, 2024HDCP version1.4Other featuresRoHS, TÜV markAC (power) in··Compliance certificatesRoHS, TÜV markFrgonomics·Pand-specific featuresCompliance certificatesRoHS, TÜV markVESA mounting interface100 x 100 mmPell Display Manager (DDM) compatibility··Cable lock slot *·····Cable lock slot typeKensington····Height adjustment *······Pivot·······Pivot·······Pivot·······Pivot·······Pivot·······Pivot·······Pivot·······Pivot·······Pivot·······	HDMI *	1	CO2e)	
HDMI version1.4of CO2e)DisplayPorts quantity1Carbon emissions, end-of-life (kg of CO2e)4DisplayPort version1.2Carbon emissions, w/o use phase (kg of CO2e)95Headphone out *×PAIA cersionGaBi version 1, 2024HDCP·AOther featuresGaBi version 1, 2024HDCP version1.4Other featuresRoHS, TÜV markAC (power) in··Compliance certificatesRoHS, TÜV markFrgonomics·Pand-specific featuresCompliance certificatesRoHS, TÜV markVESA mounting interface100 x 100 mmPell Display Manager (DDM) compatibility··Cable lock slot *·····Cable lock slot typeKensington····Height adjustment *······Pivot·······Pivot·······Pivot·······Pivot·······Pivot·······Pivot·······Pivot·······Pivot·······Pivot·······			Carbon emissions, energy usage (kg	67
DisplayPort version1.2CO2e)4DisplayPort version1.2Total carbon emissions, w/o use phase (kg of CO2e)95HDCP✓✓PAIA versionGaBi version 1, 2024HDCP version1.4 Other features Compliance certificatesRoHS, TÜV markAC (power) in✓Compliance certificatesRoHS, TÜV mark Ergonomics ✓Dell Display Manager (DDM) compatibility✓VESA mounting *✓Dell Display Manager (DDM) compatibility✓Cable nanagement✓✓✓Cable lock slot type✓✓✓Height adjustment *✓✓✓Height adjustment *✓✓✓Pivot✓✓✓			of CO2e)	
Headphone out *XTotal carbon emissions, w/o use phase (kg of CO2e)95HDCPPAIA versionGaBi version 1, 2024HDCP version1.4 Other features Compliance certificatesRoHS, TÜV markAC (power) in Brand-specific features Compliance (DDM)CompatibilityFrgonomicsDell Display Manager (DDM)VESA mounting interfaceDell Display Manager (DDM)Cable lock slot * </td <td></td> <td></td> <td></td> <td>4</td>				4
HDCP Image: Marcine stream of the second s				95
HDCP version 1.4 AC (power) in • Compliance certificates RoHS, TÜV mark Frgonomics Frand-specific features VESA mounting * • Panel mounting interface 100 x 100 mm Cable lock slot * • Cable lock slot type • Height adjustment * • Freident * • <td>HDCP</td> <td>1</td> <td></td> <td>GaBi version 1, 2024</td>	HDCP	1		GaBi version 1, 2024
AC (power) in Image: Compliance certificates RoHS, TÜV mark Ergonomics Brand-specific features Brand-specific features VESA mounting * Image: Compliance certificates Dell Display Manager (DDM) compatibility Image: Compliance certificates Panel mounting interface Image: Compliance certificates Dell Display Manager (DDM) compatibility Image: Compliance certificates Cable management Image: Compliance certificates Sector compatibility Image: Compliance certificates Cable lock slot * Image: Compliance certificates Sector certificates Image: Compliance certificates Flaght adjustment * Image: Compliance certificates Image: Compliance certificates Image: Compliance certificates Floght adjustment Image: Compliance certificates Image: Compliance certificates Image: Compliance certificates Floght adjustment Image: Compliance certificates Image: Compliance certificates Image: Compliance certificates Floght adjustment Image: Compliance certificates Image: Compliance certificates Image: Compliance certificates Floght adjustment Image: Compliance certificates Image: Compliance certificates Image: Compliance certificates Floght adjustment Image: Compliance ce	HDCP version	1.4		•
Frgonomics Brand-specific features VESA mounting * Panel mounting interface 100 x 100 mm Cable management Cable lock slot * Cable lock slot type Kensington Height adjustment * 15 cm Piot	AC (power) in	1		RoHS. TÜV mark
VESA mounting *·Panel mounting interface100 x 100 mmCable management·Cable lock slot *·Cable lock slot typeKensingtonHeight adjustment *·15 cmPiot·	Ergonomics		·	,
Panel mounting interface 100 x 100 mm compatibility Cable management ✓ Cable lock slot * ✓ Cable lock slot type Kensington Height adjustment * ✓ 15 cm Pivot ✓	VESA mounting *	1	•	
Cable lock slot *✓Cable lock slot typeKensingtonHeight adjustment *✓Height adjustment *15 cmPivot✓	Panel mounting interface	100 x 100 mm		v
Cable lock slot typeKensingtonHeight adjustment*✓Height adjustment15 cmPivot✓	Cable management	1		
Height adjustment * ✓ Height adjustment 15 cm Pivot ✓	Cable lock slot *	1		
Height adjustment 15 cm Pivot ✓	Cable lock slot type	Kensington		
Pivot 🗸	Height adjustment *	1		
	Height adjustment	15 cm		
Pivot angle -90 - 90°				
	Pivot angle	-90 - 90°		





5397184821671

0884116468639



884116468639

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.