## StarTech.com USB31CCV1M USB-kaapeli USB 3.2 Gen 2 (3.1 Gen 2) 1 m USB C musta, Harmaa

Tuotemerkki : StarTech.com

Tuotekoodi: USB31CCV1M


Tuotteen nimi : USB31CCV1M

StarTech.com USB31CCV1M. Johdon pituus: 1 m. Liitin 1: USB C, Liitin 2: USB C, USB-versio: USB 3.2 Gen 2 (3.1 Gen 2), Suurin tiedonsiirtonopeus: 10 Gbit/s, Liittimien kontaktipinnoite: Nikkeli, Tuotteen väri: musta, Harmaa





| Features   |  | Power   |                                   |
|--|--|---|-----------------------------------|
| USB version *  | nnector 1 *USB Cunector 2 *USB Cunector 1 gender *Maleunector 2 gender *Maleunector 2 gender *Maleunector 1 form factorStraightunector 2 form factorStraightunector contacts platingNickelole jacket materialThermoplastic elastomer (TPE)ole shieldingAluminum mylar foilkimum data transfer rate10 Gbit/sduct colour *Black, Greyg and Play< | Output current (max)  | 5 A                               |
| Connector 1 *  |  | Weight & dimensions   |                                   |
| Connector 2 *<br>Connector 1 gender *<br>Connector 2 gender *<br>Connector 1 form factor             |  | Cable length *<br>Cable diameter<br>Weight<br>Baskaging data                                | 1 m<br>4.8 mm<br>44 g             |
| Connector 2 form factor  |  | Packaging data  |                                   |
| Connector contacts plating<br>Cable jacket material<br>Cable shielding<br>Maximum data transfer rate |  | Package width<br>Package depth<br>Package height<br>Package weight                          | 125 mm<br>220 mm<br>10 mm<br>95 g |
| Maximum data transfer rate   |  | Packaging content   |                                   |
| Product colour *   |  | Quantity per pack *   | 1 pc(s)                           |
| 5 <i>,</i>   |  | Logistics data  |                                   |
| USB Power Delivery revision<br>USB Power Delivery up to  |  | Products per master (outer) case<br>Master (outer) case width<br>Master (outer) case longth | 160 pc(s)<br>390 mm               |
| Power  |  | Master (outer) case length<br>Master (outer) case height                                    | 430 mm<br>290 mm                  |
| Output voltage   | 20 V   | Harmonized System (HS) code   | 84733080                          |





065030893312

0065030893312

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.