PHILIPS

Philips E-Line 65BDL4152E/00 Digitaalinen litteä infotaulu 165,1 cm (65") Wi-Fi 400 cd/m² 4K Ultra HD musta Kosketusnäyttö Sisäänrakennettu prosessori Android 18/7

Tuotemerkki : Philips Tuotekoodi: 65BDL4152E/00

Tuotteen nimi: E-Line 65BDL4152E/00

Philips E-Line 65BDL4152E/00. Tuotteen muotoilu: Digitaalinen litteä infotaulu. Näytön halkaisija: 165,1 cm (65"), Näytön erottelutarkkuus: 3840 x 2160 pikseliä, Näytön kirkkaus: 400 cd/m², HD-tyyppi: 4K Ultra HD, Kosketusnäyttö. Wi-Fi. Toiminta-aika (tunteja/päiviä): 18/7. Käyttöjärjestelmä asennettu: Android. Tuotteen väri: musta

Display		Design	
Panel type	IPS	Bezel width (side)	1.67 cm
Display diagonal *	165.1 cm (65")	Bezel width (top)	1.67 cm
Display resolution *	3840 x 2160 pixels	Anti-glare screen	✓
Display brightness *	400 cd/m ²	Fingerprint resistant	✓
HD type *	4K Ultra HD	Performance	
Touchscreen *	✓	Purpose *	Universal
Touchscreen technology	Infrared	On Screen Display (OSD)	J.
Number of simultaneous touchpoints	40	On Screen display (OSD)	Arabic, Simplified Chinese,
Multi-touch	,		Traditional Chinese, Danish,
Native aspect ratio	16:9	On Screen Display (OSD) languages	German, Dutch, English, Spanish,
Contrast ratio (typical)	1200:1		Finnish, French, Italian, Japanese, Norwegian, Polish, Portuguese,
Contrast ratio (dynamic)	500000:1		Russian, Swedish, Turkish
Viewing angle, horizontal	178°	Operating hours (hours/days)	18/7
Viewing angle, vertical	178°	Mean time between failures (MTBF)	50000 h
Display number of colours	1.07 billion colours	Power	
Pixel pitch	0.372 x 0.372 mm	Power consumption (standby) *	0.5 W
Display diagonal (metric)	163.9 cm	Energy efficiency class (SDR)	G
Native refresh rate	60 Hz	AC input voltage	100 - 240 V
Ports & interfaces		AC input frequency	50 - 60 Hz
HDMI ports quantity *	3	Computer system	
HDMI version	2.0	Computer system *	1
HDMI input ports quantity	2	Computer system type	System on Chip (SoC)
HDMI output ports quantity	1	Built-in processor *	/
DVI port *	×	Processor architecture	ARM Cortex-A53+Cortex-A73
USB port *	✓	On-board graphics card model	ARM Mali-G52
USB ports quantity	8	Internal storage capacity	32 GB
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)	Operating system installed	Android
USB connector type	Micro-USB B, USB Type-A, USB Type-B, USB Type-C	Operating system version	13
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	3	Video formats supported	H.263, H.264, H.265, MPEG1, MPEG2, MPEG4, VP8, VP9
ports quantity	3	Audio formats supported	AAC, HE-AAC, MPEG
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Image formats supported	BMP, JPEG, PNG
USB Power Delivery (USB PD)	✓	Weight & dimensions	
USB Power Delivery up to	65 W	Display width	1492 mm
Ethernet LAN *	✓	Display depth	116.2 mm
Ethernet LAN (RJ-45) ports	2	Display height	892.3 mm
Wi-Fi *	✓	Packaging content	
RS-232C	✓	Remote control included	✓
Remote (IR) input	1	Batteries included	/
Remote (IR) output	1	Stylus pen	
Card reader integrated	✓	Number of stylus pens	2
		Number of Stylus pens	2

Ports & interfaces		Packaging content	
Compatible memory cards	MicroSD (TransFlash)	Cables included	AC, HDMI, USB
OPS module slot	✓	Operational conditions	
Audio Built-in speaker(s) *		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 20 - 80%
Number of built-in speakers RMS rated power	2 40 W	Storage temperature (T-T) Storage relative humidity (H-H)	-20 - 60 °C 5 - 95%
Design		Certificates	
Product design * Digital signage flat p Placement supported * Indoor Orientation Horizontal/Vertical Product colour * Black Screen shape Flat VESA mounting * ✓ Panel mounting interface 500 x 400 mm Bezel width (bottom) 4.19 cm	Digital signage flat panel	Certification	CE, FCC, Class A, RoHS, CB, EAC, EMF, ETL
		Technical details	
	Flat ✓ 500 x 400 mm	Display resolution at frequency	640 x 350 70Hz 640 x 480 60, 67, 72, 75Hz 800 x 600 56, 60, 72, 75Hz 832 x 624 75Hz 848 x 480 60Hz 960x720 75Hz 1024x768 60,70Hz 1152 x 864 60, 70, 75Hz 1152 x 900 66Hz 1280 x 720 60,70Hz 1280 x 768 60Hz, 75Hz 1280 x 800 60,75Hz 1280 x 960 60Hz 1280x1024 60,67,75Hz 1360 x 768 60Hz 1366 x 768 60Hz 1400 x 1050 60, 75Hz 1600 x 900 60Hz 1600 x 1200 60Hz 1680 x 1050 60Hz 1920 x 1080 60Hz 1920 x 1200 60Hz 3840 x 2160 24,25,30,60Hz 1440 x 900 60Hz 720 x 400 70Hz

