

DELL UltraSharp U4025QW computer monitor 101.6 cm (40") 5120 x 2160 pixels 5K Ultra HD LCD Silver

Brand : DELL Product family: UltraSharp Product code: DELL-U4025QW

Product name: U4025QW

- 101.6cm (40") 5K Ultra HD 5120 x 2160 LED IPS
- 8ms, 21:9, 450cd/m², 2000:1
- USB, HDMI, DisplayPort

101.6cm (40") 5K Ultra HD 5120 x 2160 LED IPS, 21:9, 450cd/m², 1.07B, 8ms, 178°/178°, 2000:1

DELL UltraSharp U4025QW computer monitor 101.6 cm (40") 5120 x 2160 pixels 5K Ultra HD LCD Silver:

Elevate your performance with a 40-inch curved Thunderbolt™ hub monitor featuring a stunning 5K display and a 120Hz refresh rate.

DELL UltraSharp U4025QW. Display diagonal: 101.6 cm (40"), Display resolution: 5120 x 2160 pixels, HD type: 5K Ultra HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 21:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub. VESA mounting, Height adjustment. Product colour: Silver











| Display | | Ergonomics | |
|--------------------------------|--|---|-------------|
| Display diagonal * | 101.6 cm (40") | Height adjustment * | ✓ |
| Display resolution * | 5120 x 2160 pixels | Height adjustment | 15 cm |
| HD type * | 5K Ultra HD | Swivelling | ✓ |
| Native aspect ratio * | 21:9 | Swivel angle range | -30 - 30° |
| Display technology * | LCD | Tilt adjustment | ✓ |
| Panel type * | IPS | Tilt angle range | -5 - 21° |
| Backlight type | LED | Picture-in-Picture | ✓ |
| Touchscreen * | × | On Screen Display (OSD) | ✓ |
| Display brightness (peak) | 600 cd/m² | Plug and Play | ✓ |
| Display brightness (typical) | 450 cd/m ² | LED indicators | ✓ |
| Response time * | 8 ms | Power | |
| Anti-glare screen | ✓ | Energy efficiency class (SDR) * | F |
| Screen shape * | Curved | Energy efficiency class (HDR) * | G |
| Screen curvature rating | 2500R | Energy consumption (SDR) per 1000 | 2 |
| Supported graphics resolutions | 640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2048 x 1152, 2048 x 1280, 2560 x 1080, 3840 x 2160, 4096 x 2160, 5120 x 2160 | hours * | J 40 kWh |
| | | Energy consumption (HDR) per 1000 hours * | 62 kWh |
| | | Power consumption (typical) * | 39.5 W |
| | | Power consumption (standby) * | 0.4 W |
| | | Power consumption (max) | 380 W |
| | | Power consumption (off) | 0.3 W |
| Supported video modes | 480p, 720p, 1080p | AC input voltage | 100 - 240 V |
| Contrast ratio (typical) * | 2000:1 | AC input frequency | 50/60 Hz |
| Maximum refresh rate * | 120 Hz | Input current | 4.2 A |
| Viewing angle, horizontal | 178° | Power supply type | Internal |
| Viewing angle, vertical | 178° | Energy efficiency scale | A to G |
| Display number of colours * | 1.07 billion colours | European Product Registry for | 1821612 |
| Response time (fast) | 5 ms | Energy Labelling (EPREL) code | |
| Pixel pitch | 0.1815 x 0.1815 mm | | |
| | | | |

| Display | | Operational conditions | |
|--|---|--|--|
| Pixel density | 140 ppi | Operating temperature (T-T) | 0 - 40 °C |
| Horizontal scan range | 25 - 280 kHz | Storage temperature (T-T) | -20 - 60 °C |
| Vertical scan range | 48 - 120 Hz | Operating relative humidity (H-H) | 10 - 80% |
| Viewable size, horizontal | 92.9 cm | Storage relative humidity (H-H) | 5 - 90% |
| Viewable size, vertical | 39.2 cm | Operating altitude | 0 - 5000 m |
| Viewable size diagonal | 100.9 cm | Non-operating altitude | 0 - 12192 m |
| High Dynamic Range (HDR) | | | · |
| supported | ✓ | Weight & dimensions | |
| Surface hardness | 3H | Width (with stand) | 946.6 mm |
| Colour gamut standard | DCI-P3 | Depth (with stand) | 252.8 mm |
| Colour gamut | 99% | Height (with stand) | 472.3 mm |
| sRGB coverage (typical) | 100% | Weight (with stand) | 11.7 kg |
| Dual ambient light sensor | 1 | Width (without stand) | 946.6 mm |
| Dell ComfortView technology | 1 | Depth (without stand) | 108 mm |
| Heat dissipation | 134.8 BTU/h | Height (without stand) | 419.1 mm |
| · | | Weight (without stand) | 8.35 kg |
| Performance | | Bezel width (side) | 1.13 cm |
| AMD FreeSync * | × | Bezel width (top) | 1.13 cm |
| Flicker-free technology | 1 | Bezel width (bottom) | 1.58 cm |
| Low Blue Light technology | 1 | Packaging data | |
| Windows operating systems | Windows 10, Yes | | 10 1 |
| supported | | Package weight | 19 kg |
| Mac operating systems supported | MacOS | USB cable length | 1 m |
| Multimedia | | Packaging content | |
| Number of speakers | 2 | Stand included | ✓ |
| RMS rated power | 18 W | Cables included | AC, DisplayPort, HDMI, Thunderbolt, |
| Built-in speaker(s) * | 1 | Cables ilicidded | USB Type-A to USB Type-C |
| Built-in camera * | × | Quick start guide | ✓ |
| Design | | DisplayPort cable length | 1.8 m |
| | C.I. | HDMI cable length | 1.8 m |
| Product colour * | Silver | Sustainability | |
| Front bezel colour | Black | Sustainability certificates | ENERGY STAR, TCO |
| Feet colour | Silver | Doesn't contain | PVC/BFR |
| Ports & interfaces | | | |
| Built-in USB hub * | ✓ | Carbon footprint | |
| Number of USB Type-C upstream | 2 | Total carbon footprint (kg of CO2e) | 480 |
| ports quantity | 2 | Carbon emissions, manufacturing | 197 |
| USB Type-A downstream ports | 5 | (kg of CO2e) | |
| quantity | | Carbon emissions, logistics (kg of CO2e) | 36 |
| USB Type-C downstream ports quantity | 3 | Carbon emissions, energy usage (kg | |
| USB Type-C DisplayPort Alternate | | of CO2e) | 192 |
| Mode | ✓ | Carbon emissions, end-of-life (kg of | 55 |
| USB Power Delivery | 1 | CO2e) | JJ |
| • | • | | |
| USB Power Delivery up to | 140 W | Total carbon emissions, w/o use | 288 |
| USB Power Delivery up to HDMI * | 140 W | phase (kg of CO2e) | 288 |
| , , | | | 288 GaBi verison1 |
| HDMI * | ✓ | phase (kg of CO2e) | |
| HDMI * HDMI ports quantity | √ 1 | phase (kg of CO2e) PAIA version | |
| HDMI * HDMI ports quantity HDMI version | √ 1 2.1 | phase (kg of CO2e) PAIA version Other features | GaBi verison1 ✓ |
| HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version | 1 2.1 1 | phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free | GaBi verison1 |
| HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity | 1 2.1 1 1.4 | phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control | GaBi verison1 ✓ Hg (mercury) |
| HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output | 1 2.1 1 1.4 2 | phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates | GaBi verison1 ✓ Hg (mercury) ✓ RoHS |
| HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out * | 1 2.1 1 1.4 2 | phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates | GaBi verison1 ✓ Hg (mercury) ✓ RoHS 2500 Mbit/s |
| HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out * Built-in KVM switch | 1 2.1 1 1.4 2 | phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates Ethernet LAN (RJ-45) ports | GaBi verison1 ✓ Hg (mercury) ✓ RoHS |
| HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out * Built-in KVM switch HDCP | 1 2.1 1 1.4 2 ✓ | phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates | GaBi verison1 ✓ Hg (mercury) ✓ RoHS 2500 Mbit/s |
| HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out * Built-in KVM switch HDCP HDCP version | 1 2.1 1 1.4 2 | phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates Ethernet LAN (RJ-45) ports Brand-specific features Dell Display Manager (DDM) | GaBi verison1 Hg (mercury) RoHS 2500 Mbit/s 1 |
| HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out * Built-in KVM switch HDCP HDCP version DC-in jack | 1 2.1 1 1.4 2 ✓ | phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates Ethernet LAN (RJ-45) ports Brand-specific features | GaBi verison1 ✓ Hg (mercury) ✓ RoHS 2500 Mbit/s |
| HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out * Built-in KVM switch HDCP HDCP version DC-in jack Ergonomics | 1 2.1 1 1.4 2 ✓ | phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates Ethernet LAN (RJ-45) ports Brand-specific features Dell Display Manager (DDM) | GaBi verison1 Hg (mercury) RoHS 2500 Mbit/s 1 |
| HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out * Built-in KVM switch HDCP HDCP version DC-in jack Ergonomics VESA mounting * | 1 2.1 1 1.4 2 4 ** 4 1.4/2.3 | phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates Ethernet LAN (RJ-45) ports Brand-specific features Dell Display Manager (DDM) | GaBi verison1 Hg (mercury) RoHS 2500 Mbit/s 1 |
| HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out * Built-in KVM switch HDCP HDCP version DC-in jack Ergonomics | 1 2.1 1 1.4 2 ✓ X ✓ 1.4/2.3 | phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates Ethernet LAN (RJ-45) ports Brand-specific features Dell Display Manager (DDM) | GaBi verison1 Hg (mercury) RoHS 2500 Mbit/s 1 |
| HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out * Built-in KVM switch HDCP HDCP version DC-in jack Ergonomics VESA mounting * | 1 2.1 1 1.4 2 4 ** 4 1.4/2.3 | phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates Ethernet LAN (RJ-45) ports Brand-specific features Dell Display Manager (DDM) | GaBi verison1 Hg (mercury) RoHS 2500 Mbit/s 1 |

Cable lock slot *

| _ | |
|------|----------|
| Fran | nomics |
| Ligo | 10111163 |

Cable lock slot type

Kensington





5397184821510

0884116452041



884116452041

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.