

DELL UltraSharp U4025QW tietokoneen litteä näyttö 101,6 cm (40") 5120 x 2160 pikseliä 5K Ultra HD LCD Hopea

Tuotemerkki : DELL

Tuoteperhe: UltraSharp

Tuotekoodi: DELL-U4025QW

Tuotteen nimi : U4025QW

DELL UltraSharp U4025QW. Näytön halkaisija: 101,6 cm (40"), Näytön erottelutarkkuus: 5120 x 2160 pikseliä, HD-tyyppi: 5K Ultra HD, Näytön teknologia: LCD, Vasteaika (tyypillinen): 8 ms, Vakiokuvasuhde: 21:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäiset kaiuttimet. Sisäänrakennettu USB-keskus. VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: Hopea





Display		Ergonomics	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * Backlight type Touchscreen * Display brightness (peak) Display brightness (typical) Backgroup time *	101.6 cm (40") 5120 x 2160 pixels 5K Ultra HD 21:9 LCD IPS LED X 600 cd/m ² 450 cd/m ² 8 ms	Height adjustment * Height adjustment Swivelling Swivel angle range Tilt adjustment Tilt angle range Picture-in-Picture On Screen Display (OSD) Plug and Play LED indicators	✓ 15 cm ✓ -30 - 30° ✓ -5 - 21° ✓ ✓
Response time * Anti-glare screen	8 ms	Power	•
Screen shape * Screen curvature rating Supported graphics resolutions	Curved 2500R 640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2048 x 1152, 2048 x 1280, 2560 x 1080, 3840 x 2160, 4096 x 2160, 5120 x 2160	Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Energy consumption (HDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max)	62 kWh 39.5 W 0.4 W 380 W
Supported video modes Contrast ratio (typical) * Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch	480p, 720p, 1080p 2000:1 120 Hz 178° 178° 1.07 billion colours 5 ms 0.1815 x 0.1815 mm	Power consumption (off) AC input voltage AC input frequency Input current Power supply type Energy efficiency scale European Product Registry for Energy Labelling (EPREL) code	0.3 W 100 - 240 V 50/60 Hz 4.2 A Internal A to G 1821612

Display		Onerstiens! conditions	
Display		Operational conditions	0.40.00
Pixel density	140 ppi 25 - 280 kHz	Operating temperature (T-T)	0 - 40 °C -20 - 60 °C
Horizontal scan range Vertical scan range	25 - 280 KHZ 48 - 120 Hz	Storage temperature (T-T) Operating relative humidity (H-H)	-20 - 60 °C
Viewable size, horizontal	92.9 cm	Storage relative humidity (H-H)	5 - 90%
Viewable size, vertical	39.2 cm	Operating altitude	0 - 5000 m
Viewable size diagonal	100.9 cm	Non-operating altitude	0 - 12192 m
High Dynamic Range (HDR) supported	 ✓ 	Weight & dimensions	
Surface hardness	ЗН	Width (with stand)	946.6 mm
Colour gamut standard	DCI-P3	Depth (with stand)	252.8 mm
Colour gamut	99%	Height (with stand)	472.3 mm
sRGB coverage (typical)	100%	Weight (with stand)	11.7 kg
Dual ambient light sensor	1	Width (without stand)	946.6 mm
Dell ComfortView technology	1	Depth (without stand)	108 mm
Heat dissipation	134.8 BTU/h	Height (without stand)	419.1 mm
Performance	·	Weight (without stand)	8.35 kg
		Bezel width (side)	1.13 cm
AMD FreeSync *	×	Bezel width (top) Bezel width (bottom)	1.13 cm
Flicker-free technology	✓	Bezel width (bottom)	1.58 cm
Low Blue Light technology	 Image: A set of the set of the	Packaging data	
Windows operating systems	Windows 10, Yes	Package weight	19 kg
supported		USB cable length	1 m
Mac operating systems supported Multimedia	MacOS	Packaging content	
	2	Stand included	 Image: A set of the set of the
Number of speakers RMS rated power	2 18 W	Cables included	AC, DisplayPort, HDMI, Thunderbolt,
·	16 W		USB Type-A to USB Type-C
Built-in speaker(s) *	-	Quick start guide	*
Built-in camera *	X	DisplayPort cable length	1.8 m
Design		HDMI cable length	1.8 m
Product colour *	Silver	Sustainability	
Front bezel colour	Black	Sustainability certificates	ENERGY STAR, TCO
Feet colour	Silver	Doesn't contain	PVC/BFR
Ports & interfaces		Carbon footprint	
Built-in USB hub *	✓	Total carbon footprint (kg of CO2e)	480
Built-in USB hub * Number of USB Type-C upstream ports quantity	2 2	Total carbon footprint (kg of CO2e) Carbon emissions, manufacturing (kg of CO2e)	480 197
Number of USB Type-C upstream		Carbon emissions, manufacturing	
Number of USB Type-C upstream ports quantity USB Type-A downstream ports	2	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of	197 36
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports	2 5	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg	197 36
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD)	2 5 3 •	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of	197 36 192
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to	2 5 3 • 140 W	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use	197 36 192 55
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to HDMI *	2 5 3 • 140 W	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e)	197 36 192 55 288
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to HDMI * HDMI ports quantity	2 5 3 140 W 1	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version Other features	197 36 192 55 288 GaBi version 1, 2024
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to HDMI * HDMI ports quantity HDMI version	2 5 3 ✓ 140 W ✓ 1 2.1	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP)	197 36 192 55 288 GaBi version 1, 2024 ✓
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to HDMI * HDMI ports quantity HDMI version DisplayPorts quantity	2 5 3 ✓ 140 W ✓ 1 2.1 1	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free	197 36 192 55 288 GaBi version 1, 2024 ✓
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version	2 5 3 ✓ 140 W ✓ 1 2.1 1 1.4	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control	197 36 192 55 288 36Bi version 1, 2024
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity	2 5 3 ✓ 140 W ✓ 1 2.1 1 1.4 2	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates	197 36 192 55 288 36Bi version 1, 2024 • Hg (mercury) • ROHS
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output	2 5 3 ✓ 140 W ✓ 1 2.1 1 1.4 2	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates	197 36 192 55 288 GaBi version 1, 2024
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out *	2 5 3 ✓ ✓ 140 W ✓ 1 2.1 1 1.4 2 ✓	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates Ethernet LAN (RJ-45) ports	197 36 192 55 288 36Bi version 1, 2024 • Hg (mercury) • ROHS
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out * Built-in KVM switch	2 5 3 ✓ 140 W ✓ 1 2.1 1 1.4 2	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates Ethernet LAN (RJ-45) ports Brand-specific features	197 36 192 55 288 GaBi version 1, 2024
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out * Built-in KVM switch HDCP	2 5 3 ✓ 140 W ✓ 1 2.1 1 1.4 2 ✓ ✓	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates Ethernet LAN (RJ-45) ports Brand-specific features Dell Display Manager (DDM)	197 36 192 55 288 GaBi version 1, 2024
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to HDMI * HDMI ports quantity HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out * Built-in KVM switch HDCP HDCP version	2 5 3 • • • 140 W • • 1 2.1 1 1.4 2 • • • • • • • • • • • • • • • • • •	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates Ethernet LAN (RJ-45) ports Brand-specific features	197 36 192 55 288 GaBi version 1, 2024 Hg (mercury) RoHS 2500 Mbit/s 1
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out * Built-in KVM switch HDCP	2 5 3 ✓ 140 W ✓ 1 2.1 1 1.4 2 ✓ ✓	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates Ethernet LAN (RJ-45) ports Brand-specific features Dell Display Manager (DDM)	197 36 192 55 288 GaBi version 1, 2024 Hg (mercury) RoHS 2500 Mbit/s 1
Number of USB Type-C upstream ports quantity USB Type-A downstream ports quantity USB Type-C downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery (USB PD) USB Power Delivery up to HDMI * HDMI ports quantity HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output Headphone out * Built-in KVM switch HDCP HDCP version	2 5 3 • • • 140 W • • 1 2.1 1 1.4 2 • • • • • • • • • • • • • • • • • •	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version Other features Picture-by-Picture (PbP) Heavy metals free Automatic brightness control Compliance certificates Ethernet LAN data rates Ethernet LAN (RJ-45) ports Brand-specific features Dell Display Manager (DDM)	197 36 192 55 288 GaBi version 1, 2024 Hg (mercury) RoHS 2500 Mbit/s 1

Ergonomics

Panel mounting interface Cable management Cable lock slot * Cable lock slot type 100 x 100 mm ✓ Kensington





5397184821510

0884116452041



884116452041

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.