




Lenovo 7Y37A01084 RAID-ohjain PCI Express x8 3.0 12000 Gbit/s

Tuotemerkki : Lenovo

Tuotekoodi: 7Y37A01084

Tuotteen nimi : 7Y37A01084



Lenovo 7Y37A01084. Tuetut tallennusasemaliitännät: SAS, Serial ATA III, Isäntäkoneen käyttöliittymä: PCI Express x8. RAID-tasot: 0, 1, 10, 5, 50, 6, 60, Tiedonsiirtonopeus: 12000 Gbit/s, Piirisarja: LSI SAS3508. Linux-käyttöjärjestelmätuki: SUSE Linux Enterprise Desktop 11, SUSE Linux Enterprise Desktop 12, Yhteensopivat käyttöjärjestelmät: Red Hat Enterprise Linux 6 Server x64 Edition Red Hat Enterprise Linux 7 VMware vSphere ESXi 6.0..., Tuetut palvelinkäyttöjärjestelmät: Windows Server 2012 R2, Windows Server 2016. PCI-kortti: Täysi korkeus (matala profiili)

| Ports & interfaces | | Performance | |
|--------------------------------------|---------------------------|------------------------------------|---|
| Supported storage drive interfaces * | SAS, Serial ATA III | Certification | FCC Part 15 Class A Australia/New Zealand (AS/NZS CISPR 22) Canada (ICES-003 Class B) Europe (EN55022/EN55024) Japan (VCCI V-3) Korea (RRA no 2013-24 & 25) RoHS compliant EN/IEC/UL 60950 Taiwan (CNS 13438) USA (FCC 47 CFR part 15 Subpart B class B) WEEE |
| Host interface * | PCI Express x8 | | |
| PCI Express slots version | 3.0 | | |
| Internal mini-SAS HD ports | 2 | | |
| External SAS ports | 8 | | |
| Performance | | System requirements | |
| RAID levels * | 0, 1, 10, 5, 50, 6, 60 | Linux operating systems supported | SUSE Linux Enterprise Desktop 11, SUSE Linux Enterprise Desktop 12 |
| RAID Level Migration | ✓ | Compatible operating systems | Red Hat Enterprise Linux 6 Server x64 Edition Red Hat Enterprise Linux 7 VMware vSphere ESXi 6.0 VMware vSphere ESXi 6.5 |
| Data transfer rate | 12000 Gbit/s | Server operating systems supported | Windows Server 2012 R2, Windows Server 2016 |
| SSD support | ✓ | | |
| Chipset | LSI SAS3508 | | |
| S.M.A.R.T. support | ✓ | | |
| Number of devices supported | 8 | | |
| Online Capacity Expansion | ✓ | | |
| Hot-swap | ✓ | | |
| Operational conditions | | | |
| Operating temperature (T-T) | 10 - 55 °C | | |
| Storage temperature (T-T) | -40 - 70 °C | | |
| Operating relative humidity (H-H) | 20 - 90% | | |
| Storage relative humidity (H-H) | 5 - 95% | | |
| Logistics data | | | |
| Harmonized System (HS) code | 84733080 | | |
| Other features | | | |
| PCI Card form factor | Full-height (low-profile) | | |



0889488433452



889488433452

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.