

Data Sheet

FUJITSU PFC EP Emulex LPe32000 / LPe32002 Fibre Channel Adapters

Dual- and single-port 32 Gbit PCIe 3.0 Host Bus Adapters by Broadcom

Fibre Channel Host Bus Adapters (HBA) enable data exchange over large distances and extend your existing FUJITSU server systems by including communication interfaces using high-speed communication technology. All connections are redundant and hot-pluggable.

The combination of hardware and software exemplifies the high-performance quality of communication.

The number of system restarts is reduced thanks to optimized software and extended error check functions help improve the integrity of your company's information.

Compared to the previous generation, Emulex Gen 6 HBAs deliver 2x greater bandwidth—12,800MBps (2 ports 32G, full duplex), less than half the latency, and support an industry-leading 1.6 million IOPS on a single port, ensuring SLAs are met.



PFC EP Emulex LPe32000 / LPe32002 Fibre Channel Adapters

The Emulex Gen 6 32 Gb Fibre Channel (FC) Host Bus Adapters (HBA) by Broadcom for PRIMERGY and PRIMEQUEST server systems are optimal Fibre Channel HBAs for virtualized, cloud and mission critical deployments. The PFC EP Emulex Gen 6 Fibre Channel HBAs LPe32000/32002 by Broadcom take performance to a new level with PCIe 3.0 support, data integrity capabilities and cloud scale reliability, and ease of use. Organizations looking to improve performance, protect against data corruption, and simplify operations of FC SANs in cloud or high performance environments can benefit from deploying the PFC EP LPe32000/32002.

The single and dual port FC HBAs feature the Emulex bullet-proof driver stack built on a heritage reaching back to the first generation Fibre Channel adapters resulting in rock-solid reliability in 32Gb/s, 16Gb/s and 8Gb/s environments. With over 1.6 million IOPS on a single port, they are ideally suited for Fibre Channel connectivity to flash storage arrays.

Features & Benefits

Main Features	Benefits
<ul style="list-style-type: none">■ Faster Flash. Better Virtualization. Lossless Networking	<ul style="list-style-type: none">■ Emulex Gen 6 FC HBAs are designed to address the demanding performance, reliability and management requirements of modern networked storage systems that utilize high performance and low latency solid state storage drives for caching and persistent storage as well as hard disk drive arrays.
<ul style="list-style-type: none">■ Accelerate	<ul style="list-style-type: none">■ The unique Emulex Dynamic Multi-core Architecture delivers unparalleled performance and more efficient port utilization than other HBAs by applying all ASIC resources to any port that needs it.
<ul style="list-style-type: none">■ Protect	<ul style="list-style-type: none">■ Emulex Gen 6 FC HBAs deliver enhanced security via the new secure firmware update feature which protects and ensures the authenticity of device firmware.
<ul style="list-style-type: none">■ Control	<ul style="list-style-type: none">■ The flagship OneCommand® Manager enterprise-class management application features a multiprotocol, cross-platform architecture that provides centralized management of all current and previous generations of Emulex FC HBAs. This enables IT administrators to manage network connectivity with one tool for maximum efficiency.

Technical details

Technical details

Controller Silicon	Emulex XE501
Controller type	Fibre Channel Host Bus Adapter
Connector type	LC-style
Number of ports	2
Data transfer rate(s)	8 Gbit/s; 16 Gbit/s; 32 Gbit/s
Auto Negotiation support	Yes
Bus interface	PCIe 3.0 x8
Bus transfer rate	8GT/s
LEDs	2 LEDs per port (yellow and green)
Standards	<ul style="list-style-type: none"> - Current ANSI/IEF Standards: FC-PI-4; FC-PI-5; FC-PI-6; FC-FS-3; FC-LS-2; FC-GS-6; FC-DA; FC-DA2; FCP-4; SPC-4; SBC-3; SSC-3; SSC-4 - Legacy ANSI/IEF standards: FC-PH; FC-PH-2; FC-PH-3; FC-PI; FC-PI-2; FC-FS; FC-GS-2/3/4/5; FCP-2/3; FC-HBA; FC-TAPE; FC-MI; SPC-3; SBC-2; SSC-2; SSC-3 - PCIe base spec 3.0 - PCIe card electromechanical spec 3.0 - Fibre Channel Class 3 - PHP hot plug-hot swap
Technology	Optics: 32 Gb/s short wave lasers with LC type connectors. Data rates: 28.05 Gb/s (32GFC); 14.025 Gb/s (16GFC); 8.5 Gb/s (8GFC); automatically negotiated
Supported cable length	<p>Operating at 32Gb</p> <ul style="list-style-type: none"> - OM4 (Multi-Mode 50/125µm, 4700 MHz*km) 100m - OM3 (Multi-Mode 50/125µm, 2000 MHz*km) 70m - OM2 (Multi-Mode 50/125µm, 500 MHz*km) 20m <p>Operating at 16Gb</p> <ul style="list-style-type: none"> - OM4 (Multi-Mode 50/125µm, 4700 MHz*km) 125m - OM3 (Multi-Mode 50/125µm, 2000 MHz*km) 100m - OM2 (Multi-Mode 50/125µm, 500 MHz*km) 35m <p>Operating at 8Gb</p> <ul style="list-style-type: none"> - OM4 (Multi-Mode 50/125µm, 4700 MHz*km) 190m - OM3 (Multi-Mode 50/125µm, 2000 MHz*km) 150m - OM2 (Multi-Mode 50/125µm, 500 MHz*km) 50m
FC Controller notes	the controller is equivalent to the original Emulex HBA LPe32000-Series
Fibre Channel interface	MMF

Order code	Product name (vendor)	Height of bracket	Number of ports	Related product
S26361-F4044-E202	LPe32002-M6-F	Low Profile (LP)	2	PRIMERGY Server
S26361-F4044-E2	LPe32002-M6-F	Full Height (FH)	2	PRIMERGY Server
S26361-F4044-L502	LPe32002-M6-F	Full Height / Low Profile	2	PRIMERGY Server

Environment

Power consumption	LPe32000: typical 9.3W; max 11.6 W LPe32002: typical 11.1W; max 13.3 W
Temperature (operating)	0 - 55 °C
Storage temperature	-40 - 70 °C

Compliance

Compliance notes	According to the corresponding system
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

More information

Fujitsu products, solutions & services

In addition to Fujitsu with PFC EP Emulex LPe32000 / LPe32002 Fibre Channel Adapters, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Server PFC EP Emulex LPe32000 / LPe32002 Fibre Channel Adapters, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>

Copyright 2019 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Limited
Website: www.fujitsu.com/primergy
2019-11-01 WW-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2019 FUJITSU LIMITED