



# BenQ ST4302S Digital signage flat panel 109.2 cm (43") LCD 400 cd/m<sup>2</sup> 4K Ultra HD Black Built-in processor Android 8.0

**Brand :** BenQ

**Product code:** 9H.F7GPT.RA4

**Product name :** ST4302S



- View vivid images on a 4K UHD display
  - Ready-to-use with its built-in Android™ OS
  - Flip the display for portrait or landscape viewing
  - Easily create content using custom X-Sign templates
- 43" Professional Smart Signage

BenQ ST4302S Digital signage flat panel 109.2 cm (43") LCD 400 cd/m<sup>2</sup> 4K Ultra HD Black Built-in processor Android 8.0:

## Superior Picture Quality Every Time

### 4K UHD Clarity

Enjoy crisp and colorful images with the ST series. 4K UHD resolution brings excellent clarity and readability to any space

### Built-In Android OS

Use the built-in Android OS to access files, display content and start presentations without connecting other devices.

BenQ ST4302S. Product design: Digital signage flat panel. Display diagonal: 109.2 cm (43"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 400 cd/m<sup>2</sup>, HD type: 4K Ultra HD. Operating system installed: Android 8.0. Product colour: Black



| Display                       |                       | Design                                  |                           |
|-------------------------------|-----------------------|---|---------------------------|
| Panel type                    | IPS                   | Panel mounting interface                | 200 x 200 mm              |
| Display diagonal *            | 109.2 cm (43")        | <b>Performance</b>                      |                           |
| Display technology *          | LCD                   | Purpose *                               | Corporate                 |
| Display resolution *          | 3840 x 2160 pixels    | <b>Power</b>                            |                           |
| Display brightness *          | 400 cd/m <sup>2</sup> | Power consumption (typical) *           | 110 W                     |
| HD type *                     | 4K Ultra HD           | Power consumption (standby) *           | 0.5 W                     |
| Touchscreen *                 | ✗                     | Energy efficiency class (SDR)           | G                         |
| Native aspect ratio           | 16:9                  | Energy consumption (SDR) per 1000 hours | 110 kWh                   |
| Response time                 | 8 ms                  | AC input voltage                        | 100 - 240 V               |
| Contrast ratio (typical)      | 1200:1                | AC input frequency                      | 50 - 60 Hz                |
| Active display area (W x H)   | 941.2 x 529.4 mm      | Energy efficiency scale                 | A to G                    |
| Panel life                    | 30000 h               | <b>Computer system</b>                  |                           |
| RGB colour space              | NTSC                  | Computer system *                       | ✓                         |
| <b>Ports &amp; interfaces</b> |                       | Built-in processor *                    | ✓                         |
| HDMI ports quantity *         | 2                     | Processor architecture                  | ARM Cortex-A53+Cortex-A73 |
| HDMI version                  | 2.0                   | Internal memory                         | 3 GB                      |
| HDMI input ports quantity     | 2                     | Internal storage capacity               | 16 GB                     |
| DVI port *                    | ✓                     | Operating system installed              | Android 8.0               |
| VGA (D-Sub) input ports       | 1                     | <b>Weight &amp; dimensions</b>          |                           |
| USB port *                    | ✓                     | Display width                           | 973 mm                    |
| USB ports quantity            | 2                     | Display depth                           | 63.5 mm                   |
| USB version                   | 2.0                   | Display height                          | 561.2 mm                  |
| Ethernet LAN *                | ✓                     | Display weight                          | 10.7 kg                   |
| Ethernet LAN (RJ-45) ports    | 1                     | <b>Packaging data</b>                   |                           |
| Ethernet LAN data rates       | 10,100 Mbit/s         | Package width                           | 1070 mm                   |
| Wi-Fi *                       | ✗                     | Package depth                           | 173 mm                    |
| PC Audio in                   | ✓                     |   |                           |
| Card reader integrated        | ✓                     |   |                           |
| Compatible memory cards       | MicroSD (TransFlash)  |   |                           |

| Ports & interfaces          |                            | Packaging data                    |             |
|-----------------------------|----------------------------|-----------------------------------|-------------|
| PC Audio out                | ✓                          | Package height                    | 680 mm      |
| Audio                       |                            | Package weight                    | 14.3 kg     |
| Built-in speaker(s) *       | ✓                          | Packaging content                 |             |
| Number of built-in speakers | 2                          | Remote control included           | ✓           |
| RMS rated power             | 20 W                       | Cables included                   | HDMI        |
| Design                      |                            | Operational conditions            |             |
| Product design *            | Digital signage flat panel | Operating temperature (T-T)       | 0 - 40 °C   |
| Placement supported *       | Indoor                     | Operating relative humidity (H-H) | 10 - 80%    |
| Orientation                 | Horizontal/Vertical        | Storage temperature (T-T)         | -20 - 60 °C |
| Product colour *            | Black                      | Storage relative humidity (H-H)   | 20 - 90%    |
| VESA mounting *             | ✓                          |                                   |             |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-NOV-2024. Prints or copies of Information are only valid on the printed Publication date