


BenQ ST4302S Digitaalinen litteä infotaulu 109,2 cm (43") LCD 400 cd/m² 4K Ultra HD musta Sisäänrakennettu prosessori Android 8.0

Tuotemerkki: BenQ Tuotekoodi: 9H.F7GPT.RA4

Tuotteen nimi: ST4302S







Display		Design	
Panel type	IPS	Panel mounting interface	200 x 200 mm
Display diagonal *	109.2 cm (43")	Performance	
Display technology *	LCD	Purpose *	Corporate
Display resolution *	3840 x 2160 pixels	Power	
Display brightness * HD type *	400 cd/m² 4K Ultra HD	Power consumption (typical) *	110 W
Touchscreen *	X	Power consumption (standby) *	0.5 W
Native aspect ratio	16:9	Energy efficiency class (SDR)	G
Response time	8 ms	Energy consumption (SDR) per 1000 hours	110 kWh
Contrast ratio (typical)	1200:1	AC input voltage	100 - 240 V
Active display area (W x H) Panel life	941.2 x 529.4 mm 30000 h	AC input frequency	50 - 60 Hz
RGB colour space	NTSC	Energy efficiency scale	A to G
Ports & interfaces		Computer system	
	_	Computer system *	1
HDMI norts quantity *	7	Computer system	•
HDMI ports quantity * HDMI version	2 2.0	Built-in processor *	✓
		. ,	
HDMI version	2.0	Built-in processor *	✓
HDMI version HDMI input ports quantity	2.0 2	Built-in processor * Processor architecture	✓ ARM Cortex-A53+Cortex-A73
HDMI version HDMI input ports quantity DVI port *	2.0 2 ✓	Built-in processor * Processor architecture Internal memory	✓ ARM Cortex-A53+Cortex-A73 3 GB
HDMI version HDMI input ports quantity DVI port * VGA (D-Sub) input ports	2.0 2 •	Built-in processor * Processor architecture Internal memory Internal storage capacity	ARM Cortex-A53+Cortex-A73 3 GB 16 GB
HDMI version HDMI input ports quantity DVI port * VGA (D-Sub) input ports USB port *	2.0 2 • 1	Built-in processor * Processor architecture Internal memory Internal storage capacity Operating system installed	ARM Cortex-A53+Cortex-A73 3 GB 16 GB
HDMI version HDMI input ports quantity DVI port * VGA (D-Sub) input ports USB port * USB ports quantity	2.0 2 ✓ 1 ✓	Built-in processor * Processor architecture Internal memory Internal storage capacity Operating system installed Weight & dimensions	ARM Cortex-A53+Cortex-A73 3 GB 16 GB Android 8.0
HDMI version HDMI input ports quantity DVI port * VGA (D-Sub) input ports USB port * USB ports quantity USB version	2.0 2 ✓ 1 ✓ 2 2.0	Built-in processor * Processor architecture Internal memory Internal storage capacity Operating system installed Weight & dimensions Display width Display depth Display height	ARM Cortex-A53+Cortex-A73 3 GB 16 GB Android 8.0 973 mm 63.5 mm 561.2 mm
HDMI version HDMI input ports quantity DVI port * VGA (D-Sub) input ports USB port * USB ports quantity USB version Ethernet LAN * Ethernet LAN (RJ-45) ports Ethernet LAN data rates	2.0 2 1 1 2 2.0	Built-in processor * Processor architecture Internal memory Internal storage capacity Operating system installed Weight & dimensions Display width Display depth	ARM Cortex-A53+Cortex-A73 3 GB 16 GB Android 8.0 973 mm 63.5 mm
HDMI version HDMI input ports quantity DVI port * VGA (D-Sub) input ports USB port * USB ports quantity USB version Ethernet LAN * Ethernet LAN (RJ-45) ports	2.0 2 ✓ 1 ✓ 2 2.0 ✓	Built-in processor * Processor architecture Internal memory Internal storage capacity Operating system installed Weight & dimensions Display width Display depth Display height	ARM Cortex-A53+Cortex-A73 3 GB 16 GB Android 8.0 973 mm 63.5 mm 561.2 mm
HDMI version HDMI input ports quantity DVI port * VGA (D-Sub) input ports USB port * USB ports quantity USB version Ethernet LAN * Ethernet LAN (RJ-45) ports Ethernet LAN data rates	2.0 2 1 2 2.0 1 10,100 Mbit/s	Built-in processor * Processor architecture Internal memory Internal storage capacity Operating system installed Weight & dimensions Display width Display depth Display height Display weight	ARM Cortex-A53+Cortex-A73 3 GB 16 GB Android 8.0 973 mm 63.5 mm 561.2 mm

Ports & interfaces		Packaging data	
Compatible memory cards	MicroSD (TransFlash)	Package height	680 mm
PC Audio out	✓	Package weight	14.3 kg
Audio		Packaging content	
Built-in speaker(s) *	✓	Remote control included	✓
Number of built-in speakers	2	Cables included	HDMI
RMS rated power	20 W	Operational conditions	
Design		Operating temperature (T-T)	0 - 40 °C
Product design *	Digital signage flat panel	Operating relative humidity (H-H)	10 - 80%
Placement supported *	Indoor	Storage temperature (T-T)	-20 - 60 °C
Orientation	Horizontal/Vertical	Storage relative humidity (H-H)	20 - 90%
Product colour *	Black		
VESA mounting *	✓		

