

BenQ IL5501 Interactive flat panel 139.7 cm (55") LCD 400 cd/m² 4K Ultra HD Black Built-in processor Android 8.0

Brand : BenQ Product code: 9H.F7FPK.RA6

Product name: IL5501

- Safe interactions with germ-resistant screen
- 4K UHD anti-glare display for vivid images
- Display content in portrait or landscape mode
- All-in-one signage running on Android OS

55" Smart Interactive Signage

BenQ IL5501. Product design: Interactive flat panel. Display diagonal: 139.7 cm (55"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 400 cd/m², HD type: 4K Ultra HD. Operating system installed: Android 8.0. Product colour: Black





Display		Design	
Panel type IPS Display diagonal * 139.7 cm (55") Display technology * LCD Display resolution * 3840 x 2160 pixels	Screen shape VESA mounting * Panel mounting interface Anti-glare screen	Flat 400 x 400 mm	
Display brightness * HD type * Touchscreen *	400 cd/m² 4K Ultra HD X Infrared	Performance Purpose * Power	Commercial
Touchscreen technology Number of simultaneous touchpoints Native aspect ratio Response time Contrast ratio (typical) Active display area (W x H) Panel life Surface hardness	40 16:9 9 ms 1300:1 1209.6 x 680.4 mm 50000 h 9H	Power Power consumption (typical) * Power consumption (standby) * Energy efficiency class (SDR) Energy consumption (SDR) per 1000 hours AC input voltage AC input frequency Computer system	111 W 0.5 W G 111 kWh 100 - 240 V 50 - 60 Hz
RGB colour space Ports & interfaces	NTSC	Computer system *	✓
HDMI ports quantity * HDMI version HDMI input ports quantity HDMI output ports quantity VGA (D-Sub) input ports USB port *	3 2.0 2 1	Built-in processor * Processor architecture Internal memory On-board graphics card model Internal storage capacity Operating system installed	ARM Cortex-A53+Cortex-A73 3 GB ARM Mali-G51 MP2 32 GB Android 8.0
USB ports quantity	3	Weight & dimensions	
USB connector type Ethernet LAN * Ethernet LAN (RJ-45) ports	USB Type-A, USB Type-B ✓ 2	Display width Display depth Display height Display weight	1284.1 mm 92.6 mm 754.9 mm 29.1 kg

Ports & interfaces		Packaging data	
Ethernet LAN data rates Wi-Fi *	10,100 Mbit/s ×	Package width Package depth	1400 mm 175 mm
PC Audio in PC Audio out	· · · · · · · · · · · · · · · · · · ·	Package height Package weight	845 mm 35.2 kg
OPS module slot	·	Packaging content	
Audio		Cables included	DisplayPort, HDMI, VGA
Built-in speaker(s) *	✓	Operational conditions	
Number of built-in speakers RMS rated power	2 10 W	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 20 - 85%
Design		Storage temperature (T-T) Storage relative humidity (H-H)	-10 - 60 °C 10 - 90%
Product design * Placement supported * Orientation Product colour *	Interactive flat panel Indoor Horizontal/Vertical Black	storage relative namidity (1111)	

