

## BenQ IL5501 Interaktiivinen litteä paneeli 139,7 cm (55") LCD 400 cd/m² 4K Ultra HD musta Sisäänrakennettu prosessori Android 8.0

Tuotemerkki : BenQ Tuotekoodi: 9H.F7FPK.RA6

Tuotteen nimi: IL5501

BenQ IL5501. Tuotteen muotoilu: Interaktiivinen litteä paneeli. Näytön halkaisija: 139,7 cm (55"), Näytön teknologia: LCD, Näytön erottelutarkkuus: 3840 x 2160 pikseliä, Näytön kirkkaus: 400 cd/m², HD-tyyppi: 4K Ultra HD. Käyttöjärjestelmä asennettu: Android 8.0. Tuotteen väri: musta





Display		Design	
isplay anel type isplay diagonal * 139.7 cm (55") isplay technology * LCD isplay resolution * 3840 x 2160 pixels isplay brightness * 400 cd/m² D type * 4K Ultra HD ouchscreen *  ouchscreen technology Infrared umber of simultaneous buchpoints ative aspect ratio 40 esponse time 9 ms ontrast ratio (typical) 1300:1 ctive display area (W x H) 1209.6 x 680.4 mm	Screen shape VESA mounting * Panel mounting interface Anti-glare screen  Performance Purpose *  Power  Power consumption (typical) * Power consumption (standby) * Energy efficiency class (SDR) Energy consumption (SDR) per 1000 hours AC input voltage	Flat  400 x 400 mm  Commercial  111 W  0.5 W  G  111 kWh  100 - 240 V	
Panel life Surface hardness RGB colour space Ports & interfaces	50000 h 9H NTSC	AC input frequency  Computer system  Computer system *	50 - 60 Hz
HDMI ports quantity * HDMI version HDMI input ports quantity HDMI output ports quantity VGA (D-Sub) input ports USB port *	2.0  pantity 2  quantity 1  ports 1  V  3  USB Type-A, USB Type-B	Built-in processor * Processor architecture Internal memory On-board graphics card model Internal storage capacity Operating system installed	ARM Cortex-A53+Cortex-A73 3 GB ARM Mali-G51 MP2 32 GB Android 8.0
USB ports quantity USB connector type Ethernet LAN * Ethernet LAN (RJ-45) ports		Weight & dimensions  Display width  Display depth  Display height  Display weight	1284.1 mm 92.6 mm 754.9 mm 29.1 kg

Ports & interfaces		Packaging data	
Ethernet LAN data rates Wi-Fi *	10,100 Mbit/s ×	Package width Package depth	1400 mm 175 mm
PC Audio in PC Audio out	, ,	Package height Package weight	845 mm 35.2 kg
OPS module slot	· ·	Packaging content	
Audio		Cables included	DisplayPort, HDMI, VGA
Built-in speaker(s) *	✓	Operational conditions	
Number of built-in speakers RMS rated power	2 10 W	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 20 - 85%
Design		Storage temperature (T-T) Storage relative humidity (H-H)	-10 - 60 °C 10 - 90%
Product design * Placement supported * Orientation Product colour *	Interactive flat panel Indoor Horizontal/Vertical Black	storage relative namidity (1111)	

