

DELL Precision 5490 Intel Core Ultra 7 165H Mobiilityöasema 35,6 cm (14") Full HD+ 32 GB LPDDR5x-SDRAM 1 TB SSD NVIDIA RTX 2000 Ada Wi-Fi 7 (802.11be) Windows 11 Pro Harmaa

Tuotemerkki : DELL Tuoteperhe: Precision Tuotekoodi: C6FW6

Tuotteen nimi: 5490

DELL Precision 5490. Tuotetyyppi: Mobiilityöasema, Kotelo: Simpukka. Suoritinperhe: Intel Core Ultra 7, Prosessorimalli: 165H. Näytön halkaisija: 35,6 cm (14"), HD-tyyppi: Full HD+, Näytön erottelutarkkuus: 1920 x 1200 pikseliä. Sisäinen muisti: 32 GB, Sisäisen muistin tyyppi: LPDDR5x-SDRAM. Kokonaistallennuskapasiteetti: 1 TB, Tallennusmedia: SSD. Sisältyvän näytönohjaimen malli: Intel Arc Graphics, Erillisen näytönohjaimen malli: NVIDIA RTX 2000 Ada. Käyttöjärjestelmä asennettu: Windows 11 Pro. Tuotteen väri: Harmaa





Design		Camera	
Product type * Product colour * Form factor * Market positioning Intel® vPro™ Platform Eligibility Display	Mobile workstation Grey Clamshell Business ✓	Front camera Front camera resolution (numeric) Front camera resolution Front camera HD type Video capturing speed Infrared (IR) camera	0.92 MP 1280 x 720 pixels HD 30 fps
Display diagonal * Display resolution * Touchscreen * HD type Panel type LED backlight Native aspect ratio Anti-glare screen Display brightness Pixel density RGB colour space Colour gamut Maximum refresh rate Contrast ratio (typical)	35.6 cm (14") 1920 x 1200 pixels X Full HD+ WVA 16:10 500 cd/m² 161 ppi sRGB 100% 60 Hz 1000:1	Network Top Wi-Fi standard * Wi-Fi standards Mobile network connection * Antenna type WLAN controller model WLAN controller manufacturer Bluetooth MIMO MIMO MIMO type Ports & interfaces	Wi-Fi 7 (802.11be) 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6E (802.11ax), Wi-Fi 7 (802.11be)
Processor Processor manufacturer * Processor family * Processor generation Processor model * Processor cores	Intel Intel Core Ultra 7 Intel® Core™ Ultra (Series 1) 165H 16	Thunderbolt 4 ports quantity Intel® Thunderbolt 4 Combo headphone/mic port Charging port type USB Type-C DisplayPort Alternate Mode Performance	4 ✓ USB Type-C ✓
Processor threads	22	Ambient light sensor	✓

Processor		Performance	
Processor boost frequency	5 GHz	Accelerometer	1
Performance cores	6	Hall sensor	✓
Efficient cores	8	Keyboard	
Low Power Efficient-cores	2	Pointing device	Touchpad
Performance-core Max Turbo Frequency	5 GHz	Keyboard language	Nordic
Efficient-core Max Turbo Frequency	3.8 GHz	Numeric keypad *	×
Low Power Efficient-core Max Turbo	2.5 GHz	Keyboard backlit	1
Frequency	1.4 GHz	Software	
Performance-core base frequency Efficient-core base frequency	0.9 GHz		64-bit
Low Power Efficient-core Base		Operating system architecture	Danish, English, Finnish, Norwegian,
Frequency	700 MHz	Operating system language	Swedish
Processor cache	24 MB	Trial software	No Microsoft Office Licence Included
Processor cache type	Smart Cache	Operating system installed *	- 30 day Trial Offer Only Windows 11 Pro
Processor base power Maximum turbo power	28 W 115 W		Wildows 11 110
·	113 W	Battery	
Neural processor unit (NPU)		Number of battery cells	4 72 Wh
Neural processor unit (NPU)	Intel Al Boost	Battery capacity * Battery voltage	72 Wh 15.4 V
Maximum frequency NPU	1.4 GHz	Battery recharge time	4 h
Sparsity support	✓	Fast charging	✓
Windows Studio effects support	✓ FD16 FD22 In±0	Battery weight	285 g
Al datatype support on NPU Al software frameworks supported	FP16, FP32, Int8 DirectML, ONNX RT, OpenVINO,	Power	3
by NPU	Windows ML	AC adapter power	130 W
Memory		AC adapter frequency	50 - 60 Hz
Internal memory *	32 GB	AC adapter input voltage	100 - 240 V
Internal memory type	LPDDR5x-SDRAM	USB Power Delivery (USB PD) *	✓
Memory form factor	On-board	Security	
Maximum internal memory *	32 GB		
Memory channels	Dual-channel	Cable lock slot Cable lock slot type	✓ Wedge
Memory data transfer rate	7467 MT/s	Fingerprint reader	vveuge ✓
Storage		Trusted Platform Module (TPM)	·
Total storage capacity *	1 TB	Trusted Platform Module (TPM)	
Storage media *	SSD	version	2.0
Total SSDs capacity	1 TB	Password protection	✓
Number of SSDs installed SSD capacity	1 1 TB	Operational conditions	
SSD interface	PCI Express 4.0	Operating temperature (T-T)	0 - 35 °C
NVMe	•	Storage temperature (T-T)	-40 - 65 °C
SSD form factor	M.2	Operating relative humidity (H-H)	10 - 90%
SSD performance class	40	Storage relative humidity (H-H)	0 - 95%
M.2 SSD size	2280 (22 x 80 mm)	Operating altitude	-15.2 - 3048 m
Optical drive type *	X	Non-operating altitude	-15.2 - 10668 m
Card reader integrated			
	✓	Operating shock	110 G
Compatible memory cards	MicroSD (TransFlash), MicroSDHC,	Non-operating shock	160 G
Compatible memory cards			
Compatible memory cards Graphics	MicroSD (TransFlash), MicroSDHC, MicroSDXC	Non-operating shock Operating vibration Non-operating vibration	160 G 0.66 G
Compatible memory cards Graphics Discrete GPU manufacturer	MicroSD (TransFlash), MicroSDHC, MicroSDXC	Non-operating shock Operating vibration Non-operating vibration Sustainability	160 G 0.66 G 1.3 G
Compatible memory cards Graphics Discrete GPU manufacturer Discrete graphics card model *	MicroSD (TransFlash), MicroSDHC, MicroSDXC NVIDIA NVIDIA RTX 2000 Ada	Non-operating shock Operating vibration Non-operating vibration Sustainability Sustainability compliance	160 G 0.66 G 1.3 G
Compatible memory cards Graphics Discrete GPU manufacturer Discrete graphics card model * Discrete graphics card memory	MicroSD (TransFlash), MicroSDHC, MicroSDXC NVIDIA NVIDIA RTX 2000 Ada 8 GB	Non-operating shock Operating vibration Non-operating vibration Sustainability Sustainability compliance Sustainability certificates	160 G 0.66 G 1.3 G
Compatible memory cards Graphics Discrete GPU manufacturer Discrete graphics card model * Discrete graphics card memory Discrete graphics memory type	MicroSD (TransFlash), MicroSDHC, MicroSDXC NVIDIA NVIDIA RTX 2000 Ada 8 GB GDDR6	Non-operating shock Operating vibration Non-operating vibration Sustainability Sustainability compliance Sustainability certificates Weight & dimensions	160 G 0.66 G 1.3 G ✓ ENERGY STAR, TCO
Compatible memory cards Graphics Discrete GPU manufacturer Discrete graphics card model * Discrete graphics card memory Discrete graphics memory type On-board graphics card *	MicroSD (TransFlash), MicroSDHC, MicroSDXC NVIDIA NVIDIA RTX 2000 Ada 8 GB GDDR6	Non-operating shock Operating vibration Non-operating vibration Sustainability Sustainability compliance Sustainability certificates Weight & dimensions Width	160 G 0.66 G 1.3 G ✓ ENERGY STAR, TCO
Compatible memory cards Graphics Discrete GPU manufacturer Discrete graphics card model * Discrete graphics card memory Discrete graphics memory type On-board graphics card * On-board GPU manufacturer	MicroSD (TransFlash), MicroSDHC, MicroSDXC NVIDIA NVIDIA RTX 2000 Ada 8 GB GDDR6	Non-operating shock Operating vibration Non-operating vibration Sustainability Sustainability compliance Sustainability certificates Weight & dimensions Width Depth	160 G 0.66 G 1.3 G ✓ ENERGY STAR, TCO 310.6 mm 210.3 mm
Compatible memory cards Graphics Discrete GPU manufacturer Discrete graphics card model * Discrete graphics card memory Discrete graphics memory type On-board graphics card *	MicroSD (TransFlash), MicroSDHC, MicroSDXC NVIDIA NVIDIA RTX 2000 Ada 8 GB GDDR6 Intel	Non-operating shock Operating vibration Non-operating vibration Sustainability Sustainability compliance Sustainability certificates Weight & dimensions Width Depth Height (front)	160 G 0.66 G 1.3 G ✓ ENERGY STAR, TCO 310.6 mm 210.3 mm 7.49 mm
Compatible memory cards Graphics Discrete GPU manufacturer Discrete graphics card model * Discrete graphics card memory Discrete graphics memory type On-board graphics card * On-board GPU manufacturer Discrete graphics card *	MicroSD (TransFlash), MicroSDHC, MicroSDXC NVIDIA NVIDIA RTX 2000 Ada 8 GB GDDR6 Intel	Non-operating shock Operating vibration Non-operating vibration Sustainability Sustainability compliance Sustainability certificates Weight & dimensions Width Depth	160 G 0.66 G 1.3 G ✓ ENERGY STAR, TCO 310.6 mm 210.3 mm

Audio		Carbon footprint	
Number of built-in speakers	4	Total carbon footprint (kg of CO2e)	115
Speaker power	2 W	Carbon emissions, manufacturing	87
Built-in microphone	✓	(kg of CO2e)	
Number of microphones	2	Carbon emissions, logistics (kg of CO2e)	6
		Carbon emissions, energy usage (kg of CO2e)	20
		Carbon emissions, end-of-life (kg of CO2e)	2
		Total carbon emissions, w/o use phase (kg of CO2e)	95
		PAIA version	GaBi version 1, 2024
		Packaging content	
		Cables included	AC



5397184899977

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.