

## TP-Link Omada EAP610GP-DESKTOP WLAN-tukiasema 1201 Mbit/s Valkoinen Power over Ethernet -tuki

Tuotemerkki : TP-Link Tuoteperhe: Omada Tuotekoodi: EAP610GP-

**DESKTOP** 

Tuotteen nimi: EAP610GP-


DESKTOP

TP-Link Omada EAP610GP-DESKTOP. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 1201 Mbit/s. Tietoturva-algoritmit: SNMP, SNMPv2, SNMPv3, SSH, WPA-Personal, WPA2-Personal, WPA3-Personal. Ethernet LAN -datanopeudet: 1000 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen



Features		Ports & interfaces	
2.4 GHz *	✓	Ethernet LAN (RJ-45) ports *	4
5 GHz *	✓	Power	
6 GHz *	×	Power over Ethernet (PoE) *	/
Maximum data transfer rate *	1201 Mbit/s	DC voltage range	53.5 V
Maximum data transfer rate (2.4 GHz)	574 Mbit/s	Power consumption (typical)	17.3 W
Maximum data transfer rate (5 GHz)	1201 Mbit/s	Design	
Ethernet LAN data rates	1000 Mbit/s	Placement *	Desk, Wall
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE	Product colour *	White
Networking Standards	802.11g, IEEE 802.11n	Reset button	1
Number of users	120 user(s)	LED indicators	Power
Channel bandwidth	80 MHz	Antenna	
MIMO	✓	Antenna type *	Internal
MIMO type	Multi User MIMO	Antenna direction type	Omni-directional
Spread spectrum method	OFDMA	Antennas quantity	2
Wi-Fi roaming	✓	Antenna gain level (max)	5 dBi
VLAN support	✓	Certificates	
Rate limiting	✓	Compliance certificates	CE, Federal Communications
Wireless isolation	/	·	Commission (FCC), RoHS
Band steering	✓	Certification	CE, FCC, RoHS, IC
Airtime Fairness (ATF)	✓	Weight & dimensions	
Quality of Service (QoS) support	✓	Width	175 mm
BeamForming	✓	Depth	140 mm
Transmitting power (CE)	20 dBm	Height	33 mm
Transmitting power (FCC)	25 dBm	Weight	492 g
Security		Packaging content	
	SNMP, SNMPv2, SNMPv3, SSH, WPA-	Quantity per pack	1 pc(s)
Security algorithms *	Personal, WPA2-Personal, WPA3-	Mounting kit	<b>✓</b>
	Personal	Quick start guide	✓
MAC address filtering	Multiple CCID a CCID beautions	Operational conditions	
Service Set Identifier (SSID) features	Multiple SSIDs, SSID broadcast on/off	Operating relative humidity (H-H)	10 - 90%
Number of SSID supported	16	Operating temperature (T-T)	0 - 40 °C
Remote Authentication Dial-In User	/	Storage temperature (T-T)	-40 - 70 °C
Service (RADIUS)		Storage relative humidity (H-H)	5 - 90%
Management features		Sustainability	
Web-based management	✓	Sustainability compliance	✓

Management features	
Syslog	✓



8885020620504

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.