




TP-Link Omada EAP610GP-DESKTOP WLAN-tukiasema 1201 Mbit/s Valkoinen Power over Ethernet -tuki



Tuotemerkki : TP-Link

Tuoteperhe: Omada

Tuotekoodi: EAP610GP-DESKTOP

Tuotteen nimi : EAP610GP-DESKTOP

TP-Link Omada EAP610GP-DESKTOP. 2,4 GHz, 5 GHz, Tiedonsiirron enimmäisnopeus: 1201 Mbit/s. Tietoturva-algoritmit: SNMP, SNMPv2, SNMPv3, SSH, WPA-Personal, WPA2-Personal, WPA3-Personal. Ethernet LAN -datanopeudet: 1000 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen

Features		Ports & interfaces	
2.4 GHz *	✓	Ethernet LAN (RJ-45) ports *	4
5 GHz *	✓	Power	
6 GHz *	✗	Power over Ethernet (PoE) *	✓
Maximum data transfer rate *	1201 Mbit/s	DC voltage range	53.5 V
Maximum data transfer rate (2.4 GHz)	574 Mbit/s	Power consumption (typical)	17.3 W
Maximum data transfer rate (5 GHz)	1201 Mbit/s	Design	
Ethernet LAN data rates	1000 Mbit/s	Placement *	Desk, Wall
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Product colour *	White
Number of users	120 user(s)	Reset button	✓
Channel bandwidth	80 MHz	LED indicators	Power
MIMO	✓	Antenna	
MIMO type	Multi User MIMO	Antenna type *	Internal
Spread spectrum method	OFDMA	Antenna direction type	Omni-directional
Wi-Fi roaming	✓	Antennas quantity	2
VLAN support	✓	Antenna gain level (max)	5 dBi
Rate limiting	✓	Certificates	
Wireless isolation	✓	Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Band steering	✓	Certification	CE, FCC, RoHS, IC
Airtime Fairness (ATF)	✓	Weight & dimensions	
Quality of Service (QoS) support	✓	Width	175 mm
BeamForming	✓	Depth	140 mm
Transmitting power (CE)	20 dBm	Height	33 mm
Transmitting power (FCC)	25 dBm	Weight	492 g
Security		Packaging content	
Security algorithms *	SNMP, SNMPv2, SNMPv3, SSH, WPA-Personal, WPA2-Personal, WPA3-Personal	Quantity per pack	1 pc(s)
MAC address filtering	✓	Mounting kit	✓
Service Set Identifier (SSID) features	Multiple SSIDs, SSID broadcast on/off	Quick start guide	✓
Number of SSID supported	16	Operational conditions	
Remote Authentication Dial-In User Service (RADIUS)	✓	Operating relative humidity (H-H)	10 - 90%
Management features		Operating temperature (T-T)	0 - 40 °C
Web-based management	✓	Storage temperature (T-T)	-40 - 70 °C
		Storage relative humidity (H-H)	5 - 90%
		Sustainability	
		Sustainability compliance	✓

Management features

Syslog





8885020620504

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-DEC-2024. Prints or copies of Information are only valid on the printed Publication date