



TP-Link Omada AX1800 1201 Mbit/s White

Brand : TP-Link

Product family: Omada

Product code: EAP615GP-WALL

Product name : AX1800



- Seamless 1.8 Gbps WiFi 6 Speeds: 1201 Mbps on 5 GHz & 574 Mbps on 2.4 GHz
- 1x GPON Port for High-Speed and Ultra-Range Access
- Ultra-Broadband WiFi 6: MU-MIMO, Seamless Roaming§
- One Fiber for Multiple Services: Wired, Wireless, Voice, VoIP, Data, and HD Video Services
- VoIP Calls: Support multiple VoIP accounts and various call features, exceeding traditional landlines
- Easy Use: One-Click Pairing and Automatic Adoption
- Smart O&M: PPSK△ and Multiple Portals§
- Centralized Management: Integrates with the Unified Optical Solution
- Wall-Mounted, AC Powered

1x GPON, 1x FXS, 2x Gigabit RJ-45, 100-240V~ 50/60Hz, 0.5A, 143 x 86 x 37.6 mm

TP-Link Omada AX1800. 2.4 GHz, 5 GHz, Maximum data transfer rate: 1201 Mbit/s. Security algorithms: SNMP, SNMPv2, SNMPv3, SSH, WPA-Personal, WPA2-Personal, WPA3-Personal. Ethernet LAN data rates: 1000 Mbit/s. Product colour: White

Features		Ports & interfaces	
2.4 GHz *	✓	Ethernet LAN (RJ-45) ports *	2
5 GHz *	✓	Power	
6 GHz *	✗	AC input voltage	100 - 240 V
Maximum data transfer rate *	1201 Mbit/s	AC input frequency	50/60 Hz
Maximum data transfer rate (2.4 GHz)	574 Mbit/s	Input current	0.5 A
Maximum data transfer rate (5 GHz)	1201 Mbit/s	Power consumption (typical)	12.2 W
Ethernet LAN data rates	1000 Mbit/s	Design	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Placement *	Wall
Number of users	120 user(s)	Product colour *	White
Channel bandwidth	80 MHz	Reset button	✓
MIMO	✓	LED indicators	Power
MIMO type	Multi User MIMO	Antenna	
Spread spectrum method	OFDMA	Antenna type *	Internal
Wi-Fi roaming	✓	Antenna direction type	Omni-directional
VLAN support	✓	Antennas quantity	2
Rate limiting	✓	Antenna gain level (max)	6.5 dBi
Wireless isolation	✓	Certificates	
Band steering	✓	Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Airtime Fairness (ATF)	✓	Certification	CE, FCC, RoHS, IC
Quality of Service (QoS) support	✓	Weight & dimensions	
BeamForming	✓	Width	143 mm
Transmitting power (CE)	20 dBm	Depth	86 mm
Transmitting power (FCC)	21 dBm	Height	37.6 mm
Security		Weight	320 g
Security algorithms *	SNMP, SNMPv2, SNMPv3, SSH, WPA-Personal, WPA2-Personal, WPA3-Personal	Packaging content	
MAC address filtering	✓	Quantity per pack	1 pc(s)
Service Set Identifier (SSID) features	Multiple SSIDs, SSID broadcast on/off	Mounting kit	✓
Number of SSID supported	16	Quick start guide	✓
Remote Authentication Dial-In User Service (RADIUS)	✓	Operational conditions	
Management features		Operating relative humidity (H-H)	10 - 90%
Web-based management	✓	Operating temperature (T-T)	0 - 40 °C
Syslog	✓	Storage temperature (T-T)	-40 - 70 °C
		Storage relative humidity (H-H)	5 - 90%

Sustainability

Sustainability compliance





8885020620528



8885020620535

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-NOV-2024. Prints or copies of Information are only valid on the printed Publication date