Samsung LH55VMTEBGB Digital signage flat panel 139.7 cm (55") 500 cd/m² Full HD Black 24/7

Brand : Samsung Product code: LH55VMTEBGBXEN

Product name: LH55VMTEBGB

- Transform any space with high impact visuals
- View content from any angle
- Vibrant images in any light

55", LED, 1920 x 1080, 0.63 x 0.63 mm, 500 cd/[], 1200 : 1, 178° / 178°, 8 ms, 72 %, 0.28 %, 65k Hz \sim 70k Hz, 154 MHz, 47 Hz \sim 63 Hz, 500000 : 1, G, AC100 - 240 V 50/60 Hz, 242 W

Samsung LH55VMTEBGB. Product design: Digital signage flat panel. Display diagonal: 139.7 cm (55"), Display resolution: 1920 x 1080 pixels, Display brightness: 500 cd/m², HD type: Full HD. Operating hours (hours/days): 24/7. Product colour: Black





Display		Design	
LED backlighting type Display diagonal * Display resolution * Display brightness * HD type *	Direct-LED 139.7 cm (55") 1920 x 1080 pixels 500 cd/m ² Full HD	Placement supported * Orientation Product colour * VESA mounting * Panel mounting interface	Indoor Horizontal/Vertical Black 600 x 400 mm
Touchscreen *	×	Performance	
Response time Contrast ratio (typical) Contrast ratio (dynamic)	8 ms 1200:1 500000:1 178°	Purpose * Operating hours (hours/days)	Commercial 24/7
Viewing angle, horizontal		Power	
ewing angle, vertical 178° xel pitch 0.63 x 0.63 mm orizontal scan range 65 - 70 kHz ertical scan range 47 - 63 Hz	0.63 x 0.63 mm 65 - 70 kHz	Power consumption (typical) * Power consumption (sleep) AC input voltage AC input frequency	242 W 0.5 W 100 - 240 V 50 - 60 Hz
Haze rate	28%	Weight & dimensions	
Ports & interfaces		Width	1211.5 mm
HDMI ports quantity * HDMI input ports quantity DVI port * DisplayPorts quantity * DisplayPorts in USB port * USB ports quantity Ethernet LAN * Ethernet LAN (RI-45) ports	2 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Depth Height Weight	70 mm 682.3 mm 19.4 kg
		Packaging data	
		Package width Package depth Package height Package weight	1398 mm 257 mm 844 mm 22.6 kg
Audio (L/R) in	1	Operational conditions	
Audio (L/R) out RS-232 interface Remote (IR) input	1 ✓ 1	Operating temperature (T-T) Operating relative humidity (H-H) Certificates	0 - 40 °C 10 - 90%
Design		Certification	Safety 60950-1 EMC Class A
Product design *	Digital signage flat panel	Logistics data	Surety 00330-1 Line class A
		Harmonized System (HS) code	85285210
		Harmonized System (HS) code	03203210



8592978326821

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.