

## Samsung LH55VMTEBGB Digital signage flat panel 139.7 cm (55") 500 cd/m<sup>2</sup> Full HD Black 24/7

**Brand :** Samsung

**Product code:** LH55VMTEBGBXEN

**Product name :** LH55VMTEBGB



- Transform any space with high impact visuals
- View content from any angle
- Vibrant images in any light

55", LED, 1920 x 1080, 0.63 x 0.63 mm, 500 cd/m<sup>2</sup>, 1200 : 1, 178° / 178°, 8 ms, 72 %, 0.28 %, 65k Hz ~ 70k Hz, 154 MHz, 47 Hz ~ 63 Hz, 500000 : 1, G, AC100 - 240 V 50/60 Hz, 242 W

Samsung LH55VMTEBGB. Product design: Digital signage flat panel. Display diagonal: 139.7 cm (55"), Display resolution: 1920 x 1080 pixels, Display brightness: 500 cd/m<sup>2</sup>, HD type: Full HD. Operating hours (hours/days): 24/7. Product colour: Black

Display		Design	
LED backlighting type	Direct-LED	Placement supported *	Indoor
Display diagonal *	139.7 cm (55")	Orientation	Horizontal/Vertical
Display resolution *	1920 x 1080 pixels	Product colour *	Black
Display brightness *	500 cd/m <sup>2</sup>	VESA mounting *	✓
HD type *	Full HD	Panel mounting interface	600 x 400 mm
Touchscreen *	✗	Performance	
Response time	8 ms	Purpose *	Commercial
Contrast ratio (typical)	1200:1	Operating hours (hours/days)	24/7
Contrast ratio (dynamic)	500000:1	Power	
Viewing angle, horizontal	178°	Power consumption (typical) *	242 W
Viewing angle, vertical	178°	Power consumption (sleep)	0.5 W
Pixel pitch	0.63 x 0.63 mm	AC input voltage	100 - 240 V
Horizontal scan range	65 - 70 kHz	AC input frequency	50 - 60 Hz
Vertical scan range	47 - 63 Hz	Weight & dimensions	
Haze rate	28%	Width	1211.5 mm
Ports & interfaces		Depth	70 mm
HDMI ports quantity *	2	Height	682.3 mm
HDMI input ports quantity	2	Weight	19.4 kg
DVI port *	✓	Packaging data	
DisplayPorts quantity *	1	Package width	1398 mm
DisplayPorts in	1	Package depth	257 mm
USB port *	✓	Package height	844 mm
USB ports quantity	1	Package weight	22.6 kg
Ethernet LAN *	✓	Operational conditions	
Ethernet LAN (RJ-45) ports	1	Operating temperature (T-T)	0 - 40 °C
Audio (L/R) in	1	Operating relative humidity (H-H)	10 - 90%
Audio (L/R) out	1	Certificates	
RS-232 interface	✓	Certification	Safety 60950-1 EMC Class A
Remote (IR) input	1	Logistics data	
Design		Harmonized System (HS) code	85285210
Product design *	Digital signage flat panel		



8592978326821

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-DEC-2024. Prints or copies of Information are only valid on the printed Publication date