

PHILIPS

Philips 3000 series 16B1P3302D/00 tietokoneen litteä näyttö 39,6 cm (15.6") 1920 x 1080 pikseliä Full HD LED musta

Tuotemerkki : Philips

Tuoteperhe: 3000 series

Tuotekoodi: 16B1P3302D/00

Tuotteen nimi :
16B1P3302D/00



Business Monitor 16B1P3302D Kannettava näyttö

Philips 3000 series 16B1P3302D/00 tietokoneen litteä näyttö 39,6 cm (15.6") 1920 x 1080 pikseliä Full HD LED musta:

Tämä kannettava ja kevyt näyttö on täydellinen valinta, kun haluat parantaa tuottavuutta matkustaessasi. Kaksi USB-C-liitäntää auttavat jakamaan ja esittämään sisältöä tai käyttämään useaa näyttöä samaan aikaan.

Philips 3000 series 16B1P3302D/00. Näytön halkaisija: 39,6 cm (15.6"), Näytön erotelutarkkuus: 1920 x 1080 pikseliä, HD-tyyppi: Full HD, Näytön teknologia: LED, Vasteaika (tyypillinen): 4 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 170°, Katselukulma, pystysuora: 170°. Sisäänrakennettu USB-keskus. VESA-kiinnitys. Tuotteen väri: musta



Display		Ergonomics	
Display diagonal *	39.6 cm (15.6")	Tilt angle range	0 - 90°
Display resolution *	1920 x 1080 pixels	On Screen Display (OSD)	✓
HD type *	Full HD	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Native aspect ratio *	16:9	Plug and Play	✓
Display technology *	LED	LED indicators	Operation, Stand-by
Panel type *	IPS		
Backlight type	W-LED		
Touchscreen *	✗		
Display brightness (typical)	250 cd/m ²		
Response time *	4 ms		
Anti-glare screen	✓		
Screen shape *	Flat		
Contrast ratio (typical) *	700:1		
Contrast ratio (dynamic)	50000000:1		
Dynamic contrast ratio marketing name	SmartContrast		
Maximum refresh rate *	75 Hz		
Viewing angle, horizontal	170°		
Viewing angle, vertical	170°		
Display number of colours *	16.2 million colours		
Pixel pitch	0.17925 x 0.17925 mm		
Pixel density	141 ppi		
Vertical scan range	48 - 75 Hz		
Viewable size, horizontal	34.4 cm		
Viewable size, vertical	19.4 cm		
Display diagonal (metric)	39.6 cm		
DDC/CI	✓		
Haze rate	25%		
Surface hardness	3H		
		Power	
		Energy efficiency class (SDR) *	C
		Energy efficiency class (HDR) *	Not available
		Energy consumption (SDR) per 1000 hours *	9 kWh
		Power consumption (typical) *	6.2 W
		Power consumption (standby) *	0.5 W
		Power consumption (off)	0.3 W
		Power consumption (PowerSave)	4.4 W
		Energy efficiency scale	A to G
		European Product Registry for Energy Labelling (EPREL) code	1223926
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-20 - 60 °C
		Operating relative humidity (H-H)	20 - 80%
		Operating altitude	0 - 3658 m
		Non-operating altitude	3658 - 12192 m

Display		Weight & dimensions	
Colour depth	6 bit	Width (with stand)	359 mm
Colour gamut standard	sRGB	Depth (with stand)	119 mm
sRGB coverage (typical)	64%	Height (with stand)	232 mm
NTSC coverage (typical)	46%	Weight (with stand)	1.03 kg
Display sRGB	✓	Packaging data	
Performance		Package width	404 mm
NVIDIA G-SYNC *	✗	Package depth	103 mm
AMD FreeSync *	✗	Package height	281 mm
Component video sync	Separate sync	Package weight	2.08 kg
Flicker-free technology	✓	Packaging content	
Low Blue Light technology	✓	Stand included	✓
Multimedia		Cables included	USB Type-C
Built-in speaker(s) *	✗	Manual	✓
Built-in camera *	✗	Bundled software	SmartControl
Design		Sustainability	
Market positioning *	Business	Sustainability compliance	✓
Product colour *	Black	Sustainability certificates	ENERGY STAR
Front bezel colour	Black	Doesn't contain	Mercury, PVC/BFR
Feet colour	Black	Other features	
Ports & interfaces		Compatible operating systems	Mac OS X Windows 11 / 10 / 8.1 / 8 / 7
Built-in USB hub *	✓	Exterior finish type	Textured
USB Type-C DisplayPort Alternate Mode	✓	Picture enhancement	SmartImage
USB Power Delivery (USB PD)	✓	Recyclable packaging material	100%
USB Power Delivery up to	15 W	Regulatory Approvals	CB; TUV/GS; TUV Ergo; CU-EAC; EAEU RoHS; CE Mark; FCC Class B; ICES-003; cETLus
HDMI *	✗	EasyRead mode	✓
Audio output	✓	LowBlue mode	✓
HDCP	✓	Compliance certificates	RoHS
HDCP version	1.4/2.2	Mean time between failures (MTBF)	70000 h
Ergonomics		Recycling data	
VESA mounting *	✓	Post-consumer recycled plastic	60%
Pivot	✓		
Pivot angle	0 - 90°		



8712581799526

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-DEC-2024. Prints or copies of Information are only valid on the printed Publication date