



APC BGM2200B-GR UPS-virtalähde Linjainteraktiivinen 2,2 kVA 1320 W 6 AC-pistorasia(a)

Tuotemerkki : APC

Tuotekoodi: BGM2200B-GR

Tuotteen nimi : BGM2200B-GR

APC BGM2200B-GR. UPS topologia: Linjainteraktiivinen, Kokonaislähtöteho (VA): 2,2 kVA, Lähtöteho: 1320 W. Pistorasian tyypit: C13 liitin, Tyyppi F, Virtapistoke: Tyyppi F, Ulostulojen määrä: 6 AC-pistorasia(a). Akkuteknologia: Sealed Lead Acid (VRLA), Akun jännite: 24 V, Akun kestoikä (maks.): 5 vuosi/vuosia. Kotelo: Tower, Tuotteen väri: musta, Telineen kapasiteetti: 0U. Tuotteen leveys: 104,1 mm, Tuotteen syvyys: 408,9 mm, Tuotteen korkeus: 292,1 mm



Features		Battery	
UPS topology *	Line-Interactive	Battery life (max)	5 year(s)
Output power capacity *	2.2 kVA	Battery recharge time	16 h
Output power *	1320 W	Automatic battery test	✓
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	168 V	Design	
Input operation voltage (max) *	302 V	Form factor *	Tower
Input frequency *	50/60 Hz	Rack capacity	0U
Output operation voltage (max)	230 V	Cable length	1.52 m
Output frequency	60 Hz	Product colour *	Black
Automatic Voltage Regulation (AVR)	✓	Display type	LCD
Maximum current	12 A	International Protection (IP) code	IP20
Surge energy rating	1080 J	Certification	IEC 62040-1-1 IEC 62040-2
Response time	8 ms	Operational conditions	
EMI/RFI noise filtering	✓	Operating temperature (T-T)	0 - 40 °C
Noise level	45 dB	Storage temperature (T-T)	-15 - 40 °C
Surge protection	✓	Operating relative humidity (H-H)	0 - 95%
Surge protection features	Network	Storage relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Operating altitude	0 - 3048 m
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Non-operating altitude	0 - 3048 m
Ports & interfaces		Technical details	
AC outlet types	C13 coupler, Type F	Sustainability certificates	Green Premium
Power plug	Type F	Weight & dimensions	
AC outlets quantity	6 AC outlet(s)	Width	104.1 mm
USB port	✓	Depth	408.9 mm
Serial interface type	RJ-45	Height	292.1 mm
Cabling technology	10/100/1000Base-T(X)	Weight	12.3 kg
		Package width	355 mm

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Package depth	480 mm
Battery voltage	24 V	Package height	155 mm
Number of batteries supported	1	Package weight	14.5 kg
		Packaging data	
		Cables included	USB cable
		Manual	✓



0731304634768



731304634768

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.