



TP-Link Omada ER706W-4G langaton reititin Gigabitti Ethernet Kaksitaajuus (2,4 GHz/5 GHz) musta

Tuotemerkki : TP-Link

Tuoteperhe: Omada

Tuotekoodi: ER706W-4G

Tuotteen nimi : ER706W-4G



TP-Link Omada ER706W-4G. Wi-Fi-taajuus: Kaksitaajuus (2,4 GHz/5 GHz), Wi-Fi-standardi: Wi-Fi 6 (802.11ax), WLAN-tiedonsiirtonopeus (maks.): 2402 Mbit/s. Ethernet LAN -käyttöliittymän tyyppi: Gigabitti Ethernet. Mobiiliverkon sukupolvi: 4G, 3G-standardit: HSDPA, HSUPA, WCDMA, 4G-standardit: LTE-TDD & LTE-FDD. NAT-toiminnallisuus: • One-to-One NAT • Multi-Net NAT • Virtual Server • Port Triggering† • NAT-DMZ •.... Tuotetyyppi: Pöytä-/tolppareititin, Tuotteen väri: musta, LED-merkkivalot: LAN, LTE, Tila, Järjestelmä, WAN



WAN connection		Security	
Ethernet WAN *	✓	URL filtering	✓
DSL WAN *	✗	Network address translation (NAT)	✓
SIM card slot *	✓	NAT functionality	• One-to-One NAT • Multi-Net NAT • Virtual Server • Port Triggering† • NAT-DMZ • FTP/H.323/SIP/IPSec/PPTP ALG • UPnP
3G/4G USB modem compatibility *	✗		
Wireless LAN features		Protocols	
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	DHCP server	✓
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)		
WLAN data transfer rate (max) *	2402 Mbit/s	Design	
Network		Product colour	Black
Ethernet LAN *	✓	LED indicators	LAN, LTE, Status, System, WAN
Ethernet LAN interface type *	Gigabit Ethernet	Product type *	Desktop/pole router
Dynamic DNS (DDNS)	✓	Antenna	
VPN Passthrough	✓	Antenna design *	External
Mobile network		Antennas quantity	5
Mobile network generation	4G	Features	
3G standards	HSDPA, HSUPA, WCDMA	Internal memory	512 MB
4G standard	LTE-TDD & LTE-FDD	Internal memory type	DDR4
4G bands supported	800,850,900,1800,2100,2300,2500,2600 MHz	Flash memory	128 MB
SIM card type	NanoSIM	Power	
Ports & interfaces		Power source type *	AC
Ethernet LAN (RJ-45) ports *	5	Operational conditions	
USB port *	✗	Operating temperature (T-T)	0 - 40 °C
Management features		Storage temperature (T-T)	-40 - 70 °C
Bandwidth control	✓	Operating relative humidity (H-H)	10 - 90%
Reset button	✓	Storage relative humidity (H-H)	5 - 90%

Management features		Weight & dimensions	
MU-MIMO technology	✓	Width	226 mm
MIMO	✓	Depth	131 mm
Security		Height	35 mm
Access Control List (ACL)	✓		



4895252500721



4895252500714



0840030705267



840030705267

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.