## QNAP

## QNAP TBS-H574TX-I3-12G NAS- ja tallennuspalvelimet Intel® Core™ i3 i3-1320PE 12 GB

7 7 7

Tuotemerkki: QNAP Tuotekoodi: TBS-H574TX-I3-12G

Tuotteen nimi: TBS-H574TX-I3-12G

QNAP TBS-H574TX-I3-12G. Malli: NAS, Laitteen luokka: Pienet & Keskikokoiset Yritykset. Suoritinperhe: Intel® Core™ i3, Prosessorimalli: i3-1320PE. Sisäinen muisti: 12 GB

| Storage   |   | Ports & interfaces   |                                      |
|---|---|--|--------------------------------------|
| Storage drive interface *  Hot-swap drive bays  Storage drives installed *  Installed storage drive type *  | M.2<br>✓  X                             | HDMI ports quantity HDMI version Ethernet LAN (RJ-45) ports * Thunderbolt ports quantity | 1<br>1.4b<br>2<br>2                  |
| Supported storage drive types *   | HDD & SSD                               | Design   |                                      |
| Processor   |   | LED indicators   | Status, USB                          |
| Processor manufacturer * Intel  Processor family * Intel® Core™ i3  Processor model * i3-1320PE  Processor boost frequency 4.5 GHz  Processor cores 8  Processor threads 12 | Intel® Core™ i3<br>i3-1320PE<br>4.5 GHz | Performance Type * Device class * Buzzer Reset button                                    | NAS<br>Small & Medium Business       |
| On-board graphics card model  | Intel® UHD Graphics                     | Power  |                                      |
| Memory  | 12 GB                                   | Power supply unit (PSU) capacity Power consumption (typical)                             | 120 W<br>46 W                        |
| Internal memory * Flash memory  | 5000 MB                                 | Weight & dimensions  |                                      |
| Network  Ethernet LAN *  Ethernet LAN data rates  | ✓<br>100,1000,2500,10000 Mbit/s         | Width * Depth * Height * Weight  | 215 mm<br>199 mm<br>60 mm<br>2.24 kg |
| Jumbo frames support  | ✓                                       | Operational conditions   |                                      |
| Ports & interfaces  USB port *  USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity   | <b>√</b><br>2                           | Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T)  | 0 - 40 °C<br>5 - 95%<br>-20 - 70 °C  |





4711103084694

4711103084526

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.