



ATEN VE883AK2-AT-G AV-signaalin jatkaja AV-lähetin ja -vastaanotin musta

Tuotemerkki : ATEN

Tuotekoodi: VE883AK2-AT-G

Tuotteen nimi : VE883AK2-AT-G

ATEN VE883AK2-AT-G. Malli: AV-lähetin ja -vastaanotin, Enimmäiserottelutarkkuus: 4096 x 2160 pikseliä, Tuetut kaapelityypit: Kuitu. Yhteysteknologia: Langallinen, Valokuituliitin: LC, USB-liitin: Micro-USB B. Käyttöjännite: 5 V, Tehonkulutus (lähetin) (max): 7,01 W, Tehonkulutus (vastaanotin) (max): 6,5 W. Vastaanottimen mitat (L x S x K): 146,9 x 169,4 x 30 mm, Vastaanottimen paino: 660 g, Lähettimen mitat (LxSxK): 146,9 x 169,4 x 30 mm. Pakkauksen leveys: 116 mm, Pakkauksen syvyys: 540 mm, Pakkauksen korkeus: 233 mm



Features		Power	
Type *	AV transmitter & receiver	Operating voltage	5 V
Maximum resolution *	4096 x 2160 pixels	Power consumption (transmitter) (max)	7.01 W
Cable types supported	Fiber	Power consumption (receiver) (max)	6.5 W
Maximum transfer distance	10000 m	Operational conditions	
Fiber optic wavelengths supported	1310 nm	Operating temperature (T-T)	0 - 40 °C
Fiber mode structure	Single-mode	Storage temperature (T-T)	-20 - 60 °C
Bidirectional	✓	Operating relative humidity (H-H)	0 - 80%
Electrostatic Discharge (ESD) protection	✓	Weight & dimensions	
Electrostatic Discharge (ESD) protection	15 kV	Receiver dimensions (WxDxH)	146.9 x 169.4 x 30 mm
LED indicators	✓	Receiver weight	660 g
Supported graphics resolutions	3840 x 2160, 4096 x 2160	Transmitter dimensions (WxDxH)	146.9 x 169.4 x 30 mm
Bandwidth	10.2 Gbit/s	Transmitter weight	670 g
Bandwidth	340 MHz	Packaging data	
HDCP	✓	Package width	116 mm
Material	Metal	Package depth	540 mm
3D	✓	Package height	233 mm
Firmware upgradeable	✓	Package weight	2.73 kg
Plug and Play	✓	Packaging content	
HDCP version	2.2	AC adapter included	✓
Product colour	Black	Cables included	USB
Ports & interfaces		IR emitter included	✓
Connectivity technology *	Wired	IR receiver included	✓
Ethernet LAN	✓	Technical details	
RJ-45 input ports	1	Country of origin	Taiwan
RJ-45 output ports	1	Compliance certificates	RoHS
HDMI in	1	Logistics data	
Number of HDMI outputs	1	Harmonized System (HS) code	85176200
Fiber optic connector	LC	Master (outer) case width	375 mm
USB ports quantity	1	Master (outer) case length	565 mm
USB version	2.0	Master (outer) case height	258 mm
USB connector type	Micro-USB B	Master (outer) case gross weight	8.83 kg
DC-in jack	✓		



4710469348761

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date