QNAP

QNAP TS-863XU-RP NAS Rack (2U) AMD G GX-420MC 4 GB DDR3L 0 TB QNAP Turbo System Black

Brand : QNAP **Product code:** TS-863XU-RP-4G

Product name: TS-863XU-RP

- $\ \ \text{Built-in single-port 10GbE 10GBASE-T NIC to accelerate virtualization and high-resolution video editing and sharing}$
- Qtier auto-tiering technology and SSD caching enable constant storage optimization
- Snapshots fully record system status and data, and assist in quick data recovery and mitigating the threat of ransomware attacks
- Host containerized applications and virtual machines with various operating systems
- Secure private cloud supporting centralized storage, backup, sharing, and disaster recovery
- NAS and iSCSI-SAN (IP-SAN) unified storage solution with scalable design

Copper ethernet cabling technology 10GBASE-T, 1000BASE-T

AMD G-Series GX-420MC 2.0 GHz, 4 GB DDR3L, 512MB DOM, 8x 2.5"/3.5" SATA III, 2x USB 3.0, 2x USB 2.0, 1x PCIe 2.0 x4, 1x RJ-45 10GBASE-T, 4x 1G RJ-45, 2U, 89x482x534 mm



	100	*	
9		*	
	 **		· M · · · ·

Storage		Design				
Storage drive capacity *	0 GB	Cable lock slot	✓			
Supported storage drive interfaces	Serial ATA III 2.5,3.5" ✓ 0, 1, 5, 6, 10, 50, 60, JBOD	Cable lock slot type	Kensington			
Storage drive sizes supported		Performance				
RAID support * RAID levels		Type * Device class *	NAS Small & Medium Business			
Online RAID migration Online RAID expansion Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives supported *	FAT32, HFS+, NTFS, ext3, ext4 O TB	Backup function * Backup features Buzzer Multilingual support Noise level Web-based management Share folder access right management	Cloud, iSCSI LUN			
Installed storage drive type * Supported storage drive types * Bad block scan	rted storage drive types * HDD & SSD ock scan		256-bit AES, FIPS 140-2, HTTPS, SSH, SSL/TLS			
Processor		Reset button	✓			
Processor family * Processor model * Processor frequency * Processor cores	AMD G GX-420MC 2 GHz 4	On/off switch Browser supported System log	Safari 7+, Chrome, Internet Explorer 10+, Firefox			
Memory		Hot spare	✓			
Internal memory * Internal memory type Maximum RAM supported	4 GB DDR3L 16 GB	S.M.A.R.T. support Share folder Universal Plug and Play (UPnP)	CIFS/SMB			
Memory slots	2	Software				
Memory form factor Flash memory	SO-DIMM 512 MB	Operating system installed * Operating system version	QNAP Turbo System 4.3.4			
Network		Windows operating systems	Windows 10, Windows 7, Windows			
Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max)	10,100,1000,10000 Mbit/s 10000 Mbit/s	supported Linux operating systems supported Mac compatibility	✓ ✓			
	400D465 T 4000D465 T					

Network		Software			
Wi-Fi DHCP server Jumbo frames support iSCSI support Wake-on-LAN ready Supported network protocols	X ✓ ✓ PPTP, L2TP/IPSec, OpenVPN VPN	Mac operating systems supported Server operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2,		
Ports & interfaces			Windows Server 2016		
USB port *	✓	Power			
USB 2.0 ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity Ethernet LAN (RJ-45) ports *	2 2 5	Power supply location Power supply unit (PSU) capacity Number of power supply units Power consumption (typical)	Built-in 250 W 2 107.3 W		
Design		Power consumption (HDD standby)	51.29 W		
Chassis type * Cooling type *	Rack (2U) Active Black 2 fan(s) 7 cm HDD, LAN, USB	AC input voltage Fan voltage	100 - 240 V 12 V		
Product colour		Weight & dimensions			
Number of fans Fan diameter LED indicators		Width * Depth * Height * Weight Package weight	482 mm 534 mm 89 mm 12.6 kg 14.8 kg		
		Packaging content			
		Cables included Quick installation guide	AC, LAN (RJ-45) ✓		
		Operational conditions			
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%		



4713213512777

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.