

Lenovo ThinkSystem SR630 V2 server Rack (1U) Intel Xeon Silver 4309Y 2.8 GHz 32 GB DDR4-SDRAM 750 W

Brand : Lenovo Product family: ThinkSystem Product code: 7Z71A07JEA

Product name: SR630 V2

- No OS
- Intel Xeon Silver 4309Y (12MB Cache, 2.8GHz)
- 32GB (3200MHz) DDR4-SDRAM (1 x 32)

Intel Xeon Silver 4309Y (12MB Cache, 2.8GHz), 32GB DDR4-SDRAM (3200MHz), LAN, 750W, No OS

Lenovo ThinkSystem SR630 V2 server Rack (1U) Intel Xeon Silver 4309Y 2.8 GHz 32 GB DDR4-SDRAM 750 W:

Built for business, with business-critical versatility

The versatile, highly reliable 1U ThinkSystem SR630 V2 2P rack server is designed to handle hybrid data center workloads, from IT infrastructure and HPC to cloud and hyperconverged. Lenovo ThinkSystem SR630 V2. Processor family: Intel Xeon Silver, Processor frequency: 2.8 GHz, Processor model: 4309Y. Internal memory: 32 GB, Internal memory type: DDR4-SDRAM, Memory layout (slots x size): 1 x 32 GB. Ethernet LAN. Power supply: 750 W, Redundant power supply (RPS) support. Chassis type: Rack (1U)

Processor		Design	
Processor manufacturer * Processor family * Processor model * Processor frequency * Processor boost frequency Processor cache Number of processors installed Maximum number of SMP processors	Intel Intel Xeon Silver 4309Y 2.8 GHz 3.6 GHz 12 MB 1	Redundant fans support	✓
		Performance	
		Performance management Noise level BIOS type Trusted Platform Module (TPM) Trusted Platform Module (TPM) version	XClarity Enterprise 56 dB UEFI ✓ 2.0
Memory		Software	
Internal memory * Internal memory type * Memory slots	32 GB DDR4-SDRAM 32x DIMM	Operating system installed * Compatible operating systems *	Microsoft Windows Server 2016 Microsoft Windows Server 2019 Microsoft Windows Server 2022 Red Hat Enterprise Linux 7.9 Red Hat Enterprise Linux 8.2 Red Hat Enterprise Linux 8.3 SUSE Linux Enterprise Server 12 SP5 SUSE Linux Enterprise Server 12 Xen SP5 SUSE Linux Enterprise Server 15 SP2 SUSE Linux Enterprise Server 15 Xen SP2 VMware ESXi 6.7 U3 VMware ESXi 7.0 U2
ECC Memory clock speed Memory layout (slots x size)	3200 MHz 1 x 32 GB		
Storage			
Optical drive type * Internal drive bays	4		
Graphics		Power	
Maximum graphics card memory	16 MB	Redundant power supply (RPS)	/
Network		support *	
Wake-on-LAN ready	✓	Power supply * Number of redundant power	750 W
Ethernet LAN	✓	supplies supported	2
Ports & interfaces		Number of redundant power supplies installed	1
USB 2.0 ports quantity	1	Operational conditions	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	Storage temperature (T-T)	-40 - 60 °C
VGA (D-Sub) ports quantity	1	Storage relative humidity (H-H)	8 - 90%
Design		Weight & dimensions	
Chassis type * Product colour Rack mounting	Rack (1U) Black ✓	Width Depth Height	440 mm 773 mm 43 mm

