

**Lenovo**

## Lenovo ThinkSystem SR630 V2 palvelin Teline ( 1U ) Intel® Xeon Silver 4309Y 2,8 GHz 32 GB DDR4-SDRAM 750 W

**Tuotemerkki** : Lenovo**Tuoteperhe**: ThinkSystem**Tuotekoodi**: 7Z71A07JEA**Tuotteen nimi** : SR630 V2

Lenovo ThinkSystem SR630 V2. Suoritinperhe: Intel® Xeon Silver, Prosessorin taajuus: 2,8 GHz, Prosessorimalli: 4309Y. Sisäinen muisti: 32 GB, Sisäisen muistin tyyppi: DDR4-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 32 GB. Ethernet LAN. Virtalähde: 750 W, Vikasietoisen virtalähteen tuki (RPS). Alustatyyppi: Teline ( 1U )

Processor		Design	
Processor manufacturer *	Intel	Redundant fans support	✓
Processor family *	Intel Xeon Silver	<b>Performance</b>	
Processor model *	4309Y	Performance management	XClarity Enterprise
Processor frequency *	2.8 GHz	Noise level	56 dB
Processor boost frequency	3.6 GHz	BIOS type	UEFI
Processor cache	12 MB	Trusted Platform Module (TPM)	✓
Number of processors installed	1	Trusted Platform Module (TPM) version	2.0
Maximum number of SMP processors	2	<b>Software</b>	
<b>Memory</b>		Operating system installed *	✗
Internal memory *	32 GB	Microsoft Windows Server 2016	
Internal memory type *	DDR4-SDRAM	Microsoft Windows Server 2019	
Memory slots	32x DIMM	Microsoft Windows Server 2022 Red Hat Enterprise Linux 7.9 Red Hat Enterprise Linux 8.2 Red Hat Enterprise Linux 8.3 SUSE Linux Enterprise Server 12 Xen SP5 SUSE Linux Enterprise Server 12 Xen SP5 SUSE Linux Enterprise Server 15 SP2 SUSE Linux Enterprise Server 15 Xen SP2 VMware ESXi 6.7 U3 VMware ESXi 7.0 U2	
ECC	✓	Compatible operating systems *	
Memory clock speed	3200 MHz		
Memory layout (slots x size)	1 x 32 GB		
<b>Storage</b>			
Optical drive type *	✗		
Internal drive bays	4		
<b>Graphics</b>		<b>Power</b>	
Maximum graphics card memory	16 MB	Redundant power supply (RPS) support *	✓
<b>Network</b>		Power supply *	750 W
Wake-on-LAN ready	✓	Number of redundant power supplies supported	2
Ethernet LAN	✓	Number of redundant power supplies installed	1
<b>Ports &amp; interfaces</b>		<b>Operational conditions</b>	
USB 2.0 ports quantity	1	Storage temperature (T-T)	-40 - 60 °C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	Storage relative humidity (H-H)	8 - 90%
VGA (D-Sub) ports quantity	1	<b>Weight &amp; dimensions</b>	
<b>Design</b>		Width	440 mm
Chassis type *	Rack (1U)	Depth	773 mm
Product colour	Black	Height	43 mm
Rack mounting	✓		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-DEC-2024. Prints or copies of Information are only valid on the printed Publication date