



# Lindy 43381 USB cable USB 3.2 Gen 1 (3.1 Gen 1) 8 m USB C USB A Black, Blue

**Brand :** Lindy

**Product code:** 43381

**Product name :** 43381

- High performance, active cable that provides an extended 8m connection between a computer with USB Type C port and a USB Type A device
- Can be used standalone or as part of the Lindy Active Extension System Pro to create bespoke extension systems of over 40m (depending on the cables used)
- Supports the full USB 3.2 / 3.1 Gen 1 / USB 3.0 SuperSpeed bandwidth for speeds of 5Gbps
- USB Power Adapter cable included

8m USB 3.2 Gen 1 C/A Active Extension Pro

Lindy 43381. Cable length: 8 m. Connector 1: USB C, Connector 2: USB A, USB version: USB 3.2 Gen 1 (3.1 Gen 1), Maximum data transfer rate: 5 Gbit/s, Connector contacts plating: Nickel/Gold, Product colour: Black, Blue



Features		Weight & dimensions	
USB version *	USB 3.2 Gen 1 (3.1 Gen 1)	Cable length *	8 m
Connector 1 *	USB C	Cable diameter	7 mm
Connector 2 *	USB A	Weight	630 g
Connector 1 gender *	Male	Bend radius (min)	7 cm
Connector 2 gender *	Female	Connector 1 dimensions (WxDxH)	14 x 43.65 x 11.2 mm
Connector 1 form factor	Straight	Connector 2 dimensions (WxDxH)	20 x 80 x 13 mm
Connector 2 form factor	Straight	<b>Packaging data</b>	
AWG wire size	24/24/20	Package type	Box
Connector contacts plating	Nickel/Gold	Package width	230 mm
Cable jacket material	Polyvinyl chloride (PVC)	Package depth	198 mm
Conductor material	Tinned copper	Package height	63 mm
Maximum data transfer rate	5000 Mbit/s	Package weight	830 g
Maximum data transfer rate	5 Gbit/s	<b>Packaging content</b>	
Product colour *	Black, Blue	Quantity per pack *	1 pc(s)
Cable type	Round cable	<b>Sustainability</b>	
Nominal attenuation	0.064MHz - <0.08dB	Sustainability compliance	✓
	0.256MHz - <0.13dB	<b>Operational conditions</b>	
	0.772MHz - <0.15dB	Operating temperature (T-T)	0 - 50 °C
	1.0MHz - <0.20dB	Storage temperature (T-T)	-20 - 60 °C
	4MHz - <0.39dB	<b>Other features</b>	
8MHz - <0.57dB	Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS	
12MHz - <0.67dB			
24MHz - <0.95dB			
48MHz - <1.35dB			
96MHz - <1.90dB			
200MHz - <3.20dB			
400MHz - <5.80dB			
<b>Power</b>			
Power note	2.5/0.7mm DC Connector		



4002888433815

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 30-SEP-2024. Prints or copies of Information are only valid on the printed Publication date