Canon

Canon i-SENSYS LBP712Cx Väri 9600 x 600 DPI A4

Tuotemerkki: Canon Tuoteperhe: i-SENSYS Tuotekoodi: 0656C001

Tuotteen nimi: LBP712Cx

Custom media length

Canon i-SENSYS LBP712Cx. Tulostustekniikka: Laser, Väri. Suurin toimintajakso: 80000 sivua kuukaudessa. Suurin resoluutio: 9600 x 600 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaalilaatu, A4/US Letter): 38 ppm, Kaksipuolinen tulostus. Näyttö: LCD, Tuotteen väri: musta, Valkoinen



	Network	
Auto	Ethernet LAN *	✓
600 x 600 DPI	Performance	
38 ppm	Internal memory *	1024 MB
✓	Built-in processor	✓
Laser	Processor frequency	528 MHz
✓		66 dB
9600 x 600 DPI	Sound power level (standby)	50 dB
38 ppm	Design	Dlack White
31 s		Black, White
5.1 s	, ,	✓
6 s	' '	LCD
5 mm	Display number of lines	5 lines
	Power	
V	Power consumption (printing) *	590 W
	Power consumption (max)	1470 W
80000 pages per month	• • • • • • • • • • • • • • • • • • • •	34 W
2000 - 7500 pages per month	1 , ,	0.16 W
Black, Cyan, Magenta, Yellow		1.4 kWh/week
PostScript, PCL 5c, PCL 6, UFRII-LT	•	220 - 240 V
	AC input frequency	50 - 60 Hz
550 sheets		
200 sheets		
Cassette, Paper tray		
✓		
100 sheets		
A4		
216 x 356 mm		
Postcard, Envelopes, Heavy paper, Labels, Plain paper, Recycled paper, Rough paper		
A4, A5		
B5		
16K, Executive, Letter, Statement		
101.6 - 215.9 mm		
	600 x 600 DPI 38 ppm Laser 9600 x 600 DPI 38 ppm 31 s 5.1 s 6 s 5 mm 80000 pages per month 2000 - 7500 pages per month Black, Cyan, Magenta, Yellow PostScript, PCL 5c, PCL 6, UFRII-LT 550 sheets 200 sheets Cassette, Paper tray 100 sheets A4 216 x 356 mm Postcard, Envelopes, Heavy paper, Labels, Plain paper, Recycled paper, Rough paper A4, A5 B5 16K, Executive, Letter, Statement	Auto 600 x 600 DPI 38 ppm Internal memory * Internal memory * Built-in processor Laser Processor frequency Sound pressure level (printing) Sound power level (standby) Built-in display Sound pressure level (printing) Sound power level (standby) Besign Product colour * Built-in display * Display Display Display Display Display number of lines Power Power Power consumption (printing) * Power consumption (max) Power consumption (froft) Energy Star Typical Electricity Consumption (TEC) AC input voltage AC input frequency AA 216 x 356 mm Postcard, Envelopes, Heavy paper, Labels, Plain paper, Recycled paper, Rough paper A4, A5 B5 16K, Executive, Letter, Statement

148 - 355.6 mm

Paper handling		System requirements	
Paper tray media weight	60 - 163 g/m ²	Windows operating systems supported	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8 Enterprise, Windows 8 Enterprise, Windows 8 Enterprise, Windows 8 Fro, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Pro, Windows 8.1 Pro, Windows Vista Business, Windows Vista Business, Windows Vista Enterprise x64, Windows Vista Home Basic x64, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate
Multi-Purpose Tray media weight	60 - 216 g/m ²		
Ports & interfaces			
	Ethernet, USB 2.0		
		Mac operating systems supported	x64 Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
		Linux operating systems supported	✓
	Server operating systems supported	Windows Server 2003, Windows Server 2003 R2, Windows Server 2003 x64, Windows Server 2008, Windows Server 2008 R2, Windows Server 2008 R2 x64, Windows Server 2008 x64, Windows Server 2012, Windows Server 2012 R2, Windows Server 2012 R2 x64, Windows Server 2012 x64	
		Operational conditions	
		Operating temperature (T-T)	10 - 30 °C
		Operating relative humidity (H-H)	20 - 80%
		Weight & dimensions	
		Width	458 mm
		Depth	464 mm
		Height	388 mm
		Weight	28.8 kg
		Packaging content	
	Cables included Bundled software	AC Remote User Interface (RUI), Department ID Management, Toner Status Tool, iW Management Console, eMaintenance, uniFLOW	
			compatibility with uniFLOW Login Device Client for SFP MEAP
		Logistics data	
		Harmonized System (HS) code	84433210





4549292041033

4058154163672

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.