Canon

Canon i-SENSYS LBP351x 1200 x 1200 DPI A4

Tuotemerkki : Canon Tuoteperhe: i-SENSYS Tuotekoodi: 0562C003

Tuotteen nimi: LBP351x

Canon i-SENSYS LBP351x. Tulostustekniikka: Laser. Värikasettien määrä: 1, Suurin toimintajakso: 250000 sivua kuukaudessa. Suurin resoluutio: 1200 x 1200 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaalilaatu, A4/US Letter): 55 ppm, Kaksipuolinen tulostus. Näyttö: LCD, Tuotteen väri: musta, Valkoinen





Printing		Network	
Duplex printing mode	Auto	Wi-Fi *	×
Colour *	×	Ethernet LAN *	✓
Print technology *	Laser	Web-based management	✓
Duplex printing * Maximum resolution * Print speed (black, normal quality,	✓ 1200 x 1200 DPI	Mobile printing technologies	Apple AirPrint, Canon PRINT Business, Google Cloud Print, Mopria Print Service
A4/US Letter) *	55 ppm	Performance	
Duplex print speed (black, normal quality, A4/US Letter)	36.5 ppm	Internal memory *	1024 MB
Warm-up time	29 s	Built-in processor	✓
Time to first page (black, normal)	7.2 s	Processor frequency	528 MHz
Print margins (top, bottom, right, left)	5 mm	Sound pressure level (printing)	71 dB
Secure printing	1	Design	
. 5	•	Product colour *	Black, White
Features		Built-in display *	✓
Maximum duty cycle *	250000 pages per month	Display	LCD
Recommended duty cycle	3000 - 16000 pages per month	Display number of lines	5 lines
Number of print cartridges * Page description languages *	1 PCL 5e, PCL 6, URF	Power	
Input & output capacity	1 02 30, 1 02 0, 0111	Power consumption (printing) *	800 W
	1	Power consumption (max)	1650 W
Total number of input trays * Total input capacity *	1 500 sheets	Power consumption (standby)	19 W
Total output capacity *	500 sheets	Power consumption (off) Energy Star Typical Electricity	0.17 W
Paper input type	Cassette, Paper tray	Consumption (TEC)	2.4 kWh/week
Multi-Purpose tray	✓	AC input voltage	220 - 240 V
Multi-Purpose tray input capacity	100 sheets	AC input frequency	50 - 60 Hz
Maximum number of input trays	4		
Paper handling			
Maximum ISO A-series paper size *	A4		
Paper tray media types *	Envelopes, Heavy paper, Labels, Plain paper		
ISO A-series sizes (A0A9) *	A4, A5, A6		
ISO B-series sizes (B0B9)	B5		
Non-ISO print media sizes	Index card		
Envelopes sizes	10, C5, DL, Monarch		

Paper handling		System requirements	
Custom media width Custom media length Paper tray media weight Multi-Purpose Tray media weight Duplex media weight	76 - 216 mm 127 - 356 mm 60 - 120 g/m ² 60 - 199 g/m ² 60 - 120 g/m ²	Windows operating systems supported	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8 Enterprise, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro, Windows 8.1 Pro, Windows 8.1 Pro, Windows Wista Business, Windows Vista Enterprise, Windows Vista Enterprise, Windows Vista Enterprise, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Premium, Windows Vista Ultimate, Windows Vista Ultimate, Windows Vista Ultimate, Windows Vista Ultimate x64
Ports & interfaces			
Standard interfaces Direct printing * USB 2.0 ports quantity	Ethernet, USB 2.0 1		
		Mac operating systems supported	Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
		Linux operating systems supported	✓
		Server operating systems supported	Windows Server 2003, Windows Server 2003 R2, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2
	Opera		
		Operating temperature (T-T)	10 - 30 °C
		Operating relative humidity (H-H)	20 - 80%
		Weight & dimensions	
		Width Depth	415 mm 529 mm
		Height	438 mm
		Weight	26.2 kg
		Logistics data	
		Harmonized System (HS) code	84433210
		Other features	
		Power LED	✓
		Print resolution	600 x 600 DPI



4549292051377

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.