

Canon M40 1200 x 1200 DPI

Tuotemerkki : Canon

Tuotekoodi: 2886V298

Tuotteen nimi : M40

Canon M40. Skannauksen enimmäiskoko: 1067 x 15000 mm, Optinen skannauserottelutarkkuus: 1200 x 1200 DPI, Tehostettu skannaustarkkuus: 1200 x 1200 DPI. Näyttö: TFT, Näytön halkaisija: 49,5 cm (19.5"). Anturin tyyppi: CIS, Tiedostomuodot (skanneri): JPG, PDF, TIFF, Sisäinen muisti: 4000 MB. USB-versio: 3.2 Gen 1 (3.1 Gen 1), Vakioliitännät: USB 3.2 Gen 1 (3.1 Gen 1). Virtalähteen tyyppi: AC, Virrankulutus: 40 W, Virrankulutus valmiustilassa: 0,3 W



| Scanning | | Power | |
|-----------------------------------|---------------------------|-------------------------------------|--|
| Maximum scan size * | 1067 x 15000 mm | Power supply type * | AC |
| Optical scanning resolution * | 1200 x 1200 DPI | Power consumption (typical) | 40 W |
| Enhanced scan resolution | 1200 x 1200 DPI | Power consumption (standby) | 0.3 W |
| Colour scanning | ✓ | AC input frequency | 50 - 60 Hz |
| Duplex scanning * | ✗ | Input voltage | 100-240 V |
| Input colour depth | 24 bit | Packaging content | |
| Film scanning | ✗ | Cables included | USB |
| Greyscale levels | 256 | Quick start guide | ✓ |
| Black/white scanning colour modes | Grayscale | Sustainability | |
| Design | | Sustainability certificates | ENERGY STAR |
| Display | TFT | System requirements | |
| Display diagonal | 49.5 cm (19.5") | Windows operating systems supported | Windows 7, Windows 8, Windows 8.1, Windows Vista, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64 |
| Touchscreen | ✓ | Mac operating systems supported | Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks |
| Performance | | Operational conditions | |
| Sensor type * | CIS | Operating temperature (T-T) | 10 - 35 °C |
| Scan file formats | JPG, PDF, TIFF | Operating relative humidity (H-H) | 35 - 80% |
| Internal memory | 4000 MB | Other features | |
| Built-in processor | ✓ | Compatibility | iPF770, iPF780, iPF785, iPF830, iPF840, iPF850 iPF8400SE |
| Processor frequency | 2.3 MHz | Compliance certificates | RoHS |
| Ports & interfaces | | Certification | CB, CE, FCC, UL |
| USB port * | ✓ | Technical details | |
| USB version | 3.2 Gen 1 (3.1 Gen 1) | Panel type | TFT |
| Standard interfaces | USB 3.2 Gen 1 (3.1 Gen 1) | | |



8714574631264

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.