## Canon i-SENSYS LBP664Cx Colour 1200 x 1200 DPI A4 Wi-Fi

Brand : Canon Product family: i-SENSYS Product code: 3103C001

**Product name:** LBP664Cx

LBP664Cx, A4, 27 ppm, 1200x1200 dpi, USB 2.0, Wi-Fi, LAN, 220-240V 50/60Hz, 476x469x379 mm

Canon i-SENSYS LBP664Cx Colour 1200 x 1200 DPI A4 Wi-Fi:

Optimised for small offices, the LBP664Cx is an ultra-fast, highly accurate, feature-packed colour laser printer with innovative functions like Universal Login Manager to help boost security and cost management.

Canon i-SENSYS LBP664Cx. Print technology: Laser, Colour. Maximum duty cycle: 50000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A4. Duplex printing. Display: LCD. Network ready, Wi-Fi. Product colour: Black, White

| Printing   |  | Network  |  |
|--|--|--|--|
| Duplex printing mode   | Auto   | Ethernet LAN data rates                              | 10,100,1000 Mbit/s   |
| Colour *   | ✓  | Wi-Fi Direct   | ✓  |
| Print technology *   | Laser  | Wi-Fi standards                                      | 802.11b, 802.11g, Wi-Fi 4 (802.11n)  |
| Duplex printing *  | ✓  | Near Field Communication (NFC)                       | ✓  |
| Maximum resolution * Warm-up time Time to first page (black, normal) | 1200 x 1200 DPI<br>13 s<br>7.7 s                                 | Mobile printing technologies                         | Apple AirPrint, Canon PRINT<br>Business, Google Cloud Print,<br>Mopria Print Service |
| Time to first page (colour, normal)                                  | 8.6 s  | Performance  |  |
| Print margins (top, bottom, right, left)                             | 5 mm   | Internal memory * Maximum internal memory            | 1000 MB<br>1000 MB   |
| Secure printing  | ✓  | Built-in processor                                   | <b>V</b>   |
| Features   |  | Processor frequency                                  | 800 MHz  |
| Maximum duty cycle *   | 50000 pages per month  | Processor cores                                      | 2  |
| Recommended duty cycle   | 750 - 4000 pages per month                                       | Sound pressure level (printing)                      | 63 dB  |
| Printing colours * Page description languages *                      | Black, Cyan, Magenta, Yellow<br>PCL 5c, PCL 6, PostScript, UFRII | Sound pressure level (duplex printing)               | 64 dB  |
| Number of printer fonts  | 229  | Sound power level (standby)                          | 42 dB  |
| Input & output capacity  |  | Design   |  |
|  | 250 shoots   | Market positioning *                                 | Home & office  |
| Total input capacity *  Total output capacity *                      | 250 sheets<br>150 sheets   | Product colour *                                     | Black, White   |
| Paper input type   | Cassette   | Built-in display *                                   | ✓  |
| Multi-Purpose tray   | ✓  | Display  | LCD  |
| Multi-Purpose tray input capacity                                    | 50 sheets  | Colour display                                       | ✓  |
| Maximum input capacity   | 550 sheets   | Touchscreen  | ✓  |
| Paper handling   |  | Control type   | Touch  |
|  | A4   | Power  |  |
| Maximum ISO A-series paper size *  Maximum print size                | 216 x 356 mm   | Power consumption (printing) *                       | 470 W  |
| Maximum print Size   | Envelopes, Glossy paper, Heavy                                   | Power consumption (max)                              | 1380 W   |
| Paper tray media types *   | paper, Labels, Plain paper, Postcard,                            | Power consumption (standby)                          | 17 W   |
| ISO A-series sizes (A0A9) *  | Recycled paper, Thin paper<br>A4, A5                             | Energy Star Typical Electricity<br>Consumption (TEC) | 1 kWh/week   |
| ISO B-series sizes (B0B9)  | B5   | AC input voltage                                     | 220 - 240 V  |
| Non-ISO print media sizes  | Executive, Legal, Letter, Statement                              | AC input frequency                                   | 50 - 60 Hz   |
| Envelopes sizes  | C5, Com-10, DL, Monarch  | System requirements                                  |  |
| Custom media width   | 100 - 216 mm   | Windows operating systems                            | Windows 10, Windows 7, Windows   |
| Custom media length  | 148 - 355.6 mm   | supported  | 8.1  |
| Paper tray media weight  | 60 - 163 g/m²  |  | Mac OS X 10.10 Yosemite, Mac OS X  |
| Multi-Purpose Tray media weight                                      | 60 - 176 g/m²  | Mac operating systems supported                      | 10.11 El Capitan, Mac OS X 10.12<br>Sierra, Mac OS X 10.13 High Sierra,              |
| Ports & interfaces   |  | speracing systems supported                          | Mac OS X 10.14 Mojave, Mac OS X  |
| Standard interfaces  | Ethernet, USB 2.0, Wireless LAN                                  |  | 10.9 Mavericks   |

| Ports & interfaces     |                      | System requirements               |  |
|------------------------|----------------------|-----------------------------------|--|
| USB 2.0 ports quantity | 1                    |                                   | Windows Server 2008, Windows<br>Server 2008 R2, Windows Server<br>2012, Windows Server 2012 R2,<br>Windows Server 2016 |
| Network                |                      | Server operating systems supporte |  |
| Network ready          | ✓                    |                                   |  |
| Wi-Fi *                | ✓                    | Operational conditions            |  |
| Ethernet LAN *         | ✓                    | Operating temperature (T-T)       | 10 - 30 °C   |
| Cabling technology     | 10/100/1000Base-T(X) | Operating relative humidity (H-H) | 20 - 80%   |
|                        |                      | Weight & dimensions               |  |
|                        |                      | Width                             | 476 mm   |
|                        |                      | Depth                             | 469 mm   |
|                        |                      | Height                            | 379 mm   |
|                        |                      | Weight                            | 21.2 kg  |



4549292121995

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.