

## LG 31HN713D-BA tietokoneen litteä näyttö 78,7 cm (31") 4200 x 2800 pikseliä LCD musta

Tuotemerkki : LG

Tuotekoodi: 31HN713D-BA

Tuotteen nimi : 31HN713D-BA

LG 31HN713D-BA. Näytön halkaisija: 78,7 cm (31"), Näytön erottelutarkkuus: 4200 x 2800 pikseliä, Näytön teknologia: LCD, Vasteaika (tyypillinen): 5 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäänrakennettu USB-keskus, USB-keskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys. Tuotteen väri: musta





RoHS, REACH, WEEE

## Display Ports & interfaces USB Type-A downstream ports Display diagonal \* 78.7 cm (31") 3 quantity Display resolution \* 4200 x 2800 pixels HDMI \* Native aspect ratio \* 16:9 LCD DisplayPorts quantity 2 Display technology \* DisplayPort version 1.2 IPS Panel type \* W-LED Backlight type Ergonomics Touchscreen \* X VESA mounting \* Display brightness (typical) 1080 cd/m<sup>2</sup> 200 x 100 mm Panel mounting interface Response time \* 5 ms On Screen Display (OSD) Anti-glare screen 1 Simplified Chinese, German, Flat Screen shape \* Spanish, Finnish, French, Greek, On Screen Display (OSD) languages Italian, Japanese, Polish, Contrast ratio (typical) \* 1500:1 Portuguese, Russian, SER, Ukrainian Viewing angle, horizontal 178° Number of OSD languages 14 Viewing angle, vertical 178° Plug and Play 1 16.7 million colours Display number of colours \* Digital vertical frequency 50 - 60 Hz Power Surface hardness ЗH Power consumption (standby) \* 0.3 W Colour gamut standard sRGB Power consumption (max) 180 W 97% Colour gamut AC input voltage 100 - 240 V sRGB coverage (typical) 97% AC input frequency 50 - 60 Hz Performance Weight & dimensions VESA Adaptive Sync support 1 Weight (without stand) 10.7 kg Design Packaging data Market positioning \* Medical Package weight 14 kg Product colour \* Black Packaging content Colour name Black Cables included AC, DisplayPort, HDMI Ports & interfaces Bundled software Tru Color Pro software Built-in USB hub \* 1 Other features USB hub version 3.2 Gen 1 (3.1 Gen 1) IEC60601-1 / IEC60601-1-1-2, FCC Number of upstream ports 1 Part 15 Class 1, EN606011-1 / Certification EN606601-1-2, IEC60950-1 / IEC55032,55024, cUL, FDA Class II,

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.